



PM/T1 and PM/E1 Technical Specs

PowerQUICC Architecture

- Processor Configuration
 - MPC860MH: Up to 2 channelized T1 or E1 spans
- Dual processor architecture
 - RISC-based Communications Processor Module handles communication commands
 - 32-bit Embedded PowerPC core with MMU and 4 Kbyte data and instruction caches
- 40 MHz clock
- On-chip timers (configurable as four 16-bit timers or two 32-bit timers)
- 16 serial DMA channels

Memory Configurations

- 4, 8, 16 MBytes DRAM
- PROM: 512 KBytes capacity
- NVRAM
 - 2 KBytes capacity
 - Storage for user-defined parameters such as baud rates, software and hardware revision levels, and configuration information
 - Provides field upgradeable non-volatile program storage

Configuration Options

- Choice of T1 or E1
- Choice of front panel or P14 I/O for T1/E1
- 1 EIA-422/2 EIA-232/1 E1 span configurations available
- 4 or 8 MBytes memory

Serial Communication Ports

- Up to 1 full T1 or E1 span or 2 fractional T1 or E1 spans
- Configuration available with 1 EIA-422 port and 1 E1 span featuring rear I/O
- Surge protection for T1/E1 ports with front panel I/O
- Supports T1/CEPT and other user-defined protocols (customer provided software may be required)
- Automatically performs efficient packing
- I/O routed out PMC P14 connector or front panel for T1 and E1 interfaces
- Two serial EIA-232 ports Provided for console/debug capability using the P2 connector
- I/O routed through PMC P14 connector

PMC Architecture

- Standard single-width 32-bit PMC module conforms to IEEE P1386.1
 - PCI 2.1-compliant interface
-

Software Support

- Board support package for VxWorks real-time operating system
 - HKmon monitor software
 - Future pSOS Board Support Package
 - SS-7 Message Transfer Part (MTP) levels 1 & 2
 - HDLC LAPB/LAPD
 - HDLC LAPF (Q.922)
-

Physical Characteristics

- Board size: 149.0 mm x 74.0 mm (5.87 in. x 2.91 in.)
 - Baseboard and module fit in a single 0.8 in. VMEbus slot
 - Power requirements:
 - +5VDC @ 1.4 A maximum
 - +12VDC @ 0.2A maximum (RS422 option)
 - -12VDC @ 0.2A maximum (RS422 option)
 - Storage Temperature: -25C to 70C
 - Operating range: 0-55C, 95% relative humidity (non-condensing)
-

Target Applications

- SS7 Link
 - T1/E1 interfaces for systems such as
 - Signal Switching Point (SSP)
 - Intelligent Peripheral (IP)
 - Wide Area Data Communication
 - Base Station Controller (BSC)
 - Broadband Transceiver Station (BTS)
-

Click [here](#) to return to product menu.

Click [here](#) to return to main-level PM/T1 and PM/E1 page.



**Heurikon
Home Page**



**Information
Search**



**For More
Information**

Would you like [more information](#) on Heurikon's products and services?
Do you have [Questions](#), [comments](#), or [problems](#) regarding this service?

webmaster@heurikon.com

Copyright © 1994, 1995, 1996 Heurikon Corporation. All rights reserved.

Certain names, logos, designs, titles, words or phrases on this page may constitute trademarks, servicemarks, or tradenames of Heurikon Corporation or other entities which may be registered in certain jurisdictions.