



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com



LIGHT SOURCES: Products

Intralux® 4100

- **Light adjustment: Crescent shaped diaphragm (Volpi Patent) and electronic**
- Illumination intensity at 100% voltage at lightguide input approx. 6,8 Mio. Lux
- Lamplife (Ø in continuous operation) 1500h
- Constant color temperature
- Homogeneous illuminated lightguide-Ø 10mm
- Halogen Reflector Lamp 12V/100W
- Power consumption 110W
- Temperature range: 5 - 40°C
- Weight 3 kg
- Housing Metal, powder coated, color RAL 9004
- Dims. (HxWxD): 215x120x200mm

Art. No.	Description
10435.000	Intralux 4100 EURO 230 / 240 V
10439.000	Intralux 4100 CH 230 / 240 V



Intralux® 5100

- **Light adjustment: Crescent shaped diaphragm (Volpi Patent) and electric 8-step switch**
- Illumination intensity at 110% at lightguide input approx. 12,3 Mio. Lux
- Lamplife (Ø in continuous operation at 85% intensity) 900h
- Constant color temperature
- Homogeneous illuminated lightguide-Ø 13mm
- Halogen Reflector Lamp 21V/150W
- Power consumption 190W
- Temperature range: 5 - 40°C
- Weight 4,6 kg
- Housing Metal, powder coated, color RAL 9004
- Dims. (HxWxD): 215x120x200mm

Art. No.	Description
10437.000	Intralux 5100 EURO 230 / 240 V
10440.000	Intralux 5100 CH 230 / 240 V
10438.000	Intralux 5100 USA 121 V
10438.000	Intralux 5100 JAPAN 100 V





Intralux® 6100

- **LCD display: Intensity, Color temperature, Position of diaphragm**
- **Electronic lightstabilizing by microcontroller**
- **RS 232 Interface, bidirectional**
- **Autom. recognition of daylightfilter use**
- **Light adjustment: Crescent shaped diaphragm (Volpi Patent) and electronic**
- Illumination intensity at 110% voltage at lightguide input approx. 12,3 Mio. Lux
- Lamplife (Ø in continuous operation) 200h - 3200h
- Homogeneous illuminated lightguide-Ø 13mm
- Halogen Reflector Lamp 21V/150W
- Power consumption 200W
- Temperature range: 5 - 40°C
- Weight 5kg
- Housing Metal, powder coated, color RAL 9004
- Dimensions (HxWxD): 215x120x200mm



Art. No.	Description
10445.000	Intralux 6100 EURO 230 V
10446.000	Intralux 6100 CH 230 V
10448.000	Intralux 6100 USA / JAPAN 115 V
10462.000	Converter RS 232 - USB, cable length 350mm

Intralux® DC1100

- 150W Halogen Reflector Lamp
- **Stabilized DC Lamp voltage**
- Light adjustment:
 - RS232 serial port
 - Manual Voltage intensity control (front)
 - Crescent shaped diaphragm (Volpi Patent)
- Lamplife (Ø in continuous operation) approx. 200-4000h
- Dimensions (HxWxD): 110x220x220 mm



Art. No.	Description
16605.000	DC stabilized Intralux DC1100
16612.000	DC Light Source Intralux DC1100 Sensor
16614.000	DC Light Source Intralux DC1100 Analog Entry
16616.000	DC Light Source Intralux DC1100 Filter-Holder
16617.000	DC Light Source Intralux DC1100 Kondensator 24V
16618.000	DC Light Source Intralux DC1100 Shutter
16621.000	DC Light Source Intralux DC1100 Universal
16621.410	Universal-Adapter to Intralux DC1100 Universal
16621.420	FOSTEC-Adapter to Intralux DC1100 Universal
16621.430	IT-Adapter to Intralux DC1100
16430.000	IT-, SY-, DJ-Adapter to Intralux DC1100

Intralux® 4000-1 ESD

- Illumination intensity at 100% voltage at lightguide output approx. 3,5 Mio. Lux
- Lamplife (Ø in continuous operation) 1000h
- Constant color temperature
- Homogeneous illuminated lightguide-Ø 10mm
- Light adjustment: Crescent shaped diaphragm (Volpi Patent)
- Multi-mirror halogen lamp: 14,5V/90W
- Power consumption 120W
- Noise level 25dB (A), Housing temperature max. 38°C
- Protection class 1, Weight 4.5kg, Housing: metal, light grey
- Dimensions (HxWxD): 105x169x237mm
- ESD Version (Electro Static Discharge)



Art. No.	Description
10296.000	Intralux 4000-1 EURO 230V ESD Frequenz 50/60 Hz
10292.000	Intralux 4000-1 CH 230V ESD Frequenz 50/60 Hz
10298.000	Intralux 4000-1 USA 120V ESD Frequenz 50/60 Hz





Intralux® IK-1

- Halogen lamp 24V/150W
- Lamplife (\emptyset in continuous operation) approx. 1500h
- Light adjustment: Crescent shaped diaphragm (Volpi Patent)
- Constant color temperature 3200°K
- Homogeneous illuminated fiber bundle- \emptyset 8mm
- Internal color filter holder (optional)
- Dimensions (HxWxD): 110x220x220mm



Art. No.	Description
16630.000	Intralux IK1 AC EURO 230V

Intralux® 20HE

- Halogen lamp 12V/20W
- Electronic power supply
- Homogeneous illuminated fiber bundle- \emptyset 5mm
- Fan
- Dimensions (HxWxD): 75x100x170mm



Art. No.	Description
10104.000	Intralux 20 HE EURO (2P+E) 230V
27924.000	Intralux 20 HE CH (2P+E) 230V
27925.000	Intralux 20 HE USA (2P+E) 121V

Intralux® 9000

- 150W Metal Halid Lamp
- Lamplife (\emptyset in continuous operation) 9000h
- Color temperature 5700°K
- Homogeneous illuminated fiber bundle- \emptyset 25mm
- Light adjustment:
 - RS232 serial interface
 - Crescent shaped diaphragm
- Input power: 85-265V (50/60Hz)
- Dimensions (HxWxD): 280x185x292mm



Art. No.	Description
16650.000	Intralux 9000 HQI 150W Light Source hf 85-265V
16628.000	Intralux 9000 Light Source motorized diaphragm 85-265V

Intralux® IWL 500e

- 50W Metall Halid Lamp
- Color temperature 5500°K
- Lamplife (\emptyset in continuous operation) 3500h
- Light adjustment: Crescent shaped diaphragm (Volpi Patent)
- **Homogeneous illuminated fiber bundle- \emptyset 10mm**
- Dimensions (HxWxD): 248x123x226mm



Art. No.	Description
16624.000	Intralux IWL500e 230V
16624.610	Intralux IWL500e 115V



Intralux® mhti-r 50

- 50W Metall Halid Lamp
- Lamplife (mean in continuous operation) 2'500h
- Color temperature: 7'000°K
- Light Intensity: 1'100 Lumen
- Light adjustment: Crescent shaped diaphragm (Volpi Patent)
- CE / IEC 601-1

Art. No.	Description
17083.000	Intralux mhti-r50 medical cold light source
17091.000	Headlight with light guide



Intralux® Vision

- 24W Metal Halid Lamp
- Lamplife (Ø in continuous operation) 3000h
- PAL Camera Electronic
- 1/2" CCD Camera Head 752(H)x582(V)
- OSD On Screen Display
- YIC (S-VHS) Output
- Input power 100-240V (50/60Hz)
- Dimensions (HxWxD): 150x257x256mm

Art. No.	Description
17070.600	Intralux Vision new version (picture)
17085.000	1/2" CCD PAL Color Camera Head with C-Mount, Cable (3m)
40013.000	10" LCD Color Display LC-WAE3
17050.610	Intralux Vision old version
24328.000	1/2" CCD PAL Color Camera Head
24311.200	Camera cable 2m
24311.300	Camera cable 3m
24040.000	Camera C-Mount adapter



Filter for Intralux® 4100, 6100, 4000-1, 4000-1 ESD, 5000-1, 6000-1

Art. No.	Description
23500.032	Filterholder
23500.080	Filter blue
23500.081	Filter red
23500.082	Filter green
23500.083	Filter yellow
23500.084	Daylight filter
10445.010	Daylight filter to Intralux 6100

Spare Lamps for Intralux® Light Sources

Art. No.	Description
23500.014	Intralux 5 / 6000-1 / 6100 Halogen Lamp 21V / 150W EKE
90357.008	Intralux 4100 Halogen Lamp 12V / 100W
23829.025	Intralux 4000-1 / MR2-1 MR 2 Halogen Lamp 14,5V / 90W
90357.006	Intralux DC1100 Halogen Lamp 21V / 150W EKE
90357.012	Intralux DC1100 C Halogen Lamp 24V / 150W
16624.790	Intralux IWL 500e Metal Halid Lamp
90357.015	Intralux Vision Lamp Solarc 24W
16627.130	Intralux 9000 HQI Metall Halid Lamp 150W
90357.018	Intralux mhti-r 50 Lamp Solarc 50W
10091.111	Intralux 150H Halogen Lamp 15V / 150W
10088.111	Intralux 20H Halogen Lamp 6V / 20W
90277.001	Intralux 20HE Halogen Lamp 12V / 20W
90357.017	Intralux 9000 HQI Metall Halid Lamp 150W



Lamp Sockets

<i>Art. No.</i>	<i>Description</i>
10435.110	Intralux 4100 / 6100
25750.045	Intralux 4000 / 5000 / 6000-1 / MR2-1 Socket
23500.095	Intralux 5000 / 6000 Socket
25750.110	Intralux 4000 / MR2 Socket

Spare Parts for Intralux® MR-2-1

<i>Art. No.</i>	<i>Description</i>
11027.000	Light guide to MR 2-1 Ø 7mmx1900mm
11026.000	Light guide to MR 2-1 Ø 10mmx1900mm
10287.150	Limit switch for Intralux MR2-1, kit for retrofit
10287.420	Limit switch for Intralux MR2-1
10287.410	Relais-Print for Intralux MR2-1



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com