



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

1/3 to 2 HP**Designed for long life and reliable operations in severe industrial applications**

| [Standard Features](#) | [Specifications](#) | [Performance Data](#) |

These motors are totally enclosed and sealed to minimize the possibility of dirt, dust, water, or other contaminants from entering the motor and shortening the life of the motor. The SXT motor is ideal in applications where standard open drip-proof or totally enclosed motors do not provide adequate protection. They are built extra tough for life in moist, contaminated environments found in chemical plants, petroleum refineries, paper mills and other demanding industrial installations.

Standard Features

- **Frame** - Heavy gauge steel with full seam weld. Optimum thickness for better heat dissipation. Frame-to-end-shield fits extra long, turned, and sealed with permatax® to protect motor internals from contaminants. Frame zinc chromate plated and primed with acrylic enamel primer.
- **End Shields** - Cast iron to provide extra strength and corrosion resistance. Epoxy primed.
- **Drains** - "T" drain in end shield provides drainage of any condensation and moisture collected inside motor and on windings. Fan cooled motors have drain hole in fan end providing an additional exit for moisture.
- **Base** - Heavy duty steel welded to frame. Base zinc chromate plated and primed with acrylic enamel primer.
- **Rotor** - Cast aluminum with integrally cast fins for excellent cooling. Keyless design, heat shrunk to shaft, turned for proper air gap and dynamically balanced. Coated with epoxy polyamide primer to resist corrosion. Designed for a superior, more efficient and rugged electrical design.
- **Stator** - Specially treated class "F" and "H" wire used with full slot liner material. Coil heads laced for improved mechanical strength. Stator tested before and after assembly providing optimum electrical integrity.
- **Insulation** - Non-hygroscopic, double dipped and baked insulation assures superior electrical strength and integrity. **Phase insulation included for inverter duty applications on three-phase motors.**
- **Hardware** - Zinc chromate plated, high strength, with hex heads. Plating provides exceptional corrosion protection.

- **Seals** - Lipseals on both ends.
- **Bearings** - Double sealed, oversized and permanently lubricated for improved bearing life. Rugged to hold up in tough applications.
- **Conduit Box** - Oversized, top mounted, conduit box with F1/F2 conduit connection and grounding lug for ease of installation and safety (F1/F2 conduit box in the end shield for TENV). Conduit box and lid are gasketed to protect the interior of the motor from life limiting contaminants.
- **Shaft** - High strength, 416 stainless steel. Offers better resistance to abrasive and corrosive materials.
- **Nameplate** - Stainless steel for added life in corrosive atmospheres. Provides ease of identification.
- **Connection Diagram** - Permanently attached to motor.
- **Fan** - Antistatic, bidirectional, corrosion resistant polypropylene. Provides superior cooling with reduced losses due to air movement. Keyed and clamped to prevent movement on the shaft.
- **Single-phase** - Electronic starting switch mounted in conduit box (or on end shield for TENV) providing convenience and reliability.
- **Finish** - Exterior is coated with an acrylic enamel finish coat for superior corrosion resistance, durability and extended service life.
- **Leads** - Permanently marked providing fast identification.
- **Certifications** - U.L.® component recognition and CSA® approved.
- **Energy Saving Design** - Provided by electrically matched rotor and stator which reduce primary and secondary losses. Also available in energy efficient designs for superior savings.

Specifications

Horsepower	1/3 to 2
Speed ⁽¹⁾	3600, 1800, 1200, 900 RPM
Enclosure	Totally Enclosed, Fan Cooled or Totally Enclosed Non-vent
Frame	56, 140T
NEMA Design	B
Power Supply	Single-phase, 60 Hz, 115/230 or Three-phase, 60 Hz, 208-230/460 (A wide range of other frequencies and voltages are also available.)
Insulation	Class F
Duty	Continuous
Ambient	40°C
Service Factor	1.15

(1) Single-phase 900 RPM not available.

Performance Data

Single-Phase

HP	Full Load RPM	Encl.	Type	Amperes @ 230 V			Efficiency Load ⁽¹⁾			Power Factor Load			S.F.	Torque, Lb. Ft.			Perf. Data Design
				FL	LR	Code	4/4	3/4	2/4	4/4	3/4	2/4		FL	BD	LR	

1/3	1725	TENV	CS	2.40	13.50	M	71.0	69.0	61.0	67.0	60.0	52.0	1.15	1.02	3.13	3.00	M3135
	1140	TENV	CS	3.50	15.20	M	63.0	61.0	52.0	50.0	44.0	36.0	1.15	1.53	4.04	5.08	M3151
1/2	3600	TEFC	CS	2.80	18.85	K	75.3	72.7	66.9	79.0	73.5	64.2	1.15	0.74	2.00	2.33	M2696
	1725	TENV	CS	3.20	18.50	L	75.0	73.0	68.0	68.0	60.0	50.0	1.15	1.49	3.91	5.25	M3105
	1140	TEFC	CS	4.70	22.50	L	61.0	59.0	52.0	58.0	50.0	41.0	1.15	2.27	5.24	6.50	M3131
3/4	3450	TEFC	CS	4.70	26.20	K	72.0	71.0	66.0	76.0	70.0	62.0	1.15	1.12	2.56	3.06	M2649
	1725	TEFC	CS	5.50	29.00	K	70.4	69.6	63.6	69.5	60.7	49.5	1.15	2.25	5.81	7.69	M6983
	1140	TEFC	CH	4.45	25.00	J	76.0	73.6	67.3	73.1	66.9	57.5	1.15	3.38	8.33	10.00	M4575
1	3450	TEFC	CS	5.60	34.30	J	70.0	69.0	65.0	78.0	74.0	63.0	1.15	1.45	3.58	3.56	M2651
	1725	TEFC	CS	6.80	34.30	K	72.0	70.0	64.0	67.0	58.0	47.0	1.15	3.01	7.50	10.00	M2688

Three-Phase

HP	Full Load RPM	Encl.	Type	Amperes @ 460 V			Efficiency Load ⁽¹⁾			Power Factor Load			S.F.	Torque, Lb. Ft.			Perf. Data Design
				FL	LR	Code	4/4	3/4	2/4	4/4	3/4	2/4		FL	BD	LR	
1/4	1725	TENV	P	0.65	3.50	N	65.3	59.7	51.4	55.3	48.4	39.1	1.15	.750	3.33	2.29	M2922F
1/3	1725	TENV	P	0.80	4.65	N	69.1	64.4	55.9	57.3	48.6	39.5	1.15	.981	4.50	3.38	M2971
1/2	3450	TENV	P	1.17	11.10	M	76.1	76.0	71.2	82.8	73.6	62.5	1.15	.750	2.95	2.41	M2749
	1725	TENV	P	1.10	6.10	L	74.3	72.1	66.8	65.7	56.1	44.0	1.15	1.50	5.58	3.92	M6976
3/4	3450	TENV	P	1.20	9.80	L	79.0	78.0	73.0	82.0	78.0	68.0	1.15	1.16	4.23	3.09	M2957
	1725	TENV	P	1.25	10.00	M	74.0	66.0	56.0	74.0	66.0	56.0	1.15	2.25	10.69	8.00	M2925
	1140	TEFC	P	1.60	7.15	J	74.0	72.0	68.0	66.0	57.0	46.0	1.15	3.43	10.00	7.75	M2948
1	3450	TENV	P	1.50	10.75	K	80.0	80.0	76.0	87.0	82.0	73.0	1.15	1.50	5.49	4.08	M2994
	1730	TEFC	P	2.20	12.90	L	75.0	72.0	66.0	60.0	52.0	42.0	1.15	3.03	13.30	10.00	M2921
	1725	TENV	P	1.60	12.30	M	81.0	81.0	77.0	78.0	70.0	59.0	1.15	3.01	13.30	12.50	M2968
	1140	TEFC	P	2.20	9.95	J	74.0	73.0	66.0	58.0	49.0	39.0	1.15	4.56	14.90	10.80	M141
1-1/2	3450	TEFC	P	2.20	2.03	H	79.5	78.5	74.8	84.6	80.0	70.6	1.15	2.24	8.19	6.25	M6742
	1725	TEFC	P	2.80	15.80	K	78.5	76.0	70.3	64.7	55.0	44.0	1.15	4.51	16.70	12.90	M2920
2	3450	TEFC	P	2.80	2.84	L	79.7	74.8	67.1	84.3	76.0	68.0	1.15	3.04	11.00	9.38	M6743
	1730	TEFC	P	3.20	21.00	J	81.8	80.2	77.5	74.6	67.4	55.2	1.15	6.10	21.20	16.80	M2916

(1) Efficiency values based on a motor without lip seals. SXT motors have lip seals causing efficiency to vary.

Ask for Assistance

Before you buy another AC motor, check with your Reliance sales engineer or distributor to determine why Reliance **SXT** motors are the proper choice. For further information about Reliance motor products, contact your local Reliance sales office or authorized distributor or call:

1-800-245-4501

Document number b2762_3

Note: This material is not intended to provide operational instructions. Appropriate Reliance Industrial Company instruction manuals and precautions should be studied prior to installation, operation, or

maintenance of equipment.

Reliance® is a trademark of Baldor.

U.L.® is a registered trademark of Underwriter's Laboratories, Inc.

CSA is a registered trademark of the Canadian Standards Association.

[an error occurred while processing this directive]



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com