



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)

## 1396 Universal Waveform Synthesizers

### 50 MS/s universal waveform synthesizers



- Up to 50 MS/s sampling with 12-bit resolution
- Up to 2M waveform points
- Versatile inter-module triggering, summing and phase control
- Up to 450 user-defined waveforms
- Waveform linking and looping of up to 4,096 segments
- 16-bit digital output
- Frequency sweep and hopping
- VXI Plug&play drivers provided
- Compatible with WaveForm DSP2
- Single-slot, C-size VXIbus message based device

The Fluke 1396 is ideal for applications requiring standard function generator or universal waveform capability. Model 1396 adds advanced waveform sequencing capability of up to 4,096 waveform segments for complex waveform generation. It also provides a 16-bit digital output. Standard sine waves are available to 20 MHz and square waves to 25 MHz. Universal waveforms with 12 bit vertical resolution may be generated at sampling frequencies up to 50 MS/s.

For multichannel applications, multiple units may be phase locked with programmable phase offsets. Waveforms from multiple modules may be summed using the VXI backplane sumbus. Versatile intermodule triggering capabilities are provided. In addition to built-in frequency sweep capability, a frequency list function can be used for custom sweeping or frequency hopping applications. To simplify programming and help reduce programming time, all three models support dynamic configuration, are message based, SCPI compatible and are provided with VXI Plug&play drivers.

### Specifications

#### Standard waveforms

Sine, square, triangle, ramp, haversine, random, (sine x)/x, and DC.

#### Frequency

**Range:** Sine and haversine: 1 MHz to 20 MHz.

**Square:** 1 MHz to 25 MHz.

**All others:** 1 MHz to 2 MHz.

**Resolution:** 8 digits limited by 1 mHz (5 digits above 20 MHz and in noncontinuous modes).

**Accuracy:** Same as VXI CLK10 backplane signal ( $\pm 0.01\%$  typical).

### Waveform quality

**Sine distortion (elliptic filter selected):**

Freq	Ampl	Harmonic Level
<100 kHz	10 Vpp	< -60 dBc.
<100 kHz	>10 Vpp	< -55 dBc.
<5 MHz	10 Vpp	< -45 dBc.
<5 MHz	>10 Vpp	< -40 dBc.
20 MHz	10 Vpp	< -35 dBc.
20 MHz	>10 Vpp	< -28 dBc.

**Square transition time:** < 9.5 ns.

**Square aberrations:**

< 5 % + 20 mV.

**Square wave duty cycle control**

**Range:** 0 to 100%.

**Resolution:** 3.5 digits.

**Triangle wave symmetry Control**

**Range:** 0 to 100%.

**Resolution:** 3.5 digits.

### Universal waveforms

**Sampling frequency:**

**Range:** 0.1251 S/s to 50 MS/s.

**Resolution:**

5 digits limited by 100  $\mu$ S/s.

**Accuracy:** Same as VXI CLK10 ( $\pm 0.01\%$  typical).

**Horizontal resolution:**

512k (2M optional).

**Vertical Resolution:** 12 bits.

**Waveform filters:** 20 MHz, 4-pole Bessel and 20 MHz, 7-pole, 6-zero elliptic.

# 1396 Universal Waveform Synthesizers

## Amplitude

### Range:

15 mV to 15 V<sub>pp</sub> into 50 Ω  
(30 mV to 30 V<sub>pp</sub> into > 10 kΩ).

**Resolution:** 3.5 digits.

**Accuracy:** ± (1 % of setting).

## Offset

**Range:** -7.5 to +7.5V into 50 Ω  
(-15V to +15V into >10 kΩ). Peak amplitude + absolute offset must be 7.5V into 50 Ω.

**Resolution:** 3.5 digits.

**Accuracy:** ± (1% of setting).

## Operating modes

Continuous, sweep, triggered, gated, linked sequence, and frequency list.

**Triggered:** One to 1,048,576 cycles on trigger input (limited to 10 MHz).

**Gated:** Waveform cycle started on trigger high, completed after low.

**Linked sequence:** Linking, looping, and advancing of up to 4,096 waveform segments. Allows creation of long and complex waveform sequences.

**Frequency list:** Up to 1024 programmable frequencies. Can be output phase continuously on trigger command. (Maximum rate 2 kHz).

## Frequency sweep

**Range:** 1 MHz to 20 MHz.

**Time:** 30 ms to 1000 sec.

**Modes:** Continuous or triggered up, down, or up/down, and triggered sweep and hold.

**Spacing:** Linear or logarithmic.

## Triggering

**Sources:** External, internal, TTLTRG0-7, adjacent modules via local bus and word serial command.

## Internal trigger

### frequency range:

10 μHz to 5 MHz.

## Modulation

AM & SCM.

**Range:** 0 to 100 % on external voltage.

**Bandwidth:** DC to 500 kHz.

## Multimodule summing

Input from the VXI SUMBUS may be summed with the output, or the programmed output may be sent to the SUMBUS.

## Multimodule phase control

Adjacent modules may be phase synchronized on standard waveforms.

**Phase resolution:** 0.1°.

**Phase accuracy:** ± (0.05° + 5 ns).

## Outputs

**Main Out (50 Ω):** Main waveform output, programmable on/off.

**Sync/horizontal sweep (600 Ω):**

TTL level synchronous with main output waveform, or a 0 to 10V ramp proportional to sweep frequency.

**Position Out (50 Ω):**

TTL-level marker, selectable for each waveform point.

**Clock Out (50 Ω):**

TTL level, sampling frequency clock output.

**Digital Output:** 16 bit differential ECL updated at up to 50 MHz.

**Aux analog output:**

± 1.0V output updated for each segment in a sequence.

## Inputs

**Clock in (2 kΩ):**

TTL level, selectable as main waveform clock.

## TRIG IN (2 kΩ):

TTL level, triggered on rising or falling edge.

**AM in (10 kΩ):**

Used for AM and SCM input.

## VXI interface

**Device class:** DC, message-based, SCPI compatible.

**TTLTRG0-7:** Programmable as trigger input, output, position out, burst- or loop-complete, or sequence start/advance input.

**ECLTRG0-1:** Programmable as clock input or output.

**SUMBUS:** Full driver and receiver support. Accuracy ± 5% typical.

**A24 shared memory:** Supports high-speed waveform transfers, and fast frequency updates.

## General

**Operating Temperature:**

0° to 50°C; 25° ± 10°C for specified operation.

**Dimensions:**

Single-slot, C-size VXI module.

**Weight:** < 1.8 kg (3.9 lb).

**Power:** < 35 Watts.

## Ordering information

**Model 1396-EM512:**

VXIbus 50 MS/s Universal Waveform Generator with advanced sequencing, 16-bit digital output, 512k memory and VXI *Plug&play* driver.

**Model 1396-EM2M:**

VXIbus 50 MS/s Universal Waveform Generator with advanced sequencing, 16-bit digital output, 2M memory and VXI *Plug&play* driver.

**Wave Form DSP2:** Arbitrary Waveform Creation Software.



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)