



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗


LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com



Flowmeters for



*High resolution flow waveforms,
the signature of
Transonic Systems*

Your Gold Standard for Blood Flow Measurements

- 1995** One flowmeter that does it all! T106 flowmeter capabilities expanded for micro to large vessels.
- 1994** A-Series flowprobes with small profile designed for cardiac output; WINDAQ Data Acquisition Package added.
- 1993** V-Series Microcirculation flowprobes introduced for vessels as small as 250 microns.
- 1991** T108 flowmeters with high resolution circuitry obsoletes T101D meter.
- 1990** T106 Small Animal Flowmeter & 1 mm flowprobe introduced for rat research.
- 1989** Sterile tubing flowsensors expand extracorporeal line.
- 1987** In-line probes developed for measurements in tubing.
- 1983** First T101D transit-time volume flowmeter established in Transonic Systems' founding year; R & S flowprobes developed.

Animal Research



Animal Research Flowmeters
Acute & Chronic Studies



T106 / T206
The Gold Standard
for Blood Flow
Measurement

For Acute and Chronic Studies
in vessel diameters 250 μ - 36 mm o.d.
also for
***in vitro* and tubing applications** *(see page 37)*

Accurate • Repeatable • Validated

Transonic Systems' Animal Research Flowmeters and perivascular flowprobes utilize transit-time principles of ultrasound to **directly quantitate volume flow**. Validated for accuracy in numerous applications *(page 45)*, Transonic Systems flowmeters are the **recognized gold standard** for blood flow measurement in cardiovascular research.

They feature unequalled resolution, zero baseline stability and built-in ease of use.

An **extensive selection of perivascular probes** accommodates an unsurpassed range of vessel sizes for chronic and acute studies.

Extracorporeal flow measurements in tubing are also easily obtained with in-line and sterile tubing flowsensors *(see page 38)*.

Available in **single and dual channel models**, Transonic Systems flowmeters have newly expanded flow measurement capabilities and enhanced data acquisition for comprehensive hemodynamic studies.


 **Transonic Systems Inc.**
Excellence in Quantitative Hemodynamics

34 Dutch Mill Road, Ithaca NY 14850, USA. TEL: (607) 257-5300; FAX: (607) 257-7256

3



Measurement Capabilities



Direct Quantification of Volume Flow

T106U / T206U, T106 / T206 Animal Research Flowmeters

- Available in single or dual channel models
- Display average flow rate in ml or L/min
- Pulsatile and mean analog flow signals can be externally recorded from rear-panel BNC
- Provides at-a-glance monitoring of the quality of the ultrasound signal
- Low flow scale selection for increased sensitivity
- Proven transit-time ultrasound technology
- T106U/T206U provides low cost data acquisition and pressure recording.

Acute or Chronic Animal Studies

One flowmeter to study multiple animal models with exceptional resolution and reliability.

- Measurement capability for vessels from 250 microns through 36 mm diameter
- Probes are non-constrictive and compatible for long-term implant
- New series of cardiac output flowprobes for highest accuracy in vessels with turbulent flow

Extracorporeal & In Vitro Flow Measurements *(also see page 31-39)*

One flowmeter to measure a wide variety of liquids *(ie. blood, saline, urine, buffers)*.

- high resolution in-line flowprobes for tubing I.D. from 0.046" (1.2 mm) through 0.875" (20.8 mm)
- sterile tubing flowsensors for flexible tubing I.D. from 1.8" (3.2 mm) up to 3/4" (19.0 mm)

Flowmeter Specifications



Single-channel or dual-channel flowmeters are available for your application

T206 Dual Channel Flowmeter
(front panel)



T106
single channel
10 lbs (4.5 Kg), 8 1/2" w x 5" h x 16" d
(90-130 Volts; 50-60Hz, single phase
(30 VA, 1.0 AMP slow-blow fuse);
200-260 Volts; 50-60Hz, single phase
(30VA, 0.4 AMP slow-blow fuse)

T206
dual channel
16 lbs. (7.2 Kg), 19" w x 5" h x 16" d
90-130 Volts; 50-60Hz, single phase
(60 VA, 1.6 AMP slow-blow fuse);
200-260 Volts; 50-60Hz, single phase
(60VA, 0.8 AMP slow-blow fuse)

T106U/T206U
single channel and dual channel
model with data acquisition and
pressure recording capability.
Includes:
• **Computer Interface circuitry**,
cable, and "WINDAQ" software to
connect the flowmeter to an IBM
compatible computer via its serial
RS232 port;
• **Pressure sensor amplification** by
flowmeter A/D board for
acquisition of pressure data in
addition to flow. RJ11 phone
input jack for pressure
transducers; 1 per flow channel.

Synchronization for multi-unit
operation or simultaneous use with
Doppler instrument is supplied as
standard circuitry on all units.

Gating (-G) Option for use during
MRI unit to eliminate cross-
coupling interferences.

Bubble Alarm (-B) Option with
audible alarm which sounds when
gas bubbles pass through a sterile
tubing flowsensor.

Electrical Isolation

Flowmeter is grounded. If accidentally ungrounded, line to ground leakage current is less than 50 μ A. ETL listed.

1— Push Button Control of

Mode of operation: selects Measure, transducer Test, Calibrate External Recording Devices for Zero / Full Scale

2—

Low Flow Range: expands displayed flow sensitivity by a factor of four;

3—

Polarity of Displayed Flow: inverts polarity of analog flow outputs and flow displays

4—

Output filtering: 0.1, 10, 30 and 100 Hz
Low pass filtering applied to analog output signals

Automatic Meter Adjustments

- Probe size and corresponding flow output ranges (see flowprobe tables)
- Volume flow calibration of the applied probe
- Dual channel flowmeters synchronously monitor two flowprobes at the maximum rate without cross coupling interference

Flowmeter Displays

5—

Analog Meter (taut-band needle)

6—

Digital Display

- Volume flow (in Measure mode)
- Received signal amplitude (analog meter, Test mode)
- Diagnostic Data (digital display in Test mode)
- Probe scale data (in Zero and Scale factor Calibration modes)
- Test Light: indicates when acoustic signal and flow output signals do not meet specifications.

Multi-Unit Synchronization

Rear panel master/slave control and input cable to time ultrasound signals for concurrent operation with pulsed Doppler or sonomicrometry.

7— Flow Monitor Outputs

* Average volume flow; rear panel, BNC connector, 0.1Hz low-pass filtered

* Pulsatile/Average volume flow; front/rear panel, BNC connector, filtering controlled by front panel push buttons

Zero calibration = 0 Volts out

Scale factor flow = $1V \pm 2\%$

Output resistance = 500 Ohm

Full range for flows = $\pm 5V$ (bi-

directional flows, ± 5 times

scale factor)

8— Offset Adjustment Dial

for Zero flow reading during occlusion or when no flow is passing through a sterile tubing flowsensor; front panel

9— Probe Connector

Accepts male CH10-style connector of probe or extension cable

Digital Identification

Probe identification and calibration parameters programmed into flowprobe connector.

Ultrasonic Frequency

Probe dependent (see probe tables)

Ultrasonic Transducers

R-, S-, Series: implantable (chronic/acute) perivascular flowprobes;

V-, Series: microcirculation

flowprobes (T106/T206);

A-, Series: cardiac output

flowprobes;

C-Series: sterile tubing (clamp-on)

flowsensors for extracorporeal

use with tubing.

N-Series: in-line flowprobes that

splice into laboratory tubing

Extension Cable

1, 2, 3 meter cables available;

supplied one per flowmeter

channel purchased



Flowmeter Electives

U-Model includes both Computer & Pressure Options

T106U/T206U flowmeters combine the computer interface and pressure options as a low cost package at the initial purchase of the flowmeter. One pressure channel is supplied for each flow channel. The individual options may be retrofitted to previously purchased flowmeters.

Personal Computer Interface (-P option) provides the capability to record, store and playback flow data on an IBM-PC compatible computer with Windows capability (See pages 57-60 for complete description).

- WinDAQ software**
- Automatic time & date sampling
 - Annotation capability
 - Fully scalable
 - up to 8 channels of data acquisition
 - High speed sampling



pPressure (-R option): This top quality instrumentation amplifier allows the flowmeter to record simultaneous measurements of flow and pressure. With this enhancement - an extension of our Personal Computer Interface Option - the amplified pressure signal accompanies the flow signal to your computer. The sampling rate (200 samples per second with 4-channel WinDAQ and 100 samples per second with 8-channel WinDAQ) and resolution (12 bits, 4096 steps) make this suitable for mean pressure studies and certain types of waveform analysis. Abbott Transpac external transducers are provided for plug compatibility with RJ11 input phone jacks on the rear panel of the flowmeter. Other commercial transducers in +/-5 volt range are also compatible with the Pressure option circuitry although connector plugs may need adapters. See page 61 for complete specifications.

More Electives!

MRI Gating (-G) Option

For Magnetic Resonance Imaging, the flowmeter can be programmed to temporarily interrupt its flow measurement sequence and shut down the flowmeter oscillators during the imaging cycle. This effectively eliminates interference to either flow measurements or imaging.

Bubble Alarm (-B) Option

Equips Transonic flowmeters with an audible alarm which sounds when the ultrasonic signal coupling through the flowsensor falls below an (adjustable) percentage of normal. The option allows the user to set an alarm to sound when air bubbles pass through a sterile tubing flowsensor.

Multi-Unit Synchronization Selector (-S)

Now standard on all T106/T206 flowmeters.



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com