



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

SPECIFICATIONS

CIO-DAC08/16

CIO-DAC16/16

Analog Outputs



**MEASUREMENT
COMPUTING™**

Revision 6, April, 2001

© Copyright 2000, MEASUREMENT COMPUTING CORPORATION

Power Consumption

+5V supply	
CIO-DAC16/16	1.8 A typical, 2.25 A max
CIO-DAC08/16	1.3 A typical, 1.7 A max

Analog Output

Resolution	16 bits
Number of channels	
CIO-DAC16/16	16 Voltage Outputs
CIO-DAC08/16	8 Voltage Outputs
D/A type	AD660BN
Voltage Ranges	$\pm 5V$, $\pm 10V$, 0 to 5V, 0 to 10V, jumper-selectable
Offset error	Adjustable to zero
Gain error	Adjustable to zero
Differential nonlinearity	± 1 LSB max
Integral nonlinearity	± 1 LSB max
Monotonicity	Guaranteed monotonic to 15 bits over temperature
Gain drift (DAC)	± 15 ppm/ $^{\circ}C$ max
Bipolar offset drift (DAC)	± 5 ppm/ $^{\circ}C$ max
Unipolar offset drift (DAC)	± 3 ppm/ $^{\circ}C$ max
Throughput	System dependent
Slew Rate	2.8V/ μs Typical
Settling time (20V step to .0008%)	12 μs typ, 19 μs max
Settling time (10V step to .0008%)	6 μs typ, 9 μs max
Current Drive	± 5 mA min.
Output resistance (OP-27)	0.1 ohm max.
Output short-circuit duration	40 mA min. Continuous
Miscellaneous	Double-buffered output latches Update DACs individually or all DACs simultaneously (jumper-selectable) Power up and reset, all DAC's cleared to 0 volts (jumper selects bipolar or unipolar zero)

Environmental

Operating temperature range	0 to 70 $^{\circ}C$
Storage temperature range	-40 to 100 $^{\circ}C$
Humidity	0 to 90% non-condensing

Measurement Computing Corporation
16 Commerce Boulevard,
Middleboro, Massachusetts 02346

(508) 946-5100

Fax: (508) 946-9500

E-mail: info@measurementcomputing.com
www.measurementcomputing.com



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com