



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)

# IPnexus® CPC5565 PRODUCT SHEET

## Intel® Core™2 Duo Single Board Computer

### FEATURES

Intel® Core™2 Duo Featuring a 64-Bit Dual-Core 2.2 GHz Processor

Single-Slot, High-Performance Computing Solution for PICMG® 2.16 Systems

128-Bit Addressability to 8 GB PC2-3200 DDR with ECC Memory

Onboard Eight-Port Gigabit Switch

PMC Expansion Port with Support for 2x1000 Mbps Ethernet and 32/64 bit, 33/66 MHz PCI Bus

Supports Both 32- and 64-Bit Operating Systems:

- NexusWare® CGL OS and Development Environment
- Linux® x64
- Windows® XP x64
- Solaris™ 9/10 x64

AMD/ATI Radeon E2400 Graphics Processor supporting High Performance 2D, 3D and Multimedia Graphics

Full Compliance with PICMG 2.16 and 2.9 Specifications



Part of our IPnexus® portfolio of products, the CPC5565 is a 64-bit single-slot CompactPCI® single-board computer designed for high-performance embedded applications. It features the Intel® Core™2 Duo processor.

The Intel Core2 Duo processor provides a highly scalable x86 architecture that delivers next-generation performance and a flexible upgrade path from 32- to 64-bit computing. Its multi-core architecture offers advanced processing speed while addressing the power and heat constraints of the CompactPCI form factor. Designed to run Linux®, Solaris™, and Windows® applications, the CPC5565 is the ideal processor for the high-end packet processing or multi-threaded software applications found in softswitch, aerospace, wireless, defense, or other compute-intensive applications.

Paired with a CPC5910 storage expansion module, the CPC5565 can support local storage arrays of up to 4 Terabytes of high-performance SATA drives, which makes it an ideal embedded database server.

### Hardware Features

The CPC5565 features Intel Core2 Duo processors and chipsets that have been carefully selected for longevity from Intel's embedded products roadmap. This ensures that these SBCs will be available for a number of years. The selected processors have a range of clock speeds that support either single- or dual-core operation.

The Intel 3100 chipset features an 800 MHz Front side bus and offers a path to the array of I/O options, including USB 2.0, serial, PCI bus 33/66MHz, six SATA channels, and PCI Express®. The PCI Express channels are dedicated to the dual Gb Ethernet ports of the on-board Gb ethernet controller, the high performance AMD/ATI E2400 video controller, and the PCI Express to PCI Bridge.





# Intel® Core™2 Duo Single Board Computer

## Flexible I/O and Super Computer Performance

The CPC5565 is designed for use with PT's complete line of Advanced Managed Platform™ products such as the AMP5086 and AMP5095 chassis. It allows system designers to build robust, highly-reliable solutions that combine state-of-the-art management, the highest performance power and cooling, and integrated switching.

All of these solutions are compliant with the PICMG CompactPCI® specification, which assures interoperability, broad vendor selection, and a range of choices to complement the CPC5565.

A clustered computing architecture built with the CPC5565 and standards-compliant Advanced Managed Platform can outperform proprietary blade server architectures from both computing density-per-rack and total-cost-of-ownership perspectives.

The RTM4811, an advanced rear transition module, offers support for SATA 2.5-in. hard disks or solid state drives, as well as an analog VGA video interface, and USB. The CPC5565 can boot from the HDD/SSD on this RTM or through a SATA connector on the rear face plate. By using the RTM4811, the CPC5565 can be chained to a CPC5910 storage expansion module that contains two 3.5-in. hard drive disks to make a local storage array with up to 4 TB of directly attached storage.

## Thermal Design for Embedded Applications

The CPC5565 is designed to fit into the power and cooling capabilities of PT's Advanced Managed Platform solution, so customers can be assured that their applications will meet stringent requirements that include NEBS, UL, and ETSI. It is also designed from the ground up to be RoHS-compliant for systems that require toxic materials elimination. By employing advanced techniques that include the use of the onboard IPMC microcontroller to control CPU clock speed, PT has designed the CPC5565 to automatically adjust to the most demanding environmental conditions.

## Configuration Options

Product Number	Description
PT-CPC5565-12389	Intel® Core™2 Duo 2.2 GHz 64-Bit SBC, 2GB, no HDD, PMC
PT-CPC5565-12390	Intel® Core™2 Duo 2.2 GHz 64-Bit SBC, 2GB, 250 GB 24x7 HDD, No PMC
PT-CPC5565-12391	Intel® Core™2 Duo 2.2 GHz 64-Bit SBC, 4GB, no HDD, PMC
PT-CPC5565-12392	Intel® Core™2 Duo 2.2 GHz 64-Bit SBC, 4GB, 250 GB 24x7 HDD, No PMC
PT-CPC5565-12393	Intel® Core™2 Duo 2.2 GHz 64-Bit SBC, 8GB, no HDD, PMC
PT-CPC5565-12394	Intel® Core™2 Duo 2.2 GHz 64-Bit SBC, 8GB, 250 GB 24x7 HDD, No PMC
PT-CPC5565-12425	Intel® Core™2 Duo 2.2 GHz 64-Bit SBC, 2GB, 160 GB SSD, No PMC
PT-CPC5565-12426	Intel® Core™2 Duo 2.2 GHz 64-Bit SBC, 4GB, 160 GB SSD, No PMC
PT-CPC5565-12427	Intel® Core™2 Duo 2.2 GHz 64-Bit SBC, 8GB, 160 GB SSD, No PMC

Product Number	Description
PT-CPC5910	SATA Storage Expansion Module with two hot-swappable SATA drives. Requires RTM4811 rear transition module with PT-ACC102-12479 SATA cable.

Product Number	Description
PT-RTM4811-12461	SATA Storage Expansion Rear Transition Module with no Drive
PT-RTM4811-12460	SATA Storage Expansion Rear Transition Module with a 250 GB 24/7 SATA Hard Drive
PT-RTM4811-12459	SATA Storage Expansion Rear Transition Module with a MLC Solid-State Drive
PT-RTM4811-12458	SATA Expansion Rear Transition Module, No Drive, with Dual Gb Ethernet Interfaces (for use in non-PICMG 2.16 applications)
PT-ACC102-12479	One Meter Long Mini-SAS to Mini-SAS Cable (for SATA interface)
PT-ACC7340-12077	DB9 to RJ-11 Serial Cable

# IPnexus® CPC5565 PRODUCT SHEET

## ORDERING INFORMATION

To discuss specific requirements and/or pricing, contact sales@pt.com.

## Software Options

PT's NexusWare® suite of software provides a comprehensive Carrier Grade Linux® (CGL) OS and development environment as well as middleware and protocol communications software.

For more information visit [www.pt.com](http://www.pt.com) or call your local representative.

## CONTACT US

PT  
205 Indigo Creek Drive  
Rochester, NY 14626

tel: +1.585.256.0200  
fax: +1.585.256.0791  
E-mail: sales@pt.com



## Processor

- Intel® Core2 dual-core architecture:
  - Independent L1 cache structures per core
  - Shared L2 cache (4 MB)
  - 64-bit processor
- Compatible with existing 32-bit code base
- Enhanced Intel SpeedStep® technology for more efficient power management

## Video

- AMD/ATI Radeon™ E2400 Video Processor
  - Internal 128 MB GDDR3 Memory
  - High-performance 2D, 3D, and multimedia graphics
  - QXGA resolution up to 2048 x 1536
  - HDMI output for 480p, 720p, and 1080i
  - 32 bits per pixel
  - DirectX 10 and OpenGL 2.0 support
  - Video acceleration
    - Advanced de-interlacing algorithms
    - Programmable, independent gamma control for video overlay
  - SMARTSHADER™ 4.0
  - SMOOTHVISION™ 2.0
  - Dual-display mode
  - Integrated HD audio codec supports PCM and Dolby® Digital 5.1 Audio Formats

## Memory

- Low latency, high bandwidth
- 64-bit DDR2 PC2-3200
- 200-pin SO-RDIMM
- Supports up to 8 GB DRAM
- ECC checking with double-bit detect and singlebit correct

## Physical Interfaces

- Onboard Managed Switch
  - 1 Gb routed to:
    - Host CPU, two ports
    - PMC slot, two ports
    - PICMG® 2.16 backplane, two ports
    - Front panel, two ports
- PMC slot
- Support for up to 6 SATA devices
  - 1 to the onboard SATA HDD
  - 1 to J5 of the RTM
  - Up to 4 external SATA ports on the RTM
- Three USB 2.0 ports
  - Two front and one rear

## Technical Specifications

- Onboard video
  - DVI-I connector for digital and/or analog video
  - Rear VGA connector
- Serial port
  - Front/rear
- User-defined LEDs

## Dimensions

- Single width CompactPCI® form factor, 6U x 4HP (233 mm x 160 mm)

## Switch Management

- CLI via RS-232 and in-band Ethernet ports
- Telnet
- SNMP v1, v2c, v3 – RFC 1157
- MIBs
  - MIBII – RFC 1213, MIBII bridge – RFC 1493
  - IEEE 802.1q MIB – RFC 2674
  - PT enterprise MIB

## Specification Compliance

- PICMG 2.16 R1 CompactPCI packet-switched backplane
- PICMG 2.9 R1.0 CompactPCI system management specification/IPMI (intelligent platform management interface) version 1.5
- IEEE Std. 802.3 – 2000 edition CSMA/CD access method and physical layer specification
- USB 2.0, high speed

## Power

- 66 W maximum with V(I/O) set to 3.3V
  - Multiple low power states
  - System Management Mode (SMM)
  - ACPI Compliant

## Environmental

- Operating: 0 to 55°C (32 to 131°F)
- Non-operating: -20 to 80°C (-4 to 176°F)
- Humidity: 5 to 90% RH non-condensing

## Agency Certifications (Pending)

- FCC Class A
- CE
- UL 60950
- EN 60950
- ETSI EN 300 386
- Designed to meet the requirements of NEBS Level 3

## MTBF

- TBD



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)