



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

DYNAMIC ENGINEERING

150 DuBois St. Suite C Santa Cruz CA 95060
831-457-8891 Fax 831-457-4793
sales@dyneng.com
www.dyneng.com
Est. 1988

PCI2PMC-ME-HC Features	
Size	Half size PCI card.
PMC compatible slot	1 PMC Slot provided.
Clocks	PCI bus can operate at 66 or 33 MHz. The PMC must be 66 MHz capable for 66 MHz operation to work properly. M66EN has a user shunt to allow or disable 66 MHz. operation.
Access Width	Standard PCI byte lanes supported for byte, word and long access dependent on installed PMC. 32 bit operation supported.
Software Interface	PMC register definitions as defined by installed hardware. No software set-up required by PCI2PMC.
Interrupts	INTA, B, C, D routed to PCI connector from PMC.
Signal Conditioning	AD signals are series terminated and Schottky clamping Diodes on critical PCI signals. Zero delay buffer for PCI clock distribution.
Power	+5, +3.3, +12, -12V supplied to PMC.
VIO	PCI IO Voltage is set by the PCI backplane. VIO is routed from the PCI connector to the PMC.
Thermal	The PCI2PMC has a cut-out to support increased airflow over the PMC component side.
IO Interface	Front Bezel IO supported at PCI bracket.
LEDs	+3V, +5V, +12V, -12V and Busmode 1.





Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com