



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)

---

# User Manual

## TPRO-IP

Synchronizable Timecode  
Generator with  
IP Bus Interface

Revision 3



**KSI**  
a division of DSPCon, Inc.

**For technical support, contact KSI toll-free at 866-KSI-KSI3**

TPRO-IP USER MANUAL  
Revision 3 —February 2003

A Publication of

**KSI**

© MMIII

Printed in the United States of America. All rights reserved. Contents of this publication may not be reproduced, stored in or transmitted by a retrieval system, or transmitted in any form or by any means, electronic or mechanical, including photocopying or recording, without the written permission of KSI.

KSI has worked to verify the accuracy of the information contained in this document as of its publication date; however, such information is subject to change without notice and KSI is not responsible for any errors that may occur in this document.

Trademarks are acknowledged and are the property of their owners.

# Proprietary Notice

This document contains data proprietary to DSPCon. However, permission is hereby granted by DSPCon to the purchaser and/or the purchaser's subcontractor(s) and/or customer(s), to reproduce this Operation & Maintenance Manual, in whole or in part, for the purposes of installation, operation, maintenance, repair, backup, and/or training, subject to the following conditions: This page, in its entirety, shall be included in any reproduction; The information contained herein shall not be altered, publicly displayed, or disclosed to other vendors or representatives of vendors of similar equipment; Availability via a computer network shall be strictly limited to the purchaser, the purchaser's subcontractor(s), and/or the purchaser's customer(s).

The software (if any) included with this product contains data proprietary to DSPCon. However, permission is hereby granted by DSPCon to the purchaser and/or the purchaser's subcontractor(s) and/or customer(s), to copy the software diskette to another diskette, and/or to other media, and/or to a computer network, and to modify the software, in whole or in part, for the purposes of installation, operation, maintenance, repair, backup, and/or training, subject to the following conditions: The software shall not be publicly displayed or disclosed to other vendors or representative of vendors of similar equipment; Availability via a computer network shall be strictly limited to the purchaser, the purchaser's subcontractor(s), and/or the purchaser's customer(s).

Receipt or possession of this document does not convey any rights to manufacture or reverse-engineer anything it may describe or imply, in whole or in part.

# Disclaimer

This document reflects the specifications and features of the equipment that were current at the time of publication. DSPCon disclaims responsibility for any errors and/or omissions contained herein, and reserves the right to make changes to this manual and related equipment and software without notice or obligation.

Software supplied with this product (if any) is for demonstration purposes only; it is not a full-featured program. The software media (diskette) is warranted to be readable when read in a computer using the proper operating system and proper disk drive. Software is neither warranted nor represented to be suitable for any particular application.

**THIS PRODUCT IS NOT AUTHORIZED FOR USE AS A CRITICAL COMPONENT IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN CONSENT OF THE PRESIDENT OF DSPCON, INC.**

## REVISION HISTORY

Revision Date	Revision No.	Revised Section(s)	Comments/Notes
March 2001	—	—	Initial Revision
May 2001	1.1	All	Completely reformatted to reflect new design.
June 2002	2.1	Appendix	Added programming examples
February 2003	3	2/8/9	Updated timecode input and output specifications, updated pin description, updated pin assignment, revised programming commands

# Table of Contents

Proprietary Notice .....	i
Disclaimer .....	i
<b>CHAPTER ONE—OVERVIEW .....</b>	<b>3</b>
<b>CHAPTER TWO - SPECIFICATIONS.....</b>	<b>5</b>
Physical .....	6
Timecode Input.....	6
Timecode Output.....	6
Time-Tag Input.....	6
On-Board Clock .....	7
IP Bus Interface .....	7
Match Output.....	7
<b>CHAPTER THREE – REGISTER ASSIGNMENTS.....</b>	<b>9</b>
<b>CHAPTER FOUR—ID DATA .....</b>	<b>11</b>
<b>CHAPTER FIVE—CONFIGURATION .....</b>	<b>14</b>
Input/output connections .....	14
Base address .....	14
<b>CHAPTER SIX – INSTALLATION .....</b>	<b>16</b>
Installation .....	16
<b>CHAPTER SEVEN – OPERATION .....</b>	<b>18</b>
General .....	18
Propagation Delay Adjustment.....	18
<b>CHAPTER EIGHT – INPUT/OUTPUT PIN ASSIGNMENTS .....</b>	<b>19</b>
50 Pin IP Carrier Header (P1) .....	20
Input/Output Pin Assignments .....	20
50 Pin IP Carrier Header (P2) .....	21
<b>CHAPTER NINE—PROGRAMMING .....</b>	<b>23</b>
Reading the clock through the 16-bit registers.....	24
Status .....	25
FIFO Initialization.....	25
Reading the FIFO .....	25
External Event Time Tagging .....	25
Interrupts .....	26
Forcing Hardware Reset.....	27
Commands.....	27
Setting Time .....	29

Setting Propagation Delay Correction.....	29
Disabling Synchronization to Input.....	30
Re-enabling Synchronization to Input.....	30
Simulating Power-on Reset of TPRO-IP Firmware .....	30
<b>CHAPTER TEN—PREVENTATIVE MAINTENANCE .....</b>	<b>31</b>
<b>CHAPTER ELEVEN—TROUBLESHOOTING .....</b>	<b>32</b>
Before you contact KSI .....	34
Bus Crashes .....	34
Bad data from 16bit data registers.....	34
Bad data from FIFO port .....	34
Interrupt crashes .....	35
Board never syncs to input code or 1PPS.....	35
<b>APPENDIX—FIRMWARE SAMPLE CODE .....</b>	<b>38</b>

# Chapter One

---

## Overview



## Overview

The TPRO-IP is a precision clock that can be read through a host IP carrier. The TPRO-IP automatically synchronizes to standardized time code signals. It is used for time tagging. Time tagging can be done by reading the clock through four 16-bit time registers or by a logic pulse from the outside world (an "external event"). The 16-bit reads are usually used for software initiated time tagging (for example time-tagging the time a block of data transfer starts or completes). Reading the first 16-bit time register (for units of microseconds through units of milliseconds) also freezes the tens of milliseconds through hundreds of days.

External events are usually used for time-tagging hardware related events (for example the exact time of a radar transmit pulse) because the added error of variation in software delays degrades the accuracy or a software initiated time tag. The time tag data for external events is transferred to the host through a byte wide hardware FIFO as a sequence of 10 bytes.

Inputs to the TPRO-IP are modulated timecode, host commands (not usually needed) and external event pulsed as required for the application.

Outputs are DC level shift IRIG-B time code, and a match pulse that occurs at user commanded times. The TPRO-IP also can generate interrupts to the host system as enabled and selected by the host system. Interrupt sources include external event data FIFO not empty and start or stop time match.

The clock will automatically synchronize to specified time code signals. Status bits advise the host of synchronization status. If there is no synchronization source the TPRO-IP will start counting at 000 days ..00 seconds at power-on. The clock time can be set by user commands.

# Chapter Two

---

## Specifications

## Physical

Dimensions	99.06 mm (3.9") x 45.72 mm (1.8") (Industry pack size)
IP bus Type	Single 16-bit
Power	+5V $\pm$ 5%, 100mA typical 150 mA max. +12V $\pm$ 5%, 100 mA max
Temperature	0 to 50 C operation -40 to 60 C storage
Humidity	0 to 95% non-condensing

## Timecode Input

Code Format	IRIG-B (B122)
Amplitude (mark)	1.2 Vp-p min, 8.0 Vp-p max
Polarity	Detected automatically
Modulation Ratio	2:1 min, 3:1 typ, 4:1 max input
Impedance	> 10 K ohms
Input Time Accuracy	Must be better than 100 ppm

## Timecode Output

Code Format	DC Level Shift IRIG-B (B002)
-------------	------------------------------

## Time-Tag Input

Input Voltage	-0.5 V min, +0.8 V max for logic 0 +2.0 V min, +5.5 max for logic 1 Tags rising edge
Input Current	<5 $\mu$ A for logic 0 <5 $\mu$ A for logic 1
Rise/Fall Time	500 ns max
Repetition Rate	2000 events per second max timing
Resolution	1 $\mu$ s

## On-Board Clock

Resolution	1 $\mu$ s
Range	366:23:59:59.999999
Date Format	Integer (001-366)
Synchronization Time	< 8 seconds

## IP Bus Interface

Meets IP specifications per ANSI/VITA-4 1995	
IP data Transfer cycles supported	
Input/Output (IOSEL*)	Eight 16-bit registers
ID Read (IDSEL*)	Identification (12 bytes)
Interrupt	Uses IRQ0 for interrupt at user-specified time

## Match Output

Output Voltage	3.8 V min at 6mA (high) 0.4 V max at -6 mA (low)
Settability	1 $\mu$ s

*This page intentionally left blank*

# Chapter Three

---

## Register Assignments

Offset from Base Address	Bits Bit 0 is LSB	Read Usage	Write Usage
1		Status	Interrupt Enable
1	7	FIFO not empty interrupt enable	FIFO not empty interrupt enable
	6	MATCH flag interrupt enable	MATCH flag interrupt enable
	5	N/U	N/U
	4	External event enable 1=enable 0=disable set to 0 by reset	External event enable 1=enable 0=disable
	3	MATCH flag	1 = clear flag 0 = no change
	2	In-sync flag 1 = in-sync 0 = non in-sync	Read only
	1	Time code input decodable flag 1 = decodable 0 = not decodable	Read only
	0	FIFO empty flag 0 = empty 1 = not empty	Read only
3	7..0	Data FIFO	Command Port
5	7..0	Interrupt vector	Interrupt vector
9	7..0	N/U	Simulate external event (write any data pattern)
D	7..0	N/U	Reset FIFO and release microcomputer reset
F	7..0	N/U	Assert microcomputer reset
8	15..0 (WORD)	Time ( $10^3 \mu\text{S}..10^0 \mu\text{S}$ ) Reading this word latches higher order words	N/U
A	15..0 (WORD)	Time (seconds & 100s, 10s or milliseconds)	N/U
C	15..0 (WORD)	Time (hours & minutes)	N/U
E	15..0 (WORD)	Time (days)	N/U

**Table 3.1: Register Assignments**

# Chapter Four

---

## ID Data



Offset from Base Address	Contents	Comments
81	49	ASCII "I"
83	50	ASCII "P"
85	41	ASCII "A"
87	43	ASCII "C"
89	4F	KSI ID
8B	0	
8D	0	
8F	0	
8F	0	
91	0	
93	0C	ID SIZE
95	CE	CRC

**Table 4.1: - ID Data**

# Chapter Five

---

## Configuration

## Input/output connections

For modulated IRIG-B input operation

Connect the modulated IRIG-A or IRIG-B source to the IP carrier header pin 1 and the signal ground to pin 2.

Connect the diagnostic LED anode (long lead) to pin 22 and the cathode (short lead) to pin 23.

If using external event input, connect it to pin 9. Else ground pin 9 to pin 10.

Connect pin 31 to pin 32 so IPPS TTL level input doesn't float.

## Base address

The base address of the TPRO-IP in user host space is determined by configuration of the IP carrier and by which slot in the IP carrier the TPRO-IP is placed. For example, the Greenspring Computers VIP310 VME bus dual IP carrier has a factory default base address of 6000 (for IP slot A) in A16 space.

## Interrupt request level

The host bus interrupt level associated with the IRQ0 level signal generated by the TPRO-IP is determined by configuration of the IP carrier. For example, the Greenspring Computers VIP310 VME bus dual IP carrier has a factory default VME bus IRQ41 for slot A and IRQ2L for slot B.

# Chapter Six

---

## Installation

# Installation

---



*Before installing the TPRO-IP in your system, please make a record of the serial number, the PWB Revision level (example A1 or A) the firmware version labeled on EPROM U3 (example: 4A274A22) and the version labels on FPGA devices U5 (example: 4B01A). This information is required for telephone support of the product. Please make the record known to anyone who may require support.*

---

Shut down the system, and install the TPRO-IP board in a IP carrier slot. The TPRO-IP has inputs and outputs that should be connected for the users requirements. There are up to two inputs from the external world: input time code (if used) and a TTL external event pulse (if used). For the TPRO-IP, if input time code is not provided, the board will provide "local" timing starting at 000 days, 00 hours, 00 minutes, 00 seconds. The external event pulses may come from external user equipment, or pulse outputs from the TPRO-IP may be looped back and used as external event inputs with a simple jumper connection. Custom factory configurations will have a manual addendum detailing non-standard I/O configuration.

Start the system.

# Chapter Seven

---

## Operation

## General

The TPRO-IP operates automatically as soon as the host computer system does the power-on reset. To change the operating parameters or read data consult the Programming section. A status LED can be connected to the 50-pin IP carrier I/O connector for flashing a status pattern to assist in diagnosing installation errors. The pattern is a sequence of short and long flasher. Trailing short flashes are deleted so the status pattern can repeat more frequently.

Flash Position	Meaning of short (cleared) flash	Meaning of long (set) flash
1		Modulated timecode input being used for time reference
2	Synchronization to better than 5 $\mu$ S verified with last 5 seconds	Synchronization to better than 5 $\mu$ S not verified within last 5 seconds
3		In applications with modulated time code inputs only, this status bit will always be set
4		In applications with modulated timecode inputs only, this status bit will always be set
5		In applications with modulated time code inputs only, this status bit will always be set
6	Timecode input being decoded	Timecode input not decodable. In applications without modulated timecode inputs, this status bit will always be set

## Propagation Delay Adjustment

Depending on the actual absolute time accuracy required in the user's application, the TPRO-IP may be commanded to correct for the time required for the time code signal to travel the distance between the time code source and the IP host computer. This delay time is called "propagation delay time" and is about 3.3 microseconds per kilometer for radio time code transmission and about 5  $\mu$ S per kilometer for copper wire transmission. There is also a time delay on the order of 25  $\mu$ S that may be caused by small phase shifts due to reactance's at the time code input. To correct for propagation delay, the TPRO-IP can use a propagation delay correction setting ranging between -1000 (because sometime sources transmit early) and +8999  $\mu$ S. The default setting is 0  $\mu$ S after the TPRO-IP is reset at power-on or after a RESET command from the user. Users can change the setting by a sequence of programmed commands to the command register on the TPRO-IP. If absolute microsecond accuracy is required, the user will probably need to calibrate the TPRO-IP when it is installed for propagation delay correction by comparing the on-board clock time with a portable reference. The correct propagation delay correction setting is converted on rapidly by trial and error. This setting will not need to be changed unless the location or cabling of the installation is changed. Determining the correct propagation delay setting will probably need the help of a special user program to let various propagation delay settings be tried experimentally while zeroing in on the correct setting. The normal user program should have the capability of using the correct setting once it is determined.

# Chapter Eight

---

## Input/Output Pin Assignments



# 50 Pin IP Carrier Header (P1)

## Input/Output Pin Assignments

Pin	Signal
1	Ground
2	System Clock 8 MHz
3	Reset Low
4-19	SD0-SD15
20	BS0 Low
21	BS1 Low
22	-12V
23	+12V
24	+5V
25-26	Ground
27	+5V
28	System Read Write Low
29	ID Select
30	Not Used
31	Memory Select
32	Not Used
33	Interrupt Select
34	Not Used
35	Input/Output Select
36	Reserved
37	SA1
38	Not Used
39	SA2
40	Not Used
41	SA3
42	Interrupt Request 0 Low
43	SA4
44	Interrupt Request 1 Low
45	SA5
46	Not Used
47	SA6
48	ACK Low
49	Reserved
50	Ground

## 50 Pin IP Carrier Header (P2)

PIN	Signal
1	Modulated timecode input
2	Ground
3	Not used. User should not make connection to these pins.
4,6	Not used. User should not make connection to these pins.
5,7	Not used. User should not make connection to these pins.
8	Not used. User should not make connection to these pins.
9	External event (positive going edge) TTL level input
10	Ground
11	Not used. User should not make connection to these pins.
12	Not used. User should not make connection to these pins.
13	Spare output #1 for future customization
14	Ground
15	Not used. User should not make connection to these pins.
16	Not used. User should not make connection to these pins.
17	Spare output #2 for future customization
18	Ground
19	Not used. User should not make connection to these pins.
20	Ground
21	Not used. User should not make connection to these pins.
22	+5V output for anode side of diagnostic LED. LED must have internal current limiting resistor. <b>WARNING: Users should exert extreme care in connections to pin 22. Shorting pin 22 to ground or +12V can damage the TPRO-IP or the host system.</b>
23	Cathode side of diagnostic LED
24	Ground
25	+12V output <b>WARNING: Users should exert extreme care in connections to pin 25. Shorting pin 25 to ground or +5V can damage the TPRO-IP or the host system.</b>
26	SPARE3 input for future customization
27	Not used. User should not make connection to these pins.
28,30	Not used. User should not make connection to these pins.
29	Not used. User should not make connection to these pins.
31	Ground side of 47 ohm termination resistor connected to pin 4, 6. Connect to pin 32 to terminate pin 4 or 6 in 47 ohm resistor
32	Ground
33	IRIG-A future customization option. Connects to pin 34 for IRIG-A input
34	IRIG-A future customization option. Connects to pin 33 for IRIG-A input
35,37	Not used. User should not make connection to these pins.
36	Not used. User should not make connection to these pins.
38	IRIG-B DC level shift TTL output
39	MATCH signal TTL level output
40	GATES signal TTL level output
41-50	Microprocessor signal connections for logical analyzer <b>User should make no connections to pins 41-50</b>

***This page intentionally left blank***

# Chapter Nine

---

## Programming

User programs interface to hardware and firmware functions of the TPRO-IP. The hardware functions used are:

- Reading the clock through the 16 bit registers
- Reading the status register
- Initializing the data FIFO
- Reading the data FIFO to read external event time tags or command responses
- Enabling/disabling interrupts
- Forcing hardware reset

Firmware functions are initiated by writing 8 bit commands to the command port of the TPRO-IP.

Test programs in the Appendix (Page 36) show examples of these functions.

## Reading the clock through the 16-bit registers

To measure the instantaneous time, a program first does a work I/O read from the low order 16 bit time register at base address + 8. When the low order register is read, the 3 high order time words are stored at the same time in an internal registers in the TPRO-IP. The 3 registers will be frozen until the low order time register is read again. So, whenever the high order registers are read, the time that is returned is the time when the low order register was last read. Any (or none) of the 3 high order registers may be read according to the user's application.

Bits	15	12	11	8	7	4	3	0
Data	10 <sup>3</sup> μS BCD		10 <sup>2</sup> μS BCD		10 <sup>1</sup> μS BCD		10 <sup>0</sup> μS BCD	

Data organization (base address + offset 8)

Bits	15	12	11	8	7	4	3	0
Data	10 second BCD		1 second BCD		10 <sup>5</sup> μS BCD		10 <sup>4</sup> μS BCD	

Data organization (base address + offset A)

Bits	15	12	11	8	7	4	3	0
Data	10 hour BCD		1 hour BCD		10 minute BCD		1 minute BCD	

16-bit word data organization (base address + offset C)

Bits	15	12	11	8	7	4	3	0
Data	0	10 <sup>2</sup> days BCD		10 day BCD		1 day BCD		

Data organization (base address + offset E)

# Status

The meaning of the status bits is defined in the Specifications section of this manual. The Match Interrupt Enable, FIFO Not Empty Interrupt, External Event Enable and Match Flag bits are Read/Write, while all others are read only.

## FIFO Initialization

When a user program starts using the TPRO-IP there may be stale external event or command response data in the FIFO. To initialize the FIFO the user can do a write (any data) to the FIFO Reset port, or the user can just read the FIFO 512 times. Right after initialization, the user should check the FIFO Empty Flag for "0" in case an external event just happened while initializing. Once initialization is done, it does NOT need to be done again so long as the user program makes sure that any data put in the FIFO (in response to external events or user commands) is emptied out by user programs.

## Reading the FIFO

The user program should ALWAYS check the FIFO EMPTY flag (bit 0) for "1" before reading a byte from the FIFO. Otherwise user programs may be reading FIFO data out faster than the TPRO-IP firmware is writing data into the FIFO. Data is always written in 10 byte groups to the FIFO by the TPRO-IP firmware.

## External Event Time Tagging

The External Event Enable bit (Bit 4 in the Status Register) must be a "1" for External Event Time Tags to occur. The enable bit will be cleared by a power on or programmed RESET. Once set to "1" the Enable bit will stay at "1" until written to "0" or a reset occurs.

In response to a rising edge at the external event input (pin 9 on the 50-pin IP header), the TPRO-IP copies the 10 bytes of time data into the on-board FIFO. It takes about 50  $\mu$ seconds until the last of the 10 bytes is copied into the FIFO. The transfer time fluctuates because the microcomputer may be interrupted while putting data in the FIFO. The time data is accurate to the exact  $\mu$ second when the event occurred and the accuracy is not affected by the transfer time.

The occurrence of an external event pulse can be simulated by doing a byte I/O write (any data value) to base address + 3. The simulated external event does not require that the External Event Enable bit in the Status Register be set.

The host program reads captured time information (100s of days through units of  $\mu$ seconds - a total of 10 bytes) sequentially from the FIFO through the TPRO-IP bus interface. Handshaking is done by the host testing the FIFO NOT EMPTY bit (bit 0) of the TPRO-IP status register (base + 1) for "1" *before* each byte is read from the data FIFO (base + 3). The data format for FIFO time stamps is:

<b>Byte</b>	<b>High Nibble</b>	<b>Low Nibble</b>
0	not defined	not defined
1	not defined	defined
2	0	$10^2$ days
3	$10^1$ days	$10^0$ days
4	$10^1$ hours	$10^0$ hours
5	$10^1$ minutes	$10^0$ minutes
6	$10^1$ seconds	$10^0$ seconds
7	$10^5$ $\mu$ seconds	$10^4$ $\mu$ seconds
8	$10^3$ $\mu$ seconds	$10^2$ $\mu$ seconds
9	$10^1$ $\mu$ seconds	$10^0$ $\mu$ seconds

## Interrupts

The host bus interrupt vector is set by writing to the TPRO-IP base address + 5. The TPRO-IP may be programmed to request interrupts at IRQ0 level upon selectable conditions. Interrupts may be enabled by writing a "1" into the corresponding interrupt enable bit in base address + 1.

<b>Interrupt Condition</b>	<b>Condition Asserted By</b>	<b>User Action to Deassert Condition</b>
FIFO not empty	External event or user command causes on board microprocessor to write data into FIFO	I/O read data from FIFO until FIFO empty or write to FIFO reset port
Match Flag Set	User programmed START or STOP MATCH time is detected	I/O write to base +1 with bit 3 = 1

# Forcing Hardware Reset

The user can reproduce the effect of the host power on reset on the TPRO-IP by writing (any data) to the Assert Microprocessor Reset port (base + F). The RESET will remain asserted until the user writes (any data) to the Reset FIFO port (base + D).

## Commands

Commands are sent as a sequence of bytes to the TPRO-IP command register (base address + 3). All commands should be spaced at least 100  $\mu$ sec apart so the TPRO-IP firmware has enough time to handle each command. An easy way to generate a processor speed independent 100 $\mu$ sec time delay is to read the TPRO-IP status register 100 times. Without any commands, on cold or warm start the TPRO-IP will automatically synchronize to a modulated time code input.

There are commands for:

- Setting time
- Setting propagation delay correction for modulated code input
- Disabling synchronization to input
- Re-enabling synchronization to input
- Simulating power-on reset of TPRO-IP firmware
- Setting MATCH START and MATCH STOP times



<b>Command</b>	<b>Hi Nibble</b>	<b>Lo Nibble</b>
Set time set register 10 <sup>3</sup> μS	0	0-9
Set time set register 10 <sup>2</sup> μS	1	0-9
Set time set register 10 <sup>1</sup> μS	2	0-9
Set time set register 10 <sup>0</sup> μS	3	0-9
Set next 1pps time	4	C
Enable resync	4	D
Disable sync	4	E
Reset TPRO-IP firmware	4	F
Set time set register 102 days	5	0-3
Report cog/sog/sats	5	C
Report altitude	5	D
Report longitude	5	E
Report latitude	5	F
Set time set register 10 <sup>1</sup> days	6	0-9
Set time set register 10 <sup>0</sup> DAYS	7	0-9
Set time set register 10 <sup>1</sup> HOURS	8	0-9
Set time set register 10 <sup>0</sup> HOURS	9	0-9
Set time set register 10 <sup>1</sup> MINUTES	A	0-F
Set time set register 10 <sup>0</sup> MINUTES	B	0-F
Set time set register 10 <sup>1</sup> SECONDS	C	0-F
Set time set register 10 <sup>0</sup> SECONDS	D	0-F
Copy time set register to clock time	E	0
Copy time set register to start/stop hold	E	1
Copy start/stop hold to start match register (days.seconds		
And time set register (hours,minutes,seconds) to start μS	E	2
Copy start/stop hold to stop match register (days.seconds)		
And time set register (hours,minutes,seconds) to stop μS	E	3
Clear match flag	E	4
Report firmware ID in FIFO	E	9
Clear set time register	F	0

# Setting Time

The user may set the TPRO-IP for applications where the input reference is not used to be used. If the user does not preset a time, a default preset of 0 days through seconds is used. Setting time will usually be preceded by disabling input synchronization. Otherwise, the TPRO-IP firmware will just switch back from the commanded time to the input time as soon as the input is validated. The sequence of commands for setting time is:

Send CLEAR TIME SET REGISTER command (F0h)

Send SET TIME SET REGISTER commands (5<bcd> through 8<BCD>) for 10<sup>2</sup> days through 10<sup>0</sup> seconds in any order

Send COPY TIME SET REGISTER command (E0h)

At least 100  $\mu$ S should be allowed between sending each command byte. For example to set time to 123 days 01 hours 23 minutes 45 seconds, the sequence F0 51 62 73 80 91 A2 B3 C4 D5 E0 would be sent. As each SET TIME SET REGISTER command is sent, the corresponding digit in an internal time set

buffer in the TPRO-IP will be set. When the COPY TIME SET REGISTER command (E0) is received; the time set buffer will be copied to the clock.

## Setting Propagation Delay Correction

The user may set the compensation for propagation delay between the time code source and the TPRO-IP location. On cold or warm start, the TPRO-IP will assume a propagation delay correction of 0  $\mu$ S. The sequence of commands for setting propagation delay correction is:

1. Send CLEAR TIME SET REGISTER command (F0h)
2. Send SET TIME SET REGISTER commands (0<bcd> to 3<bcd>)  
For 10<sup>3</sup>  $\mu$ S, 10<sup>2</sup>  $\mu$ S, 10<sup>1</sup>  $\mu$ S, 10<sup>0</sup> $\mu$ S, digits in any order
3. Send SET COPY TIME SET REGISTER command (E0h)

Remember to delay at least 100  $\mu$ S between sending each command byte. For example to set a propagation delay correction value of 1234  $\mu$ S, the sequence F0 31 22 13 04 E0 would be sent. Some central timing facilities transmit time codes advanced by 1 millisecond. To correct for the advanced time code, it may be desirable to use a negative propagation delay correction setting. Propagation delay settings of 9000  $\mu$ S to 9999  $\mu$ S are used to set NEGATIVE propagation delay correction values of -1000  $\mu$ S to -1 $\mu$ S respectively. For example, to set -500  $\mu$ S use a setting of 9500  $\mu$ S. So, the propagation delay correction range of the TPRO-IP is -1000  $\mu$ S to +8999  $\mu$ S. The TPRO-IP can distinguish between COPY TIME SET commands used for setting propagation delay and COPY TIME SET commands used for setting time by noting that different intervening commands have occurred after the CLEAR TIME SET REGISTER command.

## Disabling Synchronization to Input

To prevent the TPRO-IP from synchronizing its time to input signals, send the DISABLE RESYNC (4Eh) command to the TPRO-IP. This is normally used when you set the TPRO-IP time using the Set Generation Time procedure.

## Re-enabling Synchronization to Input

To release the TPRO-IP from a DISABLE RESYNC command, send the ENABLE RESYNC (4Dh) command to the TPRO-IP. The cold or warm start condition for the TPRO-IP is resync enabled.

## Simulating Power-on Reset of TPRO-IP Firmware

The RESET (4Fh) command to the TPRO-IP rests the on-board Z80 microcomputer.

# Chapter Ten

---

## Preventative Maintenance

Oscillator Aging Adjustment (applies only to models equipped with -O option ovenized oscillator)

The Oscillator aging adjustment for the TPRO-IP corrects for the effects of aging on the natural crystal oscillator frequency to insure that the undisciplined frequency of the 10 MHz oscillator is  $10.000000 \text{ MHz} \pm 10 \text{ Hz}$ .

This preventive maintenance should be once every 2 years.

You will need

- A digital frequency counter with 1 PPM or better accuracy and 1 HZ or better resolution (be *sure* that the counter is calibrated)
- A small screwdriver

If you have a custom crystal oscillator in your unit, consult the oscillator data sheet for adjustment method.

Extend the carrier module on which the TPRO-IP is mounted.

Connect a *calibrated* frequency counter to the 10 MHz signal at XO1 pin 8.

Power the system up and wait at least five minutes for the on-board crystal oven temperature to stabilize. Then adjust R10 (using the "solder side" access hole) for  $10\text{MHz} \pm 10\text{Hz}$ . If R10 is not present, you do not have the -O option and cannot adjust the oscillator.

Power down your system, and reinstall carrier without extender

# Chapter Eleven

---

## Troubleshooting

## Before you contact KSI

Have the serial number, Rev level, firmware and FPGA ID you were instructed to record during installation. Please include them in any faxes. Try to exhibit the problem in as reduced (fewest boards in the system) configuration as you can. Try to run our examples, modified as little as possible, to be sure that what you think is a hardware problem is really a software problem.

## Bus Crashes

If your program crashes due to a bus error when trying to access the TPRO-IP your problem may be:

Board address configured for IP carrier slot used by TPRO-IP doesn't agree with what your Program uses.

## Bad data from 16bit data registers

If your program doesn't crash but gets crazy (illegal BCD etc) data from the 16 bit registers your problem may be:

- You are using an address that maps into a different host bus device. To check this hypothesis, remove the TPRO-IP from the IP carrier. If you still can access data from the same address, you are not addressing the TPRO-IP.
- You are using a base address that maps into both the TPRO-IP and another host bus device.
- You are accessing high order bits at base +A, +C, or +E before freezing & reading low order bits at base +8.
- You are reading data (especially if there's lots or zeros) before the TPRO-IP has synchronized to the input code. Remember that there is about a 20-second delay from power on before the TPRO-IP jam syncs to the input code.
- You did a TIME SET command sequence with crazy values

## Bad data from FIFO port

If your program doesn't crash, but has crazy (illegal BCD etc) data from the FIFO your problem may be:

- Your code doesn't check the FIFO NOT EMPTY bit in the STATUS REGISTER for "1" *before* reading each byte from the FIFO. If your data contains "00" or seems to slip (hours show up where you expected minute's etc) this is very likely the reason.
- You are reading data (especially if there's lots of zeros) before the TPRO-IP has synchronized to the input code. Remember that here is about a 20-second delay from power on before the TPRO-IP jam syncs to the input code. You did a TIME SET command sequence with crazy values.
- You are using an address that maps into memory or into a different device.

# Interrupt crashes

Make sure that the interrupt vector register is correctly initialized.

Make sure that the host bus IRQ level agrees with the configuration of the IP carrier for the slot in which the TPRO-IP is installed.

If you are using the FIFO NOT EMPTY interrupt selection, disable the interrupt enable either at the TPRO-IP or at the host interrupt controller while reading the FIFO or you may cause nested FIFO NOT EMPTY interrupts as each byte is read from the FIFO and the IRQ line toggles.

# Board never syncs to input code

If the "in-sync" status bit is "0" (indicating an error).

In-sync *should* be "0" in many cases. A "0" does not mean that there is a fault in the board. Remember that there is about a 20 second delay from power on before the TPRO-IP jam syncs to the input code.

Does the diagnostic LED indicate decodable input signal? If not, the TPRO-IP doesn't see a signal that it can decode. Check signal amplitude and connections.

Examine the input signal on an oscilloscope and make sure that it meets the input specifications of the TPRO-IP. Is the time code carrier frequency stable to  $\pm 100$  PPM? Does it make periodic large (larger than 5  $\mu$ S) time jumps? Tape playback is very likely to have high frequency error unless you use a calibrated servo track to accurately control speed.



***This page intentionally left blank***

# Appendix

---

## Firmware Sample Code

```

3
4
5
6
7 00FF 0000 ILLEGAL EQU $FF0000
8 00FF 6001 IPSTS EQU $FF6001
9 0000 0000 BSTSOR EQU 0 BIT0: FIFO NOT EMPTY READ ONLY.
10 0000 0001 BSGOK EQU 1 BIT1: INPUT TIME CODE DECODEABLE. READ ONLY
11 0000 0002 BSYNCOK EQU 2 BIT2: GOOD SYNC READ ONLY
12 0000 0003 BMAT EQU 3 BIT3: MATCH STATUS. READ ONLY
13 0000 0004 BEXTENB EQU 4 BIT6: EXTERNAL EVENT ENABLE. READ/WRITE
14 0000 0006 BMATIE EQU 6 BIT4: MATCH INTERRUPT ENABLE. READ/WRITE
15 0000 0007 BORIE EQU 7 BIT7: FIFO NOT EMPTY INTR ENABLE. READ/WRITE
16 00FF 6003 IPCMD EQU $FF6003 COMMAND PORT (WRITE ONLY)
17 00FF 6003 IPFIFO EQU $FF6003 FIFO DATA PORT (READ ONLY)
18 00FF 6005 IPVEC EQU $FF6005 INTR VECTOR FOR IRQ0 (READ/WRITE)
19 00FF 6009 IPTAG EQU $FF6009 SIMULATED EXTERNAL EVENT PORT. WRITE ONLY
20 00FF 600D IPFIFR EQU $FF600D FIFO RESET. ALSO CLEARS RESET. WRITE ONLY
21 00FF 600F IPRESET EQU $FF600F LOCKS TPRO-IP IN RESET. WRITE ONLY
22 00FF 6008 IPLO EQU $FF6008 A16 BUS WINDOW FOR MVME133+BASE+8 OFFSET
23 00FF 600E IPHI EQU $FF600E A16 BUS WINDOW FOR MVME133+BASE+E OFFSET
24 00FF 6081 IPID EQU $FF6081 ID DATA. SEE IDCHK FOR CORRECT CONTENTS
25 000000 2A7C 0000 0533 START: MOVEA.L #STRMSG,A5
26 000006 6100 0390 BSR MESSAGE
27 *****SCAN A16 SPACE FOR DTACKS. TPRO-IP SHOULD BE AT 60XX. AITG MAYBE 0A0X
28 00000A 23CF 0000 03A6 MOVEA.L A7,SPSAV
29 000010 2038 0008 MOVE.L $8,D0
30 000014 7201 MOVE.L #1,D1 INCREMENT FOR ADDRESS ON 1ST PASS
31 000016 3801 MOVE D1,D4 INIT AITG-VME NOT FOUND
32 000018 3801 MOVE D1,D4 INIT TPRO-IP NOT FOUND
33 00001A 23F8 0008 0000 03AA MOVE.L $8,SPSAV+4
34 000022 21FC 0000 006E 0008 MOVEA.L #TRAPISR,$8 ADDRESS OF INTR SERVICE ROUTINE FOR BERR
35 00002A 227C 00FE FFFF MOVEA.L #ILLEGAL-1,A1
36 000030 D3C1 INCNEXT:ADD.L D1,A1
37 000032 1411 NEXT: MOVE.B (A1),D2
38 000034 3609 MOVE A1,D3
39 000036 0243 FF00 AND #$FF00,D3
40 00003A 0C43 6000 CMP.W #$6000,D3 IF IN TPRO-IP RANGE, WILL=0
41 00003E 6700 0028 BEQ DT60XX
42 000042 0C43 A000 CMP.W #$A000,D3 IF IN AITGVME RANGE, WILL=0
43 000046 6700 001A BEQ DT0A0X
44 00004A 2A7C 0000 0597 MOVEA.L #MYSTER,A5
45 000050 6100 0340 BSR FATAL
46 000054 2A7C 0000 056E NO60XX: MOVEA.L #NODTACK,A5
47 00005A 6100 033C BSR MESSAGE
48 00005E 7200 MOVE.L #0,D1 PREVENT FURTHER ADDR INCR FOR SCOPE LOOP
49 000060 60D0 BRA NEXT
50 000062 383C 0000 DT0A0X: MOVE #0,D4 FLAG AITG-VME FOUND
51 000066 60C8 BRA INCNEXT
52 000068 3A3C 0000 DT60XX: MOVE #0,D5 FLAG TPRO-IP FOUND
53 00006C 60C2 BRA INCNEXT
54 00006E 2E79 0000 03A6 TRAPISR: MOVEA.L SPSAV,A7 POP TRAP ADDR
55 000074 B3FC 00FF FFFF CML.L #$0FFFFFFF,A1 EXHAUSTED A16 SPACE ?
56 00007A 66B4 BNE INCNEXT NO
57 00007C 8A45 OR D5,D5 YES - WAS TPRO-IP DTACK FOUND ?
58 00007E 66D4 BNE NO60XX NO
59 000080 21F9 0000 03AA 0008 MOVE.L SPSAV+4,$8 YES - RESTORE ORIG BERR ISR

```

```

60 ***** CHECK ID DATA *****
61 000088 2A7C 0000 05C2      MOVEA.L #IDBEG,A5
62 00008E 6100 0308          BSR MESSAGE
63 000092 323C 03E8          MOVE #1000,D1      LOOP COUNT FOR 1000 CHECKS OF ID DATA
64 000096 227C 00FF 6081      IDLOP1 MOVEA.L #IPID,A1
65 00009C 247C 0000 041F      MOVEA.L #IDCHK,A2
66 0000A2 303C 000B          MOVE #11,D0      CHECK 12 BYTES
67 0000A6 B509          IDLOP2 CMP.B (A1)+,(A2)+
68 0000A8 6600 0010          BNE IDBADA
69 0000AC 4A19          TST.B (A1)+      TEST ONLY ODD BYTE ADDRESSES
70 0000AE 51C8 FFF6          DBF D0,IDLOP2    CHECK 12 BYTES EACH PASS
71 0000B2 51C9 FFE2          DBF D1,IDLOP1    DO 1000 PASSES
72 0000B6 6000 0012          BRA IE           IF ALL 12 BYTES OK FOR ALL PASSES
73 0000BA 4A21          IDBADA TST.B -(A1)     MOVE ADDRESS BACK TO ERROR ADDRESS
74 0000BC 2A7C 0000 05F4      MOVEA.L #IDBAD,A5
75 0000C2 6100 02D4          BSR MESSAGE
76 0000C6 4A11          IDBADL TST.B (A1)     LOOP ON BAD ADDRESS
77 0000C8 60FC          BRA IDBADL
78 ***** TEST IE BITS CAN BE SET *****
79 0000CA 2A7C 0000 0624      IE MOVEA.L #IETST,A5
80 0000D0 6100 02C6          BSR MESSAGE
81 0000D4 13FC 00C0 00FF 6001  MOVE.B #(1.SHL.BORIE)+(1.SHL.BMATIE),IPSTS
82 0000DC 1039 00FF 6001      MOVE.B IPSTS,D0
83 0000E2 0200 00C0          ANDI.B #(1.SHL.BORIE)+(1.SHL.BMATIE),D0
84 0000E6 0C00 00C0          CMPI.B #(1.SHL.BORIE)+(1.SHL.BMATIE),D0
85 0000EA 6700 000C          BEQ IESETOK
86 0000EE 2A7C 0000 065A      MOVEA.L #IENOSSET,A5
87 0000F4 6100 02A2          BSR MESSAGE
88 ***** TEST RESET CLEARS IE BITS *****
89 0000F8 2A7C 0000 0681      IESETOK MOVEA.L #RSTTST,A5
90 0000FE 6100 0298          BSR MESSAGE
91 000102 13C0 00FF 600F      MOVE.B D0,IPRESET
92 000108 0839 0006 00FF 6001  BTST.B #BMATIE,IPSTS
93 000110 6700 000C          BEQ FIFO
94 000114 2A7C 0000 06BA      MOVEA.L #RSTBAD,A5
95 00011A 6100 0276          BSR FATAL
96 00011E 2A7C 0000 06EE      FIFO MOVEA.L #FIFTST,A5
97 000124 6100 0272          BSR MESSAGE
98 000128 13C1 00FF 600D      MOVE.B D1,IPFIFR  PURGE FIFO
99 00012E 0839 0000 00FF 6001  BTST.B #BSTSOR,IPSTS  MAKE SURE FIFOOR=0 AFTER PURGE
100 000136 6700 0002          BEQ ECHTST
101 *****COMMAND TPRO-IP INTO ECHO MODE & ECHO 1B-FF, 01-1A 100 TIMES *****
102 00013A 2A7C 0000 077C      ECHTST MOVEA.L #ECHOBEG,A5
103 000140 6100 0256          BSR MESSAGE
104 000144 13FC 001B 00FF 6003  MOVE.B #$1B,IPCMD  PUT TPRO-IP IN ECHO MODE
105 00014C 303C 07D0          MOVE #2000,D0
106 000150 6100 01D2          BSR WT100L      WAIT FOR "1B" TO ECHO
107 000154 4A39 00FF 6003      TST.B IPFIFO    PURGE 1B
108 00015A 343C 0014          MOVE #20,D2     DO 20 LOOPS OF ALL VALUES
109 00015E 123C 0000          ECHOTOP:MOVE.B #0,D1
110 000162 0601 0001          CMDLOP:ADDI.B #1,D1
111 000166 6700 000E          BEQ WTECHOL     IF 1-255 WRITTEN TO CMD PORT
112 00016A 6100 01B4          BSR WT100
113 00016E 13C1 00FF 6003      MOVE.B D1,IPCMD
114 000174 60EC          BRA CMDLOP
115 000176 0601 0001          WTECHOL:ADDI.B #1,D1
116 00017A 6700 002E          BEQ ECHLOP2

```

```

117 00017E 0839 0000 00FF 6001      BTST.B #0,IPSTS   BYTE SHOULD BE ECHOED TO FIFO NOW
118 000186 6700 0016                   BEQ  NOECHER     IF NOT, REPORT NO ECHO & TRY AGAIN
119 00018A 1639 00FF 6003             MOVE.B IPFIFO,D3  COMPARE ECHOED BYTE WITH ORIGINAL
120 000190 B203                           CMP.B  D3,D1
121 000192 67E2                           BEQ  WTECHOL
122 000194 2A7C 0000 07BE   BADECH MOVEA.L #ECHOBAD,A5
123 00019A 6100 01F6                   BSR  FATAL
124 00019E 2A7C 0000 07F2   NOECHER:MOVEA.L #NOECHO,A5
125 0001A4 6100 01F2                   BSR  MESSAGE
126 0001A8 60FE                       HERE  BRA  HERE
127 0001AA 51CA FFB6   ECHLOP2 DBF  D2,CMDLOP   DO ALL 255 VALUES 100 TIMES
128 0001AE 13C1 00FF 6003             MOVE.B D1,IPCMD   REMOVE FROM ECHO MODE. 00 BYTE WILL ECHO
129 0001B4 6100 016A                   BSR  WT100
130 0001B8 1039 00FF 6003             MOVE.B IPFIFO,D0  CLEAR OUT 00 BYTE FROM FIFO
131 0001BE 2A7C 0000 082E             MOVEA.L #ECHOOK,A5
132 0001C4 6100 01D2                   BSR  MESSAGE
133 0001C8 323C 0000                   MOVE #0,D1   TRY 0-255 VECTOR PATTERN
134 0001CC 13C1 00FF 6005   VECLOP MOVE.B D1,IPVEC   WRITE TO INT VECTOR REG
135 0001D2 B239 00FF 6005             CMP.B IPVEC,D1
136 0001D8 6600 0012                   BNE  BADVECT
137 0001DC 0601 0001                   ADDI.B #1,D1   ALL DONE ?
138 0001E0 66EA                       BNE  VECLOP   NO
139 0001E2 2A7C 0000 0891             MOVEA.L #VECOK,A5
140 0001E8 6000 0008                   BRA  INT0TST
141 0001EC 2A7C 0000 0868   BADVECT MOVEA.L #VECERR,A5  REPORT BAD VECTOR ECHO
142                                     *****CHECK THAT IPPS, NOSYNC, INSYNC AND FIFO INTERRUPTS WORK OK
143 0001F2 6100 01A4   INT0TST BSR  MESSAGE
144 0001F6 21FC 0000 0382 0100         MOVEA.L #INT0ISR,$100
145 0001FE 3A3C 0019                   MOVE # $19,D5   INIT INTR PRIORITY TO 1
146 000202 383C 2000                   MOVE # $2000,D4 SET STS LEV = TO ALLOW INTR1
147 000206 13FC 0040 00FF 6005         MOVE.B # $40,IPVEC
148 00020E 46C4                       MOVE  D4,SR     SET STS LEV = TO ALLOW INTRX
149 000210 13FC 0000 0000 03AE         MOVE.B #0,SPSAV+8 INIT INTR COUNTS
150 000218 13FC 0000 00FF 6009         MOVE.B #0,IPTAG  FORCE EVENT DATA INTERRUPT
151 000220 13FC 0080 00FF 6001         MOVE.B # $80,IPSTS  ENABLE FIFO RDY INTR
152 000228 6100 00F6                   BSR  WT100   WAIT FOR EVENT INTR
153 00022C 2A7C 0000 094B             MOVEA.L #INTROK,A5  REPORT IRQ0 OK AT CURRENT L,A6
154 000232 0C39 0000 0000 03AE         CMPL.B #0,SPSAV+8  EVENT INTR OK ?
155 00023A 6600 0008                   BNE  IRQRPT   YES
156 00023E 2A7C 0000 091F             MOVEA.L #NOEVTI,A5  REPORT MISSING EVENT INTR.
157 000244 6100 0152   IRQRPT BSR  MESSAGE
158                                     *****CHECK SECONDS 0-59 PARALLEL=FIFO TIME*****
159 000248 13C0 00FF 600D   CHKSEC MOVE.B D0,IPFIFR  CLEAR FIFO OF IRQ0 TEST DATA
160 00024E 6100 00E2                   BSR  TAGNPAR   GET TIME TAG FIFO DATA & PARALLEL TIME
161 000252 207C 0000 03BA             MOVEA.L #HISAV+8,A0
162 000258 247C 0000 03C2             MOVEA.L #DELTA+8,A2
163 00025E 023C 0000                   ANDI.B #0,CCR
164 000262 1520                       MOVE.B -(A0),-(A2) DELTA = PARALLEL - FIFO
165 000264 4A1A                       TST.B (A2)+    SBCD NEEDS AUTODEC MODE
166 000266 8509                       SBCD  -(A1),-(A2)
167 000268 323C 0006                   MOVE #6,D1     DO 7 MORE BYTES
168 00026C 1520                       DELTLOP MOVE.B -(A0),-(A2) DELTA = PARALLEL - FIFO
169 00026E 4A1A                       TST.B (A2)+    SBCD NEEDS AUTODEC MODE
170 000270 4200                       CLR.B D0       SET Z
171 000272 8509                       SBCD  -(A1),-(A2)
172 000274 6600 003E                   BNE  NONZERO   ** REPLACE WITH NO-OP FOR WW PROTO **
173 000278 51C9 FFF2                   DBF  D1,DELTLOP

```

```

174 00027C 1039 0000 0431          MOVE.B EVTDAT+6,D0
175 000282 B039 0000 041E          CMP.B SECSAV,D0    SECONDS CHANGE ?
176 000288 67BE                    BEQ  CHKSEC
177 00028A 13F9 0000 0431 0000    MOVE.B EVTDAT+6,SECSAV
      041E
178 000294 2A7C 0000 097B          MOVEA.L #TICMSG,A5  YES - WRITE A TIC
179 00029A 6100 00FC                BSR  MESSAGE
180 00029E 4A39 0000 0430          TST.B EVTDAT+5    MINUTES NON-ZERO ?
181 0002A4 67A2                    BEQ  CHKSEC        NO - KEEP GOING
182 0002A6 2A7C 0000 08B1          MOVEA.L #DELTOK,A5
183 0002AC 6100 00EA                BSR  MESSAGE
184 0002B0 6000 000C                BRA  CHKMD         YES - CHECK MINUTES..DAYS
185 0002B4 2A7C 0000 08EE  NONZERO MOVEA.L #DELTBAD,A5
186 0002BA 6100 00D6                BSR  FATAL
187
      *****
188 0002BE 207C 0000 0435    CHKMD MOVEA.L #TIMSET,A0
189 0002C4 227C 0000 03C2    MOVEA.L #TIMCHK,A1
190 0002CA 6100 0042    CHKMDL BSR  CMDSTR    SEND TIME SET COMMANDS
191 0002CE 303C 00FF                MOVE  #$FFF,D0
192 0002D2 6100 0050                BSR  WT100L      WAIT FOR TIME SET
193 0002D6 4A79 00FF 6008          TST  IPLO        LATCH TIME
194 0002DC 2A7C 0000 09B3          MOVEA.L #DDDDMSG,A5
195 0002E2 3039 00FF 600E          MOVE  IPHI,D0
196 0002E8 B059                    CMP  (A1)+,D0    0DDD OK ?
197 0002EA 6600 00A6                BNE  FATAL       NO
198 0002EE 2A7C 0000 097D          MOVEA.L #HHMMMSG,A5
199 0002F4 3039 00FF 600C          MOVE  IPLO+4,D0  HHMM
200 0002FA B059                    CMP  (A1)+,D0    HR..MIN OK ?
201 0002FC 6600 0094                BNE  FATAL       NO
202 000300 4A10                    TST.B (A0)       DONE WITH CHKMD TEST ?
203 000302 66C6                    BNE  CHKMDL
204 000304 2A7C 0000 09E9  MDDON MOVEA.L #CHKMDOK,A5
205 00030A 6000 0086                BRA  FATAL
206 00030E 1018                    CMDSTR: MOVE.B (A0)+,D0    SEND NON-0 COMMANDS (A0) SPACED BY WT100
207 000310 6700 001E                BEQ  WTRTS
208 000314 13C0 00FF 6003          MOVE.B D0,IPCMD
209 00031A 6100 0004                BSR  WT100
210 00031E 60EE                    BRA  CMDSTR
211 000320 303C 00FF                WT100: MOVE  #$FF,D0
212 000324 0839 0001 00FF 6001 WT100L: BTST.B #1,IPSTS    LIMITS LOOP SPEED TO I/O SPEED
213 00032C 51C8 FFF6                DBF  D0,WT100L
214 000330 4E75                    WTRTS: RTS
215
      ***** SUBROUTINE TAGS TIME IN FIFO & READS PARALLEL INTO HISAV..HISAV+6 *****
216 000332 13FC 0000 00FF 6009 TAGNPAR MOVE.B #0,IPTAG    TRIGGER EVENT BCD TIME REPORT
217 00033A 33F9 00FF 6008 0000    MOVE  IPLO,HISAV+6
      03B8
218 000344 33F9 00FF 600A 0000    MOVE  IPLO+2,HISAV+4
      03B6
219 00034E 33F9 00FF 600C 0000    MOVE  IPLO+4,HISAV+2
      03B4
220 000358 33F9 00FF 600E 0000    MOVE  IPHI,HISAV
      03B2
221 000362 227C 0000 042B          MOVEA.L #EVTDAT,A1
222 000368 323C 0009                MOVE  #9,D1
223 00036C 0839 0000 00FF 6001 WTFIFA: BTST.B #0,IPSTS    READ 10 BYTES OF FIFO DATA
224 000374 67F6                    BEQ  WTFIFA
225 000376 12F9 00FF 6003          MOVE.B IPFIFO,(A1)+ READ WITHOUT MESSING UP A REGISTER

```

```

226 00037C 51C9 FFEE          DBF  D1,WTFIFA
227 000380 4E75             RTS
228 000382 5239 0000 03AE     INT0ISR:ADD.B #1,SPSAV+8  TELL BACKGROUND CODE THAT INTR HAPPENED
229 000388 13FC 0000 00FF 6001  MOVE.B #0,IPSTS  DISABLE FIFO OR INTR
230 000390 4E73             RTE
231 000392 6100 0004          FATAL: BSR  MESSAGE  FATAL ERROR REPORT
232 000396 60FE          FATALW BRA  FATALW
233 000398 3C4D          MESSAGE:MOVE  A5,A6
234 00039A 4A1E          MSGEND: TST.B (A6)+  FIND END OF MESSAGE
235 00039C 66FC          BNE  MSGEND
236 00039E 4A26          TST.B -(A6)
237 0003A0 4E4F          TRAP #15
238 0003A2 0006          DW  $6  DISPLAY STRING. NO AUTO CR/LF
239 0003A4 4E75             RTS
240 0003A6 0000 0000 0000 0000  SPSAV: LWORD  0,0,0 SPSAV,+4=$8 SAV,+8=INTCNT3..0
      0000 0000
241 0003B2 0000 0000 0000 0000  HISAV: LWORD  0,0  SEC,FRAC
242 0003BA 0000 0000 0000 0000  DELTA: LWORD  0,0
243 0003C2 0000 0001 0000 0002  TIMCHK: WORD  $0000,$0001,$0000,$0002,$0000,$0004,$0000,$0008
      0000 0004 0000 0008
244 0003D2 0000 0010 0000 0020  WORD  $0000,$0010,$0000,$0020,$0000,$0040 * 1 MIN..40 MIN
      0000 0040
245 0003DE 0000 0100 0000 0200  WORD  $0000,$0100,$0000,$0200,$0000,$0400,$0000,$0800
      0000 0400 0000 0800
246 0003EE 0000 1000 0000 2000  WORD  $0000,$1000,$0000,$2000 * 1 HR .. 20 HR
247 0003F6 0001 0000 0002 0000  WORD  $0001,$0000,$0002,$0000,$0004,$0000,$0008,$0000
      0004 0000 0008 0000
248 000406 0010 0000 0020 0000  WORD  $0010,$0000,$0020,$0000,$0040,$0000,$0080,$0000
      0040 0000 0080 0000
249 000416 0100 0000 0200 0000  WORD  $0100,$0000,$0200,$0000 * 1 DAY..200DAY
250 00041E 00             SECSAV: .BYTE  0
251 00041F 49 50 41 43 4F 00  IDCHK: .BYTE  "IPAC", $4F,0,0,0,0,0,$0C,$CE
252 00042B 00 00 00 00 00 00  EVTDAT:.BYTE  0,0,0,0,0,0,0,0
253 000435 50 60 70 80 90 A0  TIMSET:.BYTE  $50,$60,$70,$80,$90,$A0,$B1,$C0,$D0,$E0,0 000:00:01:00
254 000440 50 60 70 80 90 A0  .BYTE  $50,$60,$70,$80,$90,$A0,$B2,$C0,$D0,$E0,0 000:00:02:00
255 00044B 50 60 70 80 90 A0  .BYTE  $50,$60,$70,$80,$90,$A0,$B4,$C0,$D0,$E0,0 000:00:04:00
256 000456 50 60 70 80 90 A0  .BYTE  $50,$60,$70,$80,$90,$A0,$B8,$C0,$D0,$E0,0 000:00:08:00
257 000461 50 60 70 80 90 A1  .BYTE  $50,$60,$70,$80,$90,$A1,$B0,$C0,$D0,$E0,0 000:00:10:00
258 00046C 50 60 70 80 90 A2  .BYTE  $50,$60,$70,$80,$90,$A2,$B0,$C0,$D0,$E0,0 000:00:20:00
259 000477 50 60 70 80 90 A4  .BYTE  $50,$60,$70,$80,$90,$A4,$B0,$C0,$D0,$E0,0 000:00:40:00
260 000482 50 60 70 80 91 A0  .BYTE  $50,$60,$70,$80,$91,$A0,$B0,$C0,$D0,$E0,0 000:01:00:00
261 00048D 50 60 70 80 92 A0  .BYTE  $50,$60,$70,$80,$92,$A0,$B0,$C0,$D0,$E0,0 000:02:00:00
262 000498 50 60 70 80 94 A0  .BYTE  $50,$60,$70,$80,$94,$A0,$B0,$C0,$D0,$E0,0 000:04:00:00
263 0004A3 50 60 70 80 98 A0  .BYTE  $50,$60,$70,$80,$98,$A0,$B0,$C0,$D0,$E0,0 000:08:00:00
264 0004AE 50 60 70 81 90 A0  .BYTE  $50,$60,$70,$81,$90,$A0,$B0,$C0,$D0,$E0,0 000:10:00:00
265 0004B9 50 60 70 82 90 A0  .BYTE  $50,$60,$70,$82,$90,$A0,$B0,$C0,$D0,$E0,0 000:20:00:00
266 0004C4 50 60 71 80 90 A0  .BYTE  $50,$60,$71,$80,$90,$A0,$B0,$C0,$D0,$E0,0 001:00:00:00
267 0004CF 50 60 72 80 90 A0  .BYTE  $50,$60,$72,$80,$90,$A0,$B0,$C0,$D0,$E0,0 002:00:00:00
268 0004DA 50 60 74 80 90 A0  .BYTE  $50,$60,$74,$80,$90,$A0,$B0,$C0,$D0,$E0,0 004:00:00:00
269 0004E5 50 60 78 80 90 A0  .BYTE  $50,$60,$78,$80,$90,$A0,$B0,$C0,$D0,$E0,0 008:00:00:00
270 0004F0 50 61 70 80 90 A0  .BYTE  $50,$61,$70,$80,$90,$A0,$B0,$C0,$D0,$E0,0 010:00:00:00
271 0004FB 50 62 70 80 90 A0  .BYTE  $50,$62,$70,$80,$90,$A0,$B0,$C0,$D0,$E0,0 020:00:00:00
272 000506 50 64 70 80 90 A0  .BYTE  $50,$64,$70,$80,$90,$A0,$B0,$C0,$D0,$E0,0 040:00:00:00
273 000511 50 68 70 80 90 A0  .BYTE  $50,$68,$70,$80,$90,$A0,$B0,$C0,$D0,$E0,0 080:00:00:00
274 00051C 51 60 70 80 90 A0  .BYTE  $51,$60,$70,$80,$90,$A0,$B0,$C0,$D0,$E0,0 100:00:00:00
275 000527 52 60 70 80 90 A0  .BYTE  $52,$60,$70,$80,$90,$A0,$B0,$C0,$D0,$E0,0 200:00:00:00
276 000532 00             .BYTE  0

```

```

277 000533 4E 4F 57 20 53 45   STRTMSG:ASCII  NOW SEACHING ALL A16 SPACE FOR DTACKS. DISCONNECT INPUT!
278 00056B 0D 0A 00           .BYTE $0D,$0A,0
279 00056E 45 52 52 3A 4E 4F   NODTACK:ASCII  ERR:NO TPRO-IP DTACK IN ALL A16 SPACE.
280 000594 0D 0A 00           .BYTE $0D,$0A,0
281 000597 45 52 52 3A 57 52       MYSTER:ASCII  ERR:WRONG ADDR A16 DTACK (AT ABORT (A1))
282 0005BF 0D 0A 00           .BYTE $0D,$0A,0
283 0005C2 4F 4B 3A 20 46 4F   IDBEG: ASCII  OK: FOUND TPRO-IP AT 60XX. NOW STARTING ID TEST
284 0005F1 0D 0A 00           .BYTE $0D,$0A,0
285 0005F4 45 52 52 3A 49 4E   IDBAD: ASCII  ERR:INCORRECT ID DATA. REPEATING (A1) FOREVER
286 000621 0D 0A 00           .BYTE $0D,$0A,0
287 000624 4F 4B 3A 20 31 30   IETST: ASCII  OK: 1000 CHECKS OF ID DATA OK. NOW STARTING IE TEST
288 000657 0D 0A 00           .BYTE $0D,$0A,0
289 00065A 45 52 52 3A 43 41   IENOSSET:ASCII ERR:CANT SET MATIE AND ORIE IN IPSTS
290 00067E 0D 0A 00           .BYTE $0D,$0A,0
291 000681 4F 4B 3A 20 42 4F   RSTTST:ASCII  OK: BOTH IE BITS SET BY WRITE. NOW STARTING RESET TEST
292 0006B7 0D 0A 00           .BYTE $0D,$0A,0
293 0006BA 45 52 52 3A 57 52   RSTBAD: ASCII  ERR:WRITE TO RESET DOESNT CLEAR MATCH IE OR OR IE
294 0006EB 0D 0A 00           .BYTE $0D,$0A,0
295 0006EE 4F 4B 3A 20 49 50   FIFTST: ASCII  OK: IPSTS RESET & RELEASE OK. NOW TESTING FIFO
296 00071C 0D 0A 00           .BYTE $0D,$0A,0
297 00071F 45 52 52 3A 57 52   FIFSBAD:ASCII  ERR:WRITE TO INTERNAL EVT ADDR DOESNT SET FIFOR
298 00074F 0D 0A 00           .BYTE $0D,$0A,0
299 000752 45 52 52 3A 57 52   FIFRBAD:ASCII  ERR:WRITE TO IPFIFR DOESNT CLEAR FIFOR
300 000779 0D 0A 00           .BYTE $0D,$0A,0
301 00077C 4F 4B 3A 20 49 4E   ECHOBEG:ASCII  OK: INT EVT SETS OR, IPFIFR WRT CLRS OR. CMD ECHO TEST STARTING
302 0007BB 0D 0A 00           .BYTE $0D,$0A,0
303 0007BE 45 52 52 3A 49 4E   ECHOBAD:ASCII  ERR:INCORRECT CMD DATA ECHO. REPEATING D1 FOREVER
304 0007EF 0D 0A 00           .BYTE $0D,$0A,0
305 0007F2 45 52 52 3A 43 4D   NOECHO: ASCII  ERR:CMD DATA (ABORT D1) NOT ECHOED. REPEATING D1 FOREVER.
306 00082B 0D 0A 00           .BYTE $0D,$0A,0
307 00082E 4F 4B 3A 20 32 35   ECHOOK: ASCII  OK: 255 COMMANDS ECHOED 20 TIMES EACH. CHECKING VEC REG
308 000865 0D 0A 00           .BYTE $0D,$0A,0
309 000868 45 52 52 3A 56 45   VECERR: ASCII  ERR:VECTOR REG DID NOT ECHO (ABORT D1)
310 00088E 0D 0A 00           .BYTE $0D,$0A,0
311 000891 4F 4B 3A 20 56 45   VECOK: ASCII  OK: VECTOR REG WR/RD 0-255 OK
312 0008AE 0D 0A 00           .BYTE $0D,$0A,0
313 0008B1 0D 0A           DELTOK: .BYTE $0D,$0A
314 0008B3 4F 4B 3A 20 50 41   ASCII  OK: PARALLEL TIME - FIFO TAG TIME OK. NOW TEST MIN..DAYS
315 0008EB 0D 0A 00           .BYTE $0D,$0A,0
316 0008EE 0D 0A           DELTBAD:BYTE $0D,$0A
317 0008F0 45 52 52 3A 20 50   ASCII  ERR: PARALLEL TIME - FIFO DIFFERENCE TOO BIG
318 00091C 0D 0A 00           .BYTE $0D,$0A,0
319 00091F 45 52 52 3A 4E 4F   NOEVTI: ASCII  ERR:NO IRQ0 INTERRUPT FROM SIM. EXT EVENT
320 000948 0D 0A 00           .BYTE $0D,$0A,0
321 00094B 4F 4B 3A 20 49 52   INTROK: ASCII  OK: IRQ0 OK. NOW CHECK USEC..40S OF SECS BITS
322 000978 0D 0A 00           .BYTE $0D,$0A,0
323 00097B 59             TICMSG: ASCII  Y
324 00097C 00             .BYTE 0
325 00097D 45 52 52 3A 20 48   HHMMMSG:ASCII  ERR: HHMM READ FROM TPRO-IP DOESN'T MATCH SET VALUE
326 0009B0 0D 0A 00           .BYTE $0D,$0A,0
327 0009B3 45 52 52 3A 20 30   DDDMSG: ASCII  ERR: ODDD READ FROM TPRO-IP DOESN'T MATCH SET VALUE
328 0009E6 0D 0A 00           .BYTE $0D,$0A,0
329 0009E9 49 50 54 53 54 31   CHKMDOK:ASCII  IPTST1 COMPLETED
330 0009F9 0D 0A 00           .BYTE $0D,$0A,0
331 0009FC           END

```

Lines Assembled : 331

Assembly Errors : 0



```

3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55

```

\*\*\*\*\*  
\* TITLE IPTST2.001 7NOV94 JCK TPRO-IP VME BUS LATCHED VS FIFO DELTA  
\* NOTE: FOR THIS DEMO, HOST IS A XYCOM XVME-600 (10 MHZ 68000)  
\*\*\*\*\*

```

00FF 6001 IPSTS EQU $FF6001
0000 0000 BSTSOR EQU 0 BIT0: FIFO NOT EMPTY READ ONLY.
00FF 6003 IPFIFO EQU $FF6003 FIFO DATA PORT (READ ONLY)
00FF 6009 IPTAG EQU $FF6009 SIMULATED EXTERNAL EVENT PORT. WRITE ONLY
00FF 600D IPFIFR EQU $FF600D FIFO RESET. ALSO CLEARS RESET. WRITE ONLY
00FF 6008 IPLO EQU $FF6008 A16 BUS WINDOW FOR MVME133+BASE+8 OFFSET
00FF 600E IPHI EQU $FF600E A16 BUS WINDOW FOR MVME133+BASE+E OFFSET
000000 2A7C 0000 0102 START: MOVEA.L #STRMSG,A5
000006 6100 00D0 BSR MESSAGE
*****CHECK SECONDS 0-59 PARALLEL=FIFO TIME*****
00000A 13C0 00FF 600D CHKSEC MOVE.B D0,IPFIFR CLEAR FIFO OF IRQ0 TEST DATA
000010 6100 0076 BSR TAGNPAR GET TIME TAG FIFO DATA & PARALLEL TIME
000014 207C 0000 00FA MOVEA.L #HISAV+8,A0
00001A 247C 0000 0102 MOVEA.L #DELTA+8,A2
000020 023C 0000 ANDL.B #0,CCR
000024 323C 0007 MOVE #7,D1 DO 8 BYTES
000028 1520 DELTLOP MOVE.B -(A0),-(A2) DELTA = PARALLEL - FIFO
00002A 4A1A TST.B (A2)+ SBCD NEEDS AUTODEC MODE
00002C 8509 SBCD -(A1),-(A2)
00002E 51C9 FFF8 DBF D1,DELTLOP
000032 6100 0042 BSR WT100 LIMIT MAX EVENT RATE
000036 3239 0000 0100 MOVE DELTA+6,D1
00003C 0241 FFF0 ANDI #FFF0,D1 ONLY DISPLAY IF BIG DELTA
000040 67C8 BEQ CHKSEC
000042 2A7C 0000 0141 MOVEA.L #ASCBUF,A5 CONVERT FIFO, PAR, DELT TO ASCII
000048 323C 0017 MOVE #24-1,D1 LOOP COUNT FOR 24 BYTES
00004C 1E19 ASCLOP MOVE.B (A1)+,D7 GET 2 NIBBLES
00004E 3407 MOVE D7,D2 SAVE A COPY
000050 E84F LSR #4,D7 RIGHT JUSTIFY HI ORDER NIBBLE
000052 0207 000F ANDL.B #$0F,D7
000056 0607 0030 ADDL.B #"0",D7
00005A 1AC7 MOVE.B D7,(A5)+
00005C 0202 000F ANDL.B #$0F,D2
000060 0602 0030 ADDL.B #"0",D2
000064 1AC2 MOVE.B D2,(A5)+
000066 51C9 FFE4 DBF D1,ASCLOP
00006A 2A7C 0000 0141 MOVEA.L #ASCBUF,A5
000070 6100 0066 BSR MESSAGE
000074 6094 BRA CHKSEC
000076 303C 00FF WT100: MOVE #FFF,D0
00007A 0839 0001 00FF 6001 WT100L: BTST.B #1,IPSTS LIMITS LOOP SPEED TO I/O SPEED
000082 51C8 FFF6 DBF D0,WT100L
000086 4E75 WRTS: RTS
***** SUBROUTINE TAGS TIME IN FIFO & READS PARALLEL INTO HISAV..HISAV+6 *****
000088 13FC 0000 00FF 6009 TAGNPAR MOVE.B #0,IPTAG TRIGGER EVENT BCD TIME REPORT
000090 33F9 00FF 6008 0000 MOVE IPLO,HISAV+6
00F8
00009A 33F9 00FF 600A 0000 MOVE IPLO+2,HISAV+4
00F6
0000A4 33F9 00FF 600C 0000 MOVE IPLO+4,HISAV+2
00F4
0000AE 33F9 00FF 600E 0000 MOVE IPLO+6,HISAV
00F2

```

```

56 0000B8 227C 0000 00E8          MOVEA.L #EVTDAT-2,A1
57 0000BE 323C 0009          MOVE #9,D1
58 0000C2 0839 0000 00FF 6001    WTFIFA: BTST.B #0,IPSTS  READ 10 BYTES OF FIFO DATA
59 0000CA 67F6          BEQ WTFIFA
60 0000CC 12F9 00FF 6003          MOVE.B IPFIFO,(A1)+  READ WITHOUT MESSING UP A REGISTER
61 0000D2 51C9 FFEE          DBF D1,WTFIFA
62 0000D6 4E75          RTS
63 0000D8 3C4D          MESSAGE:MOVE A5,A6
64 0000DA 4A1E          MSGEND:TST.B (A6)+  FIND END OF MESSAGE
65 0000DC 66FC          BNE MSGEND
66 0000DE 4A26          TST.B -(A6)
67 0000E0 4E4F          TRAP #15
68 0000E2 0002          DW $2
69 0000E4 4E75          RTS
70 0000E6 0000 0000          LWORD 0
71 0000EA 0000 0000 0000 0000    EVTDAT: LWORD 0,0
72 0000F2 0000 0000 0000 0000    HISAV: LWORD 0,0 SEC,FRAC
73 0000FA 0000 0000 0000 0000    DELTA: LWORD 0,0
74 000102 53 49 4D 20 45 58      STRTMSG:ASCII SIM EXT EVT, READ PARALLEL, DISPLAY BIG DELTA PARALLEL-EXT EVT
75 000140 00          .BYTE 0
76 000141 30 30 30 30 30 30      ASCBUF: ASCII 0000000000000000000000000000000000000000000000000000000
77 000171 00          .BYTE 0
78 000172          END

```

Lines Assembled : 78      Assembly Errors : 0



```

3
4
5
6
7      00FF 6001      IPSTS EQU $FF6001
8      0000 0000      BSTSOR EQU 0      BIT0: FIFO NOT EMPTY  READ ONLY.
9      00FF 6003      IPFIFO EQU $FF6003  FIFO DATA PORT (READ ONLY)
10     00FF 6009      IPTAG EQU $FF600D  FIFO RESET. ALSO CLEARS RESET. WRITE ONLY
12     00FF 6008      IPLO EQU $FF6008   A16 BUS WINDOW FOR MVME133+BASE+8 OFFSET
13     00FF 600E      IPHI EQU $FF600E   A16 BUS WINDOW FOR MVME133+BASE+E OFFSET
14 000000 2A7C 0000 0106 START: MOVEA.L #STRMSG,A5
15 000006 6100 00D4      BSR MESSAGE
16
17 00000A 13C0 00FF 600DCHKSEC MOVE.B D0,IPFIFR  CLEAR FIFO OF IRQ0 TEST DATA
18 000010 6100 007A      BSR TAGNPAR  GET TIME TAG FIFO DATA & PARALLEL TIME
19 000014 207C 0000 00FE      MOVEA.L #HISAV+8,A0
20 00001A 247C 0000 0106      MOVEA.L #DELTA+8,A2
21 000020 023C 0000      ANDL.B #0,CCR
22 000024 323C 0007      MOVE #7,D1      DO 8 BYTES
23 000028 1520      DELTLOP MOVE.B -(A0),-(A2)  DELTA = PARALLEL - FIFO
24 00002A 4A1A      TST.B (A2)+     SBCD NEEDS AUTODEC MODE
25 00002C 8509      SBCD -(A1),-(A2)
26 00002E 51C9 FFF8      DBF D1,DELTLOP
27 000032 6100 0046      BSR WT100      LIMIT MAX EVENT RATE
28 000036 3239 0000 0104      MOVE DELTA+6,D1
29 00003C 2A7C 0000 0145      MOVEA.L #ASCBUF,A5  CONVERT FIFO, PAR, DELT TO ASCII
30 000042 303C 0003      MOVE #3,D0      DISPLAY FIFO, PAR, DELT
31 000046 323C 0007      ASCOLP MOVE #7,D1      LOOP COUNT FOR 8 BYTES
32 00004A 1E19      ASCLOP MOVE.B (A1)+,D7  GET 2 NIBBLES
33 00004C 3407      MOVE D7,D2      SAVE A COPY
34 00004E E84F      LSR #4,D7      RIGHT JUSTIFY HI ORDER NIBBLE
35 000050 0207 000F      ANDL.B #$0F,D7
36 000054 0607 0030      ADDL.B #"0",D7
37 000058 1AC7      MOVE.B D7,(A5)+
38 00005A 0202 000F      ANDL.B #$0F,D2
39 00005E 0602 0030      ADDL.B #"0",D2
40 000062 1AC2      MOVE.B D2,(A5)+
41 000064 51C9 FFE4      DBF D1,ASCLOP
42 000068 4A1D      TST.B (A5)+     LEAVE A SPACE
43 00006A 51C8 FFDA      DBF D0,ASCOLP
44 00006E 2A7C 0000 0145      MOVEA.L #ASCBUF,A5
45 000074 6100 0066      BSR MESSAGE
46 000078 6090      BRA CHKSEC
47 00007A 303C 00FF      WT100: MOVE #$FF,D0
48 00007E 0839 0001 00FF 6001  WT100L: BTST.B #1,IPSTS  LIMITS LOOP SPEED TO I/O SPEED
49 000086 51C8 FFF6      DBF D0,WT100L
50 00008A 4E75      WTRTS: RTS
51
52 00008C 13FC 0000 00FF 6009      TAGNPAR MOVE.B #0,IPTAG  TRIGGER EVENT BCD TIME REPORT
53 000094 33F9 00FF 6008 0000      MOVE IPLO,HISAV+6
54 00009E 33F9 00FF 600A 0000      MOVE IPLO+2,HISAV+4
55 0000A8 33F9 00FF 600C 0000      MOVE IPLO+4,HISAV+2
56 0000B2 33F9 00FF 600E 0000      MOVE IPLO+6,HISAV

```

```

00F6
57 0000BC 227C 0000 00EC          MOVEA.L #EVTDAT-2,A1
58 0000C2 323C 0009          MOVE #9,D1
59 0000C6 0839 0000 00FF 6001 WTFIFA: BTST.B #0,IPSTS  READ 10 BYTES OF FIFO DATA
60 0000CE 67F6          BEQ WTFIFA
61 0000D0 12F9 00FF 6003          MOVE.B IPFIFO,(A1)+ READ WITHOUT MESSING UP A REGISTER
62 0000D6 51C9 FFEE          DBF D1,WTFIFA
63 0000DA 4E75          RTS
64 0000DC 3C4D          MESSAGE:MOVE A5,A6
65 0000DE 4A1E          MSGEND: TST.B (A6)+ FIND END OF MESSAGE
66 0000E0 66FC          BNE MSGEND
67 0000E2 4A26          TST.B -(A6)
68 0000E4 4E4F          TRAP #15
69 0000E6 0002          DW $2
70 0000E8 4E75          RTS
71 0000EA 0000 0000          LWORD 0
72 0000EE 0000 0000 0000 0000 EVTDAT: LWORD 0,0
73 0000F6 0000 0000 0000 0000 HISAV: LWORD 0,0 SEC,FRAC
74 0000FE 0000 0000 0000 0000 DELTA: LWORD 0,0
75 000106 53 49 4D 20 45 58 STRTMSG: ASCII SIM EXT EVT, READ PARALLEL, DISPLAY BIG DELTA PARALLEL-EXT EVT
76 000144 00          .BYTE 0
77 000145 30 30 30 30 30 30 ASCBUF: ASCII 0000000000000000 0000000000000000 0000000000000000
78 000177 00          .BYTE 0
79 000178          END

```

Lines Assembled : 79      Assembly Errors : 0

```

3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
011C

*****
* TITLE IPTST5.001 7NOV94 JCK TPRO-IP EXT EVT INTERRUPT TEST
* THIS DEMO ASSUMES A XYCOM XVME-600 (10 MHZ 68000) + GREENSPRING VIPC310
* THIS DEMO ASSUMES A XYCOM XVME-600 (10 MHZ 68000) + GREENSPRING VIPC310
*****
IPSTS EQU $FF6001
BSTSOR EQU 0 BIT0: FIFO NOT EMPTY READ ONLY.
BEXTENB EQU 4 BIT6: EXTERNAL EVENT ENABLE. READ/WRITE
BORIE EQU 7 INTERRUPT ENABLE
IPFIFO EQU $FF6003 FIFO DATA PORT (READ ONLY)
IPVEC EQU $FF6005 INTR VECTOR FOR IRQ0 (READ/WRITE)
IPFIFR EQU $FF600D FIFO RESET. ALSO CLEARS RESET. WRITE ONLY
IPL0 EQU $FF6008 A16 BUS WINDOW FOR MVME133+BASE+8 OFFSET
START: MOVE.B D0,IPFIFR CLEAR FIFO OF IRQ0 TEST DATA
MOVEA.L #INT0ISR,$100
MOVE.B #$40,IPVEC
MOVE #$2000,SR SET STS LEV = TO ALLOW INTR1
MOVE.B #1,SHL,BORIE+1,SHL,BEXTENB,IPSTS ENABLE FIFO OR INTR
CHKSEC Cmpl.B #100,EVTCNT DISPLAY EVERY 100TH SET OF EXT EVT,PAR,DELTA
BNE CHKSEC
MOVE.B #0,EVTCNT RESET COUNT
MOVEA.L #HISAV+8,A0
MOVEA.L #EVTDAT+8,A1
MOVEA.L #DELTA+8,A2
ANDI.B #0,CCR
MOVE #7,D1 DO 8 BYTES
DELTLOP MOVE.B -(A0),-(A2) DELTA = PARALLEL - FIFO
TST.B (A2)+ SBCD NEEDS AUTODEC MODE
SBCD -(A1),-(A2)
DBF D1,DELTLOP
MOVE DELTA+6,D1
MOVEA.L #ASCBUF,A5 CONVERT FIFO, PAR, DELT TO ASCII
MOVE #3,D0 DISPLAY FIFO, PAR, DELT
ASCLOP MOVE #7,D1 LOOP COUNT FOR 8 BYTES
ASCLOP MOVE.B (A1)+,D7 GET 2 NIBBLES
MOVE D7,D2 SAVE A COPY
LSR #4,D7 RIGHT JUSTIFY HI ORDER NIBBLE
ANDI.B #$0F,D7
ADDI.B #"0",D7
MOVE.B D7,(A5)+
ANDI.B #$0F,D2
ADDI.B #"0",D2
MOVE.B D2,(A5)+
DBF D1,ASCLOP
TST.B (A5)+ LEAVE A SPACE
DBF D0,ASCLOP DISPLAY 3 16 DIGIT NUMBERS
MOVEA.L #ASCBUF,A5
MOVEA.L #ASCEND,A6
TRAP #15
DW $2
BRA CHKSEC
**INTERRUPT SERVICE ROUTINE TAGS TIME IN FIFO & READS PARALLEL INTO HISAV..HISAV+6 *****
INT0ISR: MOVEM.L D1/A1,-(A7)
MOVE.B #1,SHL,BEXTENB,IPSTS DISABLE FIFO OR INTERRUPTS WHILE READING FIFO
ADDI.B #1,EVTCNT
TAGNPAR MOVE IPL0,HISAV+6

```

```

59 0000C0 33F9 00FF 600A 0000      MOVE  IPLO+2,HISAV+4
    011A
60 0000CA 33F9 00FF 600C 0000      MOVE  IPLO+4,HISAV+2
    0118
61 0000D4 33F9 00FF 600E 0000      MOVE  IPLO+6,HISAV
    0116
62 0000DE 227C 0000 010C            MOVEA.L #EVTDAT-2,A1
63 0000E4 323C 0009                MOVE  #9,D1      READ 10 BYTES OF FIFO DATA
64 0000E8 0839 0000 00FF 6001      WTFIFA: BTST.B #0,IPSTS  FOR EACH BYTE, CHECK FOR READY. **IMPORTANT!**
65 0000F0 67F6                      BEQ   WTFIFA
66 0000F2 12F9 00FF 6003            MOVE.B IPFIFO,(A1)+ READ WITHOUT MESSING UP A REGISTER
67 0000F8 51C9 FFEE                DBF   D1,WTFIFA
68 0000FC 13FC 0090 00FF 6001      MOVE.B #1,SHL,BORIE+1,SHL,BEXTENB,IPSTS REENABLE FIFO NOT EMPTY INTR
69 000104 4CDF 0202                EVTISR MOVEM.L (A7)+,D1/A1  RESTORE A0 AND D0
70 000108 4E73                      RTE
71 00010A 0000 0000                LWORD 0
72 00010E 0000 0000 0000 0000      EVTDAT: LWORD 0,0
73 000116 0000 0000 0000 0000      HISAV: LWORD 0,0 SEC,FRAC
74 00011E 0000 0000 0000 0000      DELTA: LWORD 0,0
75 000126 00                      EVTCNT: .BYTE 0
76 000127 30 30 30 30 30 30        ASCBUF: ASCII 0000000000000000 0000000000000000 0000000000000000
77 000159 00                      ASCEND: .BYTE 0
78 00015A                          END

```

Lines Assembled : 78      Assembly Errors : 0

# *Warranty*

KSI warrants that all products manufactured by KSI conform to published DSPCon specifications and are free from defects in materials and workmanship for a period of one (1) year from the date of delivery when used under normal conditions and within the service conditions for which they were furnished.

The obligation upon KSI arising from a warranty claim shall be limited to repairing, or, at its option, replacing without charge, any product which, in KSI's sole opinion, proves to be defective within the scope of this warranty.

KSI must be notified in writing of the defect or nonconformity within the warranty period, and the affected product must be returned to KSI within thirty (30) days after discovery of such defect or nonconformity.

The buyer shall prepay shipping charges, taxes, duties and insurance for products returned to KSI for warranty service. KSI shall pay for the return of products to buyer except for products returned to another country or from outside the forty-eight contiguous United States.

KSI shall have no responsibility for any defect or damage caused by improper installation, unauthorized modification, misuse, neglect, inadequate maintenance, accident or for any product that has been repaired or altered by anyone other than KSI or its authorized representatives.

The warranty described above is the buyer's sole and exclusive remedy and no other warranty, whether oral or written, is expressed or implied KSI specifically disclaims fitness for a particular purpose. Under no circumstances shall KSI be liable for any direct, indirect, special, incidental or consequential damages, expenses, losses or delays (including loss of profits) based on contract, tort, or any legal theory.

This warranty is valid for a period of one (1) year from the date of shipment. Upon warranty expiration, all services on KSI hardware and software are subject to a current hourly rate, plus travel expenses where applicable. As an option, KSI offers extended warranties when purchased within ten (10) days of receipt of product.

## *Extended Warranties*

### *HARDWARE*

KSI offers an extended warranty on its hardware at a cost of 15% of the current list price per year of coverage. This coverage is available for KSI hardware only.

### *SOFTWARE*

KSI offers an extended warranty on its software at a cost of 15% of the current list price per year of coverage. This coverage is available for KSI software only.

## *Service and Repair*

Before returning a product for service and repair, please contact KSI at (866) KSI-KSI3 to obtain a Return Material Authorization (RMA) number. Have available the Model and Serial numbers of the item, a description of the problem, your company name, and the name and address of the person returning the product.





a division of DSPCon, Inc.

**11209 Armour Drive  
El Paso, TX 79935**

**Toll Free Phone: 866-KSI-KSI3**

**Toll Free Fax: 866-593-2080**

**Website: [www.ksi-corporation.com](http://www.ksi-corporation.com)**

**E-mail: [info@ksi-corporation.com](mailto:info@ksi-corporation.com)**

### Technical Support

#### **General/Hardware/Software**

Phone 866-KSI-KSI3

Fax 866-593-2080

Email [dcs@ksi-corporation.com](mailto:dcs@ksi-corporation.com)

### Additional Contact Information

#### **Literature**

Phone 866-KSI-KSI3

Fax 866-593-2080

Email [info@ksi-corporation.com](mailto:info@ksi-corporation.com)

#### **Repairs/Returns**

Phone 866-KSI-KSI3

Fax 866-593-2080

Email [info@ksi-corporation.com](mailto:info@ksi-corporation.com)

### Shipping Address for Repairs and Returns

**(Call KSI to obtain a Return Material Authorization (RMA) number)**

Ship to: KSI  
Attention: RMA-#### (replace with RMA number)  
11209 Armour Drive  
El Paso, TX 79935-4801  
USA

A Publication of

**KSI**

© MMIII

Printed in the United States of America. All rights reserved. Contents of this publication may not be reproduced, stored in or transmitted by a retrieval system, or transmitted in any form or by any means, electronic or mechanical, including photocopying or recording, without the written permission of KSI.

KSI has worked to verify the accuracy of the information contained in this document as of its publication date; however, such information is subject to change without notice and KSI is not responsible for any errors that may occur in this document.

Trademarks are acknowledged and are the property of their owners.



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)