



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)

**Thomas Products, Ltd.**

987 West Street Southington, CT 06489-1023

Toll Free: (800) 666-9101 Telephone: (860) 621-9101 Fax: (860) 621-1470

E-Mail: Sales@ThomasProd.com Website: www.ThomasProd.com

**Item # 19651, Adjustable Paddle Type - 2400 Series Flow Switch.****Adjustable Paddle Type - 2400 Series Flow Switch.**

To adjust flow set point, simply cut paddle for the appropriate set point listed.

**SPECIFICATIONS**

Housing Material	316 SST
Mounting Sizes	1" NPT
Paddle	316 SST
Shuttle	316 SST
Spring	316 SST
Reed Switches (Non UL Recognized Units)	20 VA SPDT
Wire	18 AWG Polymeric 24" Long
Operating Temperature	-30 <sup>0</sup> to 300 <sup>0</sup> F
Operating Pressure	850 psig
Set point Accuracy	± 25% Max
Repeatability	5% Max Deviation
Pressure drop	3 PSIG Max
Advantages	SPDT reed switch assembly, all metal wetted parts, rugged investment cast components.

## NOTES

### Notes:

- Flow tests were performed in water with unit installed into standard reducing tee.
  - Set point accuracy depends on paddle cut-off length.
  - Unit installs into a 1" reducing tee or weld-o-let etc. for 1" pipe sizes and up.
  - Install vertically as shown, lead wires up.
  - Higher temperature units available up to 450° F. Consult factory.
  - Relays for higher loads, junction boxes, terminal strips, etc. are available. See accessories section for details (See Page 28)
  - To adjust flow set point, simply cut paddle for the appropriate set point listed. See also installation/maintenance sheet.
  - For pipe sizes larger than 3", actuation of the 5" paddle is a velocity of approximately .5 ft./sec.
  - Also available: leads in different lengths, cable, terminated ends, etc. Consult factory.
  - Optional 100W SPST reed switches are stocked. Consult factory.
-



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)