



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

CL-band Optical Fiber Amplifier (EDFA)

The AMP-FL8021-CLB series are optical fiber amplifier designed to cover both for *C-band and L-band*. This instrument utilized a unique optical design based on Er³⁺ doped fiber that is optimized to provide spectrally flat gain profile, high signal gain and low noise figure over the wide bandwidth.

Features

- Wide signal bandwidth
- Excellent noise figure
- Excellent gain flatness
- Cost effective
- Output power & pumping current monitoring
- ACC/ALC mode operation



AMP-8021-CLB-13/16/19

Applications

- [DWDM](#), [CWDM](#), Datacom
- Test & measurement
- Scientific Applications



AMP-8021-CLB-22

Standard Specifications

[What is optical amplifier ?](#)

Item	AMP-FL8021-CLB -22	AMP-FL8021-CLB -19	AMP-FL8021-CLB -16	AMP-FL8021-CLB -13
Signal Wavelength	1530 ~ 1560nm , 1570 ~ 1610nm			
Maximum Output Power *1	>+22dBm (>160mW)	>+19dBm (>80mW)	>+16dBm (>40mW)	>+13dBm (>20mW)
Gain *2	>35dB	>35dB	>30dB	>25dB
Noise Figure *2	<7dB			
Amplifier control	ACC / ALC			
Monitor items	Optical output power, Pumping LD current, Pumping LD temperature, Case temperature			
Safety function	Remote shutdown interlock			
Remote control Interface	RS232C / IEEE488.2(GP-IB)			
Input & Output Fibers	SMF			
Optical Connectors	FC/PC			
Operation Temperature	0 ~ 40 °C			
Storage Temperature	-10 ~ 60 °C			

Size (H) x(W) x(D) mm	88 x 430 x 350	88 x 260 x 350
Weight	7Kg	
Power consumption	<50W	<30W
Power Supply	AC 100 ~ 240V (50/60Hz)	

*1 Input Power: >0dBm@1550nm,1580nm

*2 Input Power: -30dBm@1550nm,1580nm

The specifications are subject to change.

All functions, characteristics and exterior design can be optimized according to customer requirements, and please feel free to contact FiberLabs sales engineers.

Pricing, Questions, Order, etc.
Contact Us

Products / About FiberLabs / Technology / Contact Us

Copyright(C) FiberLabs Inc. All Rights Reserved.



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com