



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

Dissolved Oxygen Meter & Electrode

Order # ISO2



[Ask a question about this product](#)

- Measures gas and dissolved oxygen
- Low oxygen consumption
- 2mm electrode tip

[View Full-Size Image](#)

Details

Isolation prevents adverse interaction with other electrodes and instruments. Highly accurate and stable SYS-ISO2 measures oxygen concentrations in aqueous solutions and in gas mixtures. Measurement modes are percent oxygen, parts per million, and oxygen reduction current in nanoamperes.

Detection limit

The lower detection limit (DL) for SYS-ISO2 (in gaseous or in liquid phase) is 0.1 ppm or 0.1%. Oxygen concentration around 0.5 ppm or 0.5% and up can be routinely measured in the gaseous or in the liquid phases. DL for a particular sensor tends to be different in gaseous and liquid phases when the baseline noise level is also different. In the case of SYS-ISO2, however, the baseline noise level is very close whether the electrode is immersed in solution or used in the gaseous phase, so DL for the SYS-ISO2 remains relatively close in either phase.

Electrode

The small tip size (2 mm diameter) and low oxygen consumption of the OXELP electrode make it ideal for measurements in vivo or in vitro. With a T-Adapter (#5399), the sensor probe can be used also for continuous-flow monitoring of oxygen in small fluid volumes. OXELP also features a fast response time, typically 10 seconds. Optional BNC-to-double banana adaptor (#13347) and BNC cable (#500184) allow ISO2 to be connected directly to your chart recorder.



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com