



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)

# Features

## GX7900 Series

- Double-Slot 6U cPCI/PXI Controller for use with GX7000 Series PXI Chassis
- Interfaces to common peripherals available through front panel and rear I/O panel of GX7000
- Supports Pentium® II, Pentium® III, and AMDTM CPUs
- On-Board high-performance AGP SVGA controller
- One PMC Slot for added I/O options such as GPIB
- Optional Flash Disk up to 144 MB available



**GX7900**

## GX7910 Series

- Single-Slot 6U cPCI/PXI Controller for use with GX7100 Series PXI Chassis
- Interfaces to common peripherals available through front panel and rear I/O panel GX7100
- Supports Pentium® 4 CPUs
- Up to 2GM DDR RAM (512MB standard)
- On-Board Gigabit Ethernet
- On-Board high-performance AGP SVGA controller
- One PMC Slot for added I/O options such as GPIB
- Optional Flash Disk up to 144 MB available



**GX7910**

The GX79x0 is a family of 6U, high-performance embedded system controllers that are fully compatible with the PXI and cPCI specifications. With multiple CPU and memory configurations and a full range of peripherals, combined with the embedded storage peripherals of the GX7000 and GX7100, the GX79x0 is the ultimate solution for a system controller.

# Configuration

The GX7900 is a dual-slot 6U controller for use with Geotest's GX7000 PXI chassis. The GX7910 is a single-slot 6U controller for use with Geotest's GX7100 PXI combo chassis and is also PICMG 2.16 compatible.

Both the GX7900 and GX7910 controllers are offered in multiple CPU and memory configurations ranging from the cost-effective 500 MHz Celeron processor to the high-performance 2.4GHz P4 processor. On-board memory starts at 64 MB and supports up to 2GB of on-board memory.

All Controllers offer multiple peripherals and I/O interfaces through either the PXI controller front panel or the rear I/O panel of the GX7000 and GX7100. All storage devices (i.e. Floppy disk, Hard disk, and CD-ROM drives) are built-in to the GX7000 and GX7100 chassis and are connected to the GX7900 internally.

The front panel I/O is factory default configuration and is fully functional in any PXI or cPCI chassis. Rear panel I/O is only enabled when the Controllers are used in conjunction with the GX7000 and GX7100 PXI chassis.

# Specifications

Interface	GX7900			GX7910		
	Front	Rear	Comments	Front	Rear	Comments
Parallel (LPT)	1	1	Select one option	1	1	Select one option
Serial (RS-232)	2 1	2 1	Select one option: 2 front OR 2 rear 1 front AND 1 rear	1	2	Select one option
USB	2	1	–	2	1	–
Ethernet (10/100 Base T)	1	1	–	1	1	–

GigabitEthernet (1000 Base T)	-	-	-	1	-	-
Keyboard	1	1	Select one option	1	1	Select one option
Mouse	1	1	Select one option	1	1	Select one option
VGA	1	-	-	1	-	-
EIDE	-	-	2 (Used internally by the chassis)	-	-	2 (Used internally by the chassis)
Floppy	-	-	Internal	-	-	-
SCSI	-	Optional	-	-	-	-
PMC	Optional	-	-	Optional	-	-

## Ordering Information

<b>GX7900-850</b>	PXI Controller, 850 MHz PIII, 128 MB
<b>GX7900-1256</b>	PXI Controller, 1 GHz PIII, 128 MB
<b>GX7910-22512</b>	PXI Controller, 2.2 GHz P4, 512 MB
<b>GX7910-24512</b>	PXI Controller, 2.4 GHz P4, 512 MB
<b>GX7910-20512E</b>	PXI Controller, 2 GHz P4, 512 MB, Extended Temperature Range
<b>GX79x0-NT</b>	Upgrade any GX7900 to Windows NT Operating System
<b>GX79x0-XP</b>	Upgrade any GX7900 to Windows XP Operating System
<b>GX7900-64M</b>	64 MB Memory Upgrade to GX7900
<b>GX7900-128M</b>	128 MB Memory Upgrade to GX7900
<b>GX7910-512M</b>	512 MB Memory Upgrade to GX7900
<b>GX7900-GPIB</b>	GPIB interface for any GX79x0 controller(PMC plug-in card)

Pentium is a registered trademark of Intel Corporation.  
AMD is a registered trademark of Advanced Micro Devices, Inc.



To place an order or obtain additional information, call **1-888-TEST-BY-PXI (1-888-837-8297)**.

Copyright © 1996-2005 Geotest - Marvin Test Systems, Inc.



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)