



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

PC-1553

Multi-Function MIL-STD-1553

Interface for IBM-PC/AT and Compatibles



FEATURES:

- Conforms to MIL-STD-1553B Notice II
- Simultaneous emulation of Bus Controller, 31 Remote Terminals and Bus Monitor
- Variable voltage output
- Extensive error injection/detection
- Sub-microsecond time-tagging
- Complete message programmability
- Flexible message status/interrupt generation
- Dual redundant bus support
- Optional Microsoft Windows GUI user interface available
- Windows API and C utility libraries for DOS provided
- Multi-level Input/Output triggering and filtering options
- Built-in-Test
- 256 KB RAM

SPECIFICATIONS:

Physical

16-bit ISA bus full card: 13.125" x 4.2"

Environmental

0 to +70 degrees C Operating Temperature
0 to 90% Relative Humidity (Non-condensing)

Maximum Power Consumption

+5 VDC: 2.3 A
+12 VDC: 230 mA

-12 VDC: 20 mA

On-board Static RAM

256 KBytes

Sliding window access (32K, 64K, or 128K)

Hardware Configuration Options

Interrupt level (IRQ)

I/O and Memory Addresses Up to four cards per PC

Connections

Direct or transformer coupling (software controlled)

Variable voltage outputs (software controlled)

PC-1553: two BJ-77 Twinax

Input and Output Triggers: subminiature coaxial BNC

System Requirements

386 or higher processor

MS-DOS 5.0 or higher

Microsoft Windows 3.1 (when using DLL or VxD)

640 KB of RAM (8 MB recommended for Windows)

Software

DOS C utility libraries included

Windows DLL and VxD included

Optional [WIN-1553](#) BusTools Windows GUI

Available Configurations

PC-1553

MIL-STD-1553B Interface board, 256 KB RAM

**BusTools is a trademark of Condor Engineering.
Specifications subject to change without notice.**

[products](#)

[home](#)



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com