



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

PCI-IIRO-8 and PCI-IIRO-16

Isolated Digital Input/Output Cards

Features

- Universal PCI, PCI-X, 3.3V and 5V compatible (Call for PCI-Express availability)
- Eight or sixteen optically isolated, non-polarized digital inputs
- Eight or sixteen electro-
- Opto-isolated channel to
- Can detect input state change and assert interrupt
- Automatically detected under Windows



mechanical relay outputs
channel and channel to ground

The PCI-IIRO-8 and PCI-IIRO-16 are low-cost, half-size cards that provide isolated input and output for PCI-Bus computers. The cards have eight or sixteen optically-isolated digital inputs for AC or DC control signals and eight or sixteen electro-mechanical relay outputs. PCI-IIRO-8 occupies four consecutive eight-bit registers in I/O space. PCI-IIRO-16 occupies eight consecutive eight-bit registers in I/O space.

Inputs

The isolated inputs can be driven by either AC or DC and are not polarity sensitive. Input signals are rectified by a diode bridge and applied to the inputs of opto-isolators. A 470 ohm resistor in series provides current limiting. Standard 12/24 AC control transmitter outputs can be accepted as well as DC voltages. The input voltage range is 5V to 24V (rms). To extend the input voltage range, you may connect external resistors in series.

Each input circuit contains a switchable slow/fast filter that has a 10 millisecond (PCI-IIRO-8) or 5 millisecond (PCI-IIRO-16) time constant. (Without filtering, the response is 20 microseconds.) The filter must be selected for AC inputs in order to eliminate response to zero crossings. The filter is also valuable for use with slow DC input signals in a noisy environment. The filter may be switched out for DC inputs in order to obtain faster response. For the PCI-IIRO-16 the filters are globally controlled by software. For the PCI-IIRO-8 the filters can also be individually selected by switches on the card.

Interrupts

Interrupts are enabled/disabled by software. When the change-of-state detection circuit is enabled, the card asserts an interrupt whenever one or more of the interrupts changes state. Once

an interrupt has been generated and serviced, it must be cleared by system software. This feature greatly frees up system resources by eliminating the need for constant polling to see when an input has changed state.

Outputs

The electro-mechanical relay outputs of the PCI-IIRO-8 are comprised of five form C SPDT outputs and three Form A SPST (normally-open) type. The outputs of the PCI-IIRO-16 are divided into two groups of eight, each group being similar to the PCI-IIRO-8. The relays are all de-energized at power-on. Data to the relays is latched.

Connections

For the PCI-IIRO-8, I/O is accessed via a 37 pin DBF connector on the mounting bracket of the card.

For the PCI-IIRO-16, I/O is accessed via a 78 pin DBF connector on the mounting bracket of the card. A molded breakout cable (model CAB78-37/2) is optionally available that divides the 78 pins into two DB37F connectors. Also available is a kit (model STB-37/2 Kit) which includes the cable and two STB-37 Screw Terminal Cards that mount into an included one-foot length of Snap-Trak.



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com