



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com



[[Home](#)] [[Search](#)] [[Sales](#)]

VME BUS Serial Interface Adaptors

GET 10042701 VME/ROLM S311

GET 10042901 VME/STANAG 4156

The **GET** VME to S311 Interface Adaptor connects a ROLM S311 Serial channel with an **A24:D16:I8** VME based system.

The **GET** VME to STANAG 4156 Interface Adaptor connects a STANAG 4156 Serial channel with an **A24:D16:I8** VME based system.

FEATURES

Short Circuit and Transient Protection on **all** Transceivers.

Circuit card fits in a single 6U 4HP VME slot (233.35 X 160 mm X 20 mm).

Onboard MC 68000 CPU, local 64KB DP SRAM, 64KB EPROM, 4 channel DMA, and 2 diagnostic serial ports.

VME Master/Slave interface D16:A24:BLT compatible. VME Bus Master BR0:3 Level Jumper selectable. VME I(8) vectors software selectable.

Data Buffers may reside in DP SRAM or VME system memory.

Low Power (typ): + 5 VDC @ 2.5 Amp.

S311

16 bit Data or Commands

Input and Output ports are independent - Full Duplex operation

Software selectable Parity Modes and Data Clocking Rates

STANAG 4156

16 bit Data with Software selectable Parity Modes

Input and Output ports are independent - 3 MB/s Full Duplex operation

Software selectable User, Terminal, or Direct Connection Coupler

Type A (Simplified) and B (Complex) protocols supported

Status indicator and base address selection DIP switch front panel accessible.

Front panel DB25-S connector (standard) and optional VME P2 module.

[Device drivers](#) for 10042701 - HP-UX and SunOS.

10042901 - HP-UX 10.20 and VxWorks.

These **VME** adaptors are application software and driver firmware compatible with the other members of the **GET** VME family of interface adaptors.



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com