


Xycom AP482

32-Bit Counter/Timer Module



Limited Availability
Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/47413-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com



- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

AcroPack® Modules

AP480 Series Counter/Timers



Eight 32-bit Counters ♦ TTL and RS422/RS485 I/O ♦ Wide Temperature Range ♦ PCIe Bus Interface

Description

Model: AP483E-LF

The AcroPack® product line updates our popular Industry Pack I/O modules with a PCIe interface format. This tech-refresh design offers a compact size, low-cost I/O, the same functionality and memory map of the existing IP modules and a rugged form factor. Combine different AcroPack modules on one carrier for a simplified modular approach to system assembly.

Support for internal or external triggering simplifies the synchronization of operations to specific events.

Designed for COTS applications these RS422/RS485 & TTL counter/timers deliver high-speed and high-performance.

AcroPack modules are RoHS compliant and ideal for military, defense, automation, aerospace, scientific, and development labs industries.

The AP483 module is 70mm long, this is 19.05mm longer than the full length mini PCIe card at 50.95mm. The board's width is the same as mPCIe board of 30mm and they use the same mPCIe standard board hold down standoff and screw keep out areas.

A down facing 100 pin Samtec connector will mate with the carrier card. Fifty of these signals are available as field I/O signals.

The AP483 maintains the same functionality and memory map of the existing Industry Pack modules providing a smooth transition to the AcroPack I/O modules.

Key Features & Benefits

- PCI Express Generation 1 interface
- Mix and match countless I/O combinations in a single slot.
- Sample software and diagnostics
- Available with both TTL and RS422/RS485 driver interface
- 62.5MHz clock time base
- Single counter/timer modes:
 - Event counting
 - Frequency measurement
 - Period/pulse-width measurement
 - Quadrature position measurement
 - Square wave/pulse train generation
 - Time/period interrupter
 - Pulse width generation
- Most configuration is handled by a single register which minimizes programming.
- Solid-down connector I/O interface
- Wide temperature range
- PCIe, VPX and XMC carriers
- Linux®, Windows®, and VxWorks® support

Performance Specifications

■ Counter/timers

Counter/timer configuration:

AP483: Five 32-bit counters – TTL

Three 32-bit counters – RS422/RS485

Clock frequency

Selectable internal clock frequencies: 1.95MHz, 3.9MHz, 7.81MHz, 15.62MHz, or 62.5MHz.

Minimum input event

32nS.

Minimum pulse measurement

32nS.

Minimum period measurement

64nS.

Minimum gate/trigger pulse

32nS.

Interrupts

Supported for watchdog timer time-out, event count complete, pulse width or periodic rate measurement complete, pulse wave complete (one-shot mode), successive waveform generation (continuous).

Triggering/gate

Programmable via register write or external trigger.

Minimum pulse width 32nS. Line may be used for gating of counter.

Counter trigger

Interface for triggering counter functions. Input level is TTL and RS422 differential digital.

Counter input

Interface for events and pulse/period measurements. Also triggers load of watchdog timer register. Level is TTL and RS422 differential digital.

TTL compatibility

$V_{IH} = 2.0V$ and $V_{IL} = 0.8V$. Inputs are buffered and include 4.7K pull-ups to +3.3V.

Counter output

Level is TTL and RS422 differential digital.

■ PCI Express Base Specification

Conforms to revision 2.1

Lanes

1 lane in each direction.

Bus Speed

2.5 Gbps (Generation 1).

Memory

4k space required.

1 base address register.

■ Environmental

Operating temperature

-40 to 70°C.

-40 to 85°C.

(requires an AcroPack heatsink conduction-cool kit)

Storage temperature

-55 to 150°C.

Relative humidity

5 to 95% non-condensing.

Power

3.3V DC $\pm$ 5%.

1.6A Typical, 2.0A Maxium.

■ Physical

Length

70mm.

Width

30mm.

Ordering Information

AcroPack[®] Modules

[AP483E-LF](#)

Five 32-bit TTL and three 32-bit RS422/RS485 counters

(Note: Acropack modules are compatible only with the carriers listed below)

Accessories

[AP-CC-01](#)

Conduction-cool kit

Carrier Cards

See Acromag.com/AcroPack-Carriers for a full list of AcroPack carrier cards.

Software (see software documentation for details)

[APSW-API-VXW](#)

VxWorks[®] software support package.

[APSW-API-WIN](#)

Windows[®] DLL driver software support package.

[APSW-API-LNX](#)

Linux[®] support (website download only).



AP-CC-01 Conduction-Cool Kit

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

