### **16-Channel Isolated Digital-Output Module**



In Stock

**New From Surplus Stock** 

**Open Web Page** 

https://www.artisantg.com/59140-85

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- · Full-service, independent repair center



Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisantg.com | artisantg.com

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

#### Table 13-3 HP 44724A Specifications

Maximum Input Voltage: 55 V DC Between High and Low Terminal (of

each channel)

350 V peak or 250 V DC (between channels

or between any Terminal and Chassis)

Maximum Sink Current: 500 mA DC per channel (1 A fuse protected)

Maximum Reverse Polarity Current: 500 mA DC per channel

TTL Compatibility: 200 mA per channel with Vout =<0.4 volts

Closed Channel Path Resistance:  $1.5~\Omega$ 

Maximum Off Leakage: 0.25 mA per channel at 55 V DC

Maximum Wire Size: 16 AWG

# Artisan Technology Group is an independent supplier of quality pre-owned equipment

## **Gold-standard solutions**

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

# We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

### Learn more!

Visit us at artisantg.com for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today? (217) 352-9330 | sales@artisantg.com | artisantg.com

