

Alnor 350-CEM
Airgard Air Flow Monitor



**Limited Availability
Used and in Excellent Condition**

Open Web Page

<https://www.artisanng.com/62807-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

[AirGard® Air Flow Monitors

For Bio-Safety Cabinets
and other Critical Environments

Models 315-BSC

The AirGard Model 315-BSC is a simple, go/no-go monitor for critical airflows including the downflow of a bio-safety cabinet. By warning of poor bio-safety cabinet performance, the 315-BSC can increase staff protection while reducing experiment contamination.



AirGard 315-BSC

Model 350-CEM

The AirGard Model 350-CEM goes a step beyond the Model 315-BSC. Its large LED and digital display of measured velocity give unrivaled information to users, making this monitor a powerful diagnostic tool.



AirGard 350-CEM

specifications

	AirGard 350-CEM	AirGard 315-BSC
bar graph display range	25–2,000 fpm (0.13–10.2 m/s)	n/a
alarm range	25–2,000 fpm (0.13–10.2 m/s)	25–2,000 fpm (0.13–10.2 m/s)
alarm delays	user configurable through menu	3 seconds
relay output	NC, NO	NC, NO
remote alarm acknowledge	yes	no
units	selectable (English & Metric)	n/a
display–visual	bar graph, red zone–alarm, yellow zone–marginal, green zone–normal, jumbo LEDs (digital LCD can be enabled)	jumbo green LED for normal jumbo yellow LED for warning jumbo red LED for alarm
alarm indications	jumbo red LED and audible alarm (85 dB @ 4" [10 cm])	jumbo red LED and audible alarm (85 dB @ 4" [10 cm])
high flow alarm disable	yes	n/a
horn silence	temporary and permanent	temporary and permanent
mounting	flush or kit	flush or kit
cable length	10 ft (3 m)	10 ft (3 m)
calibration	single point field calibration recommended	low alarm set point
operating temperature	50–95°F (10–35°C)	50–95°F (10–35°C)
storage temperature	-40–150°F (-40–65°C)	-40–150°F (-40–65°C)
power requirement	9–30V AC/DC	9–30V AC/DC
instrument dimensions		
FRONT FACE PLATE	5.25" x 3.0" x 0.625" 13.3 cm x 7.62 cm x 1.59 cm	5.25" x 3.0" x 0.625" 13.3 cm x 7.62 cm x 1.59 cm
REAR ENCLOSURE	3.0" x 2.0" x 0.5" 7.62 cm x 5.08 cm x 1.27 cm	3.0" x 2.0" x 0.5" 7.62 cm x 5.08 cm x 1.27 cm
accuracy	±5% of reading or 5 fpm, whichever is greater	±5% of set point
agency listings	CE	CE

Specifications are subject to change without notice.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

