

Analog Devices 5B47-K-05

High Performance Plug-In Signal Conditioner



Limited Availability
Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/59462-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

Analog Devices 5B Series Model Definitions

Part Number	Model	Input Range	Output Range
5B30	5B30-01	-10 mV to +10 mV	-5 V to +5 V
	5B30-02	-50 mV to +50 mV	-5 V to +5 V
	5B30-03	-100 mV to +100 mV	-5 V to +5 V
	5B30-04	-10 mV to +10 mV	0 V to +5 V
	5B30-05	-50 mV to +50 mV	0 V to +5 V
	5B30-06	-100 mV to +100 mV	0 V to +5 V
	5B30-Custom	*	*
Part Number	Model	Input Range	Output Range
5B31	5B31-01	-1 V to +1 V	-5 V to +5 V
	5B31-02	-5 V to +5 V	-5 V to +5 V
	5B31-03	-10 V to +10 V	-5 V to +5 V
	5B31-04	-1 V to +1 V	0 V to +5 V
	5B31-05	-5 V to +5 V	0 V to +5 V
	5B31-06	-10 V to +10 V	0 V to +5 V
	5B31-07	-20 V to +20 V	-5 V to +5 V
	5B31-Custom	*	*
Part Number	Model	Input Range	Output Range
5B32	5B32-01	4 mA to 20 mA	0 V to +5 V
	5B32-02	0 mA to 20 mA	0 V to +5 V
	5B32-Custom	*	*
Part Number	Model	Input Range	Output Range
5B34	5B34-01	100Ω Platinum, Alpha = 0.00385 -100°C to +100°C (-140°F to +212°F)	0 V to +5 V
	5B34-02	0°C to +100°C (+32°F to 212°F)	0 V to +5 V
	5B34-03	0°C to +200°C (+32°F to 392°F)	0 V to +5 V
	5B34-04	0°C to +600°C (+32°F to 1112°F)	0 V to +5 V
	5B34-C-01	10Ω Copper, Alpha = 0.004274 0°C to +120°C (10Ω@ 0°C) (+32°F to +248°F)	0 V to +5 V
	5B34-C-02	0°C to +120°C (10Ω@ 25°C) (+32°F to +248°F)	0 V to +5 V
	5B34-N-01	120Ω Nickel, Alpha = 0.00672 0°C to +300°C (+32°F to +572°F)	0 V to +5 V
	5B34-Custom	*	*

Part Number	Model	Input Range	Output Range			
5B35	5B35-01	100Ω Platinum, Alpha = 0.00385 -100°C to +100°C (-148°F to +212°F)	0 V to +5 V			
	5B35-02	0°C to +100°C (+32°F to 212°F)	0 V to +5 V			
	5B35-03	0°C to +200°C (+32°F to 392°F)	0 V to +5 V			
	5B35-04	0°C to +600°C (+32°F to 1112°F)	0 V to +5 V			
	5B35-05	-100°C to +200°C (-148°F to +392°F)	0 V to +5 V			
	5B35-C-01	10Ω Copper, Alpha = 0.004274 0°C to +120°C (10Ω@ 0°C) (+32°F to +248°F)	0 V to +5 V			
	5B35-C-02	0°C to +120°C (10Ω@25°C) (+32°F to +248°F)	0 V to +5 V			
	5B35-N-01	120Ω: Nickel, Alpha = 0.00672 0°C to +300°C (+32°F to +572°F)	0 V to +5 V			
	5B35-Custom	*	*			
Part Number	Model	Input Range	Output Range			
5B36	5B36-01	0Ω to 100Ω	0 V to +5 V			
	5B36-02	0Ω to 500Ω	0 V to +5 V			
	5B36-03	0Ω to 1 kΩ	0 V to +5 V			
	5B36-04	0Ω to 10 kΩ	0 V to +5 V			
	5B36-Custom	*	*			
Part Number	Model	Input Range	Output Range			
5B37	5B37-J-01	-100°C to +760°C (-148°F to +1400°F)	0 V to +5 V			
	5B37-K-02	-100°C to +1350°C (-148°F to +2462°F)	0 V to +5 V			
	5B37-T-03	-100°C to +400°C (-148°F to +752°F)	0 V to +5 V			
	5B37-E-04	0°C to +900°C (+32°F to +1652°F)	0 V to +5 V			
	5B37-R-05	0°C to +1750°C (+32°F to +3182°F)	0 V to +5 V			
	5B37-S-05	0°C to +1750°C (+32°F to +3182°F)	0 V to +5 V			
	5B37-B-06	0°C to +1800°C (+32°F to +3272°F)	0 V to +5 V			
	5B37-N-08	0°C to +1300°C (+32°F to +2372°F)	0 V to +5 V			
	5B37-Custom	Type J, K, T, E, R, S, B, N, C	*			
Part Number	Model	Bridge Range	Output Range	Excitation	Sensitivity	Input Bridge Type
5B38	5B38-02	300Ω to 10 kΩ	-5 V to +5 V	+10.0V	3 mV/V	Full Bridge
	5B38-04	300Ω to 10 kΩ	-5 V to +5 V	+10.0V	3 mV/V	Half Bridge

	5B38-05	300Ω to 10 kΩ	-5 V to +5 V	+10.0V	2 mV/V	Full Bridge
	5B38-Custom	300Ω to 10 kΩ	-5 V to +5 V	+10.0V	*	*
Part Number	Model	Input Range			Output Range	
5B39	5B39-01	0 V to +5 V			4 mA to 20 mA	
	5B39-02	-5 V to +5 V			4 mA to 20 mA	
	5B39-03	0 V to +5 V			0 mA to 20 mA	
	5B39-04	-5 V to +5 V			0 mA to 20 mA	
Part Number	Model	Input Range			Output Range	
5B40	5B40-01	-10 mV to +10 mV			-5 V to +5 V	
	5B40-02	-50 mV to +50 mV			-5 V to +5 V	
	5B40-03	-100 mV to +100 mV			-5 V to +5 V	
	5B40-04	-10 mV to +10 mV			0 V to +5 V	
	5B40-05	-50 mV to +50 mV			0 V to +5 V	
	5B40-06	-100 mV to +100 mV			0 V to +5 V	
	5B40-Custom	*			*	
Part Number	Model	Input Range			Output Range	
5B41	5B41-01	-1 V to +1 V			-5 V to +5 V	
	5B41-02	-5 V to +5 V			-5 V to +5 V	
	5B41-03	-10 V to +10 V			-5 V to +5 V	
	5B41-04	-1 V to +1 V			0 V to +5 V	
	5B41-05	-5 V to +5 V			0 V to +5 V	
	5B41-06	-10 V to +10 V			0 V to +5 V	
	5B41-07	-20 V to +20 V			-5 V to +5 V	
	5B41-Custom	*			*	
Part Number	Model	Input Range			Output Range	
5B42	5B42-01	4 mA to 20 mA V to +1 V			+1 V to +5 V	
	5B42-02	4 mA to 20 mA V to +1 V			+2 V to +10 V	
Part Number	Model	Input Range	Output Range	Rise/Fall Time	Step Response	
5B45	5B45-01	0 Hz to 500 Hz	0 V to +5 V	80 ms	150 ms	

	5B45-02	0 Hz to 1 kHz	0 V to +5 V	60 ms	140 ms
	5B45-03	0 Hz to 2.5 kHz	0 V to +5 V	50 ms	130 ms
	5B45-04	0 Hz to 5 kHz	0 V to +5 V	50 ms	130 ms
	5B45-51	0 Hz to 10 kHz	0 V to +5 V	50 ms	130 ms
	5B45-Custom	*	*		
Part Number	Model	Input Range	Output Range	Rise/Fall Time	Step Response
5B46	5B46-01	0 Hz to 25 kHz	0 V to +5 V	15 ms	44 ms
	5B46-02	0 Hz to 50 kHz	0 V to +5 V	7 ms	22 ms
	5B46-03	0 Hz to 100 kHz	0 V to +5 V	4 ms	4 ms
	5B46-Custom	*	*		
Part Number	Model	Input Range		Output Range	
5B47	5B47-J-01	0°C to +760°C (+32°F to +1400°F)		0 V to +5 V	
	5B47-J-02	-100°C to +300°C (-148°F to +572°F)		0 V to +5 V	
	5B47-J-03	0°C to +500°C (+32°F to +932°F)		0 V to +5 V	
	5B47-K-04	0°C to +1000°C (+32°F to +1832°F)		0 V to +5 V	
	5B47-K-05	0°C to +500°C (+32°F to +932°F)		0 V to +5 V	
	5B47-T-06	-100°C to +400°C (-148°F to +752°F)		0 V to +5 V	
	5B47-T-07	0°C to +200°C (+32°F to +392°F)		0 V to +5 V	
	5B47-E-08	0°C to +1000°C (+32°F to +1832°F)		0 V to +5 V	
	5B47-R-09	+500°C to +1750°C (+932°F to +3182°F)		0 V to +5 V	
	5B47-S-10	+500°C to +1750°C (+932°F to +3182°F)		0 V to +5 V	
	5B47-B-11	+500°C to +1800°C (+932°F to +3272°F)		0 V to +5 V	
	5B47-Custom	Type J, K, T, E, R S, B, N		*	

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisan^{tg}.com](https://www.artisantg.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisan^{tg}.com | [artisan^{tg}.com](https://www.artisantg.com)

