

C&H Technologies VX405C
M/MA Module Carrier



In Stock

Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/81236-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.



VX405C M/MA Module Carrier

The VX405C carrier provides the mechanical and electrical interfaces between the VXIbus and up to six (6) VITA 12-1996 standard M/MA Modules. The carrier provides VXI register configuration and access to the M/MA modules I/O space and memory (if present). Each M/MA module is controlled separately and appears as a different Logical Address in the VXI environment. Over 200 M/MA modules are available that can provide custom interfacing to the unit under test (UUT). Up to six (6) unique instruments or interfaces may be provided in a single VXI slot.

Specifications:

Number of M/MA Modules Carried:

- Up to six(6). Each appears as an independent VXI instrument.

Unique Logical Address for each M/MA Module:

- Can be configured for sequential numbering or Modulo-8 numbering for Agilent Command Module compatibility.

M/MA Module Triggers:

- TRIGA or TRIGB of M/MA module may be connected to any VXI TTL Trigger under software control.

M/MA Module Interrupts:

- Each module interrupt can have a software programmable VXI IRQ level.

M/MA Module Identification:

- M/MA IDENT function supported.

Connectors:

- Each M/MA Module has its own front panel and connectors.

Indicators:

MODID
SYSFAIL
M/MA Module Access (6)

Power:

+5V @ 1.3 A typical
Plus M/MA Power
+12V and -12V provided to the M/MA Modules but not used by the carrier.

Ordering Information

Description	Part Number
M/MA Mod. Carrier	11027050-0001

VXIbus Compliance

Complies with ANSI/IEEE Std 1014-1987, IEC8921, and VXIbus Rev 1.4

A16/24/32:D8/16/32 Slave

SYSFAIL: Supported

Interrupts: ROAK, programmable levels

BRX tied to BGX

TTL Triggers: Supports I/O synchronous (SYNC) trigger protocol

Form Factor: Size C

Applications

- Multiple instrument types in a single VXI slot.
- Port customer interfaces from ITA to a VXI slot
- VXI ATE "glue logic"

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

