

C&H Technologies VX405C
M/MA Module Carrier



In Stock

Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/81236-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.



M207 Precision Oscillator

The M207 is a precision oscillator source that provides a highly accurate and stable clock reference that can be used as a frequency or time reference. Using selectable switches, the output of the on-board ovenized oscillator can be output as is or be divided by any value from 2 to 16383. The resulting output can be directed to a front SMA connector and/or to either or both of the M-Module triggers. The output can be a 100ns pulse or a square wave.

Specifications:

Ovenized Oscillator:

Nominal Frequency:	10MHz
Stability (Freq. vs. Temp)	± 0.01 ppm
Aging (Freq. vs. Time)	
1 st year	± 0.1 ppm
10 years	± 1.0 ppm
Cal. (Freq. vs. Control)	± 1.0 ppm
Warm Up (Freq. Ref. to 1 hr.)	
5 minutes	± 0.1 ppm
30 minutes	± 0.01 ppm

Front panel accessible calibration
25-turn potentiometer provided for
10 year adjustability.

Pulse Output: (front panel)

High, I_{OH} = -24mA	3.76V min.
Low, I_{OL} = 24mA	0.44V max.
Source/Sink	± 50 mA
Rise/Fall (0.8 to 2.0V)	1.5ns
Impedance (selectable)	3 or 50 Ω

Pulse Width: 100ns*

* Pulse width is 50% of period when
"Square Wave Output" or "No divide"
output is selected.

Outputs:

- Front Panel
- M-Module Trig A
- M-Module Trig B

Switch Controls:

- Divide-by-N Value (3 to 16383)
- Clock Out Select
 - Square Wave Output ($N \div 2$)
 - Divide-By-2
 - No divide (10MHz output)
 - Divide-By-N
- M-Trigger A/B Output Enable
- Front Panel Output Enable
- Front Panel Output Impedance

Front Panel Connector: SMA

Temperature:

Operating:	0°C to 50°C
Storage:	-40°C to 70°C

Power:

+5V (during warm-up)	500mA
+5V (after warm-up)	250mA

M Module Compliance

Complies with ANSI/VITA Std. 12-1996 for single-wide M-Modules; however, the module does require or support data transfers.

Compatible with VXI, VME, PCI, cPCI and other M Module carriers.

Applications

- Frequency or Time Reference
- M-Module Triggering
- Synchronization of data acquisition hardware

Ordering Information

Part Number 11028610-0001

Additional Information

User Manuals for C&H carriers and this module can be found on our website at www.chtech.com.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanTG.com](https://www.artisanTG.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanTG.com | [artisanTG.com](https://www.artisanTG.com)

