



Limited Availability
Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/97412-2>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

PXC Frame Grabber Family

Specifications & Features Overview Common to all PXC Family Members

Specifications

- **Bus** PCI bus master design for real-time image capture
- **Input video format** NTSC, PAL, SECAM, S-video
- **Input video** 1 V peak to peak, 75 ohms
- **Output formats** Color: YcrCb 4:2:2 and 4:1:1; RGB 32, 24, 16, 15; Monochrome: Y8
- **Resolution** NTSC: 640 x 480; PAL/SECAM: 768 x 576
- **Power** + 5 VDC, 500 mA
- **Camera Power** + 12 VDC output
- **Supported Operating systems** Win 95 / 98 / ME, Win NT / 2000 / XP
- **Supported Languages** C / C++, C#, Visual Basic and Visual Basic .NET

Features

- **Sampling jitter** Maximum of ± 4 ns relative to horizontal synchronization (for a stable source)
- **External trigger** Input pulled by 10k ohm to 5 V, trigger requires a TTL pulse of 100 ns (minimum); software programmable edge or level sensitivity; software programmable polarity
- **Video noise** < 1 LSB (least significant bit)
- **Video Multiplexer** Standard product: four video inputs (only one can S-video); Standard product plus Optional Control Package: four video inputs, any or all of which can be S-video
- **Real time scaling** With interpolation, plus horizontal and vertical cropping
- **DAC reference generator** Eliminates inconsistency of AGC
- **FCC verification and CE marked**
- **Compatible with** CVB, Halcon, ActiVision Tools and Xcaliper

Specific to Individual PXC Family Members

	PXC200AL	PXC200AF
Form Factor	PCI	PCI
4 Composite video inputs	*	*
3 Composite and 1 S-video input	*	
4 S-video inputs		*
Independent DC restore in 4 video inputs		*
Fast field detect for unsynchronized sources		*
1 TTL input	*	
4 TTL inputs		*
4 TTL outputs		*
Horizontal and vertical drive outputs		*

Cables

	PXC200AL Cables	PXC200AF Cables
4 Composite cameras, Basic I/O	CB-009-00	CB-009-00
4 Composite cameras, Extended I/O	N/A	CB-020-00
4 S-video cameras, Basic	N/A	CB-008-00



I/O

4 S-video cameras,

N/A

CB-008-00

Extended I/O

Basic I/O (PXC200-L) - Single trigger input

Extended I/O (PXC200-F, also referred to as the Option Package) - All I/O beyond single trigger input

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

