

8-Axis Motion Controller



Limited Availability
Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/83429-4>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

PMAC2A PC/104

8 Axis

Part Number: 4-3670xx-xx0x-0x00xx

ABOUT PMAC2A PC/104



The PMAC2A PC/104 provides up to 8 axes of control in the smallest form factor that Delta Tau offers, capable of Filtered PWM output, using the PMAC2 CPU.

FEATURES

HARDWARE FEATURES

- 40 MHz DSP563xx CPU (OPT-5AF 80 MHz 560xx equivalent)
- 128K x 24 internal zero-wait-state SRAM
- 512K x 8 flash memory for user backup and firmware
- Latest released firmware version
- RS-232 serial interface
- 4 channels axis interface circuitry, each including:
 - 12-bit +/-10V analog output
 - Pulse-&-direction digital output
- Quadrature encoder inputs A, B, C, channels with differential/single-ended drivers
- 4 input flags, 2 output flags at TTL levels
- 3 PWM top-and-bottom pairs (unbuffered)
- 50-pin IDC header for amplifier/encoder interface

- 34-pin IDC header for flag interface
- PID/notch/feedforward servo algorithms
- 1-year warranty from date of shipment

Servo Features

- Standard digital PID feedback filter
- Velocity, acceleration, and friction feedforward
- 2nd-order notch/low-pass filter
- Gains changeable at any time
- Programmable input, integrator, and output limits
- Optional 35-term pole-placement servo filter

Commutation Features

- Sinusoidal commutation of AC servo motors
- Vector control of AC induction motors
- Digital current-loop closure with direct PWM output (PMAC2)

Compensation Features

- Position compensation tables (1D and 2D)
- Torque compensation tables
- Backlash compensation
- Tool radius compensation

SOFTWARE FEATURES

Trajectory Generation Features

- Linear interpolation mode with S-curve accel/decel
- Circular interpolation mode with S-curve accel/decel
- Rapid point-to-point move mode
- Cubic B-spline interpolation mode
- Cubic Hermite-spline (PVT) interpolation mode
- Automatic move-until-trigger functions with hardware capture
- Interactive jog moves
- Optional multi-move lookahead for velocity and acceleration limiting

Safety Features

- Hardware and software overtravel limits
- Amplifier enable/fault handshaking
- Following error limits
- Integrated current limit
- Encoder loss detection (some versions)
- Watchdog timer
- Program and communications checksums

Computational Features

- Real-time multi-tasking operating system
- 48-bit floating-point math for user programs
- Trigonometric and transcendental functions
- Automatic type-matching of different variable types

Feedback sensor types that can be processed

- Digital quadrature encoders
- Sinusoidal encoders, interferometers
- Resolvers
- Potentiometers
- LVDTs, RVDTs
- Parallel-format encoders, interferometers
- MLDTs
- Serial absolute encoders (e.g. SSI)

Coordination and Master/Slave Features

- User-defined coordinate systems for automatic coordination of axes
- Separate coordinate systems for independent motion of axes
- Multi-motor axis support (e.g. gantries)
- Dynamic axis transformations (e.g. offsets, rotations, mirroring)
- Electronic gearing (no programming required)
- Electronic cams with programmable profiles

Motion Program Features

- High-level programming language
- Automatic sequenced execution of moves
- Calculations and I/O synchronous to motion
- Axes programmed in user engineering units
- Motion values as constants or expressions
- Automatic coordination of multiple axes
- Ability to execute G-code programs

PLC Program Features

- Execution asynchronous to programmed motion
- I/O control as in hardware PLC
- Executive functions for standalone applications
- Safety and status monitoring
- Servo gain scheduling
- Data reporting functions
- Access to all registers in controller

OPTIONS

Processor and Firmware Options

- OPT-10 - Firmware version specification
- OPT-5AF - 40 MHz DSP56311 CPU
- OPT-5CF - 80 MHz DSP563xx CPU (160 MHz 560xx equivalent)
- OPT-5EF - 160 MHz CPU (320 MHz 560xx equivalent)
- OPT-6 - Extended-servo-algorithm firmware
- OPT-6L - Multi-block lookahead firmware
- OPT-8A - High-accuracy clock crystal (+/-25ppm)

Base Board Options

- OPT-12 - 2-channel on-board 12-bit A/D converter
- OPT-2A - PC/104 Bus Stack Interface

Connector Options

- Terminal Block 10-pin - 10-pin flat cable breakout board
- Terminal Block 34-pin - 34-pin flat cable breakout board
- Terminal Block 50-pin - 50-pin flat cable breakout board

ACCESSORY

Axis Interface Boards

- ACC-1P - Additional 4 Axis Interface, feedback & I/O, PC/104 stack board
- ACC-8ES - 4 Channel Analog Servo (16-bit) Interface, PC/104 stack board
- ACC-8FS - 4 Channel Digital Direct PWM, PC/104 stack board

Feedback Interface Boards

- ACC-1P - Additional 4 Axis Interface, feedback & I/O, PC/104 stack board
- ACC-28B - Analog-to Digital (A/D) Hi-Res Conversion Board
- ACC-51S - High Resolution Sinusoidal Interpolator, PC/104 stack board
- ACC-8TS - Interface to ACC-28B Hi- Res analog inputs, PC/104 stack board

Digital I/O Boards

- ACC-1P - Additional 4 Axis Interface, feedback & I/O, PC/104 stack board

- ACC-2P - High-speed Communications / Digital-I/O, PC/104 stack board
- ACC-34AA - 32 Inputs and 32 Outputs Optically Isolated, I/O board
- ACC-34B - 32 Inputs and 32 Outputs for Opto-22
- ACC-35A - Thumbwheel Port Differential Line Driver, Local
- ACC-35B - Thumbwheel Port Differential Line Driver, Receiver
- ACC-65ETH - Modbus/TCP-IP OPTO (Sourcing 24in/24out)
- ACC-76 - 32 Inputs and 32 Outputs for SNAP I/O from Opto-22
- ACC-77 - 64 Inputs module for SNAP I/O from Opto-22

Communication Interface Boards

- ACC-26A - Serial Communications Optical Isolation Board
- ACC-2P - High-speed Communications / Digital-I/O, PC/104 stack board

Power Supply

- ACC-2A - Power Supply - +/-15V 0.4 A & +5V HBAA-40W
- ACC-2B - Power Supply - +/-15V (0.8 A) & +5V HBAA-40W

PC/104 Accessories

- ACC-PC104 - PC-104 size COMPUTER

Cable Accessories

- ACC-21F - Cable 50-pin card-edge to 34-pin IDC header for PMAC (1) JOPT connector

Demo/Test Accessories

- ACC-3P - 50-pin to 60-pin JMACH adapter board

Miscellaneous Accessories

- ACC-40 - On-site 2-Day Field Service and Training

Warranty

- ACC-22 - Extended Two Year Warranty
- ACC-2P - High-speed Communications / Digital-I/O, PC/104 stack board

SOFTWARE

Development Software

PMAC Executive Pro2 Suite

CNC Software

PMAC-NC Pro2 Runtime

Tools and Libraries

Power PMAC Communication library

Tools and Libraries

PMAC HMI Pro2 Designer

CNC Software

PMAC-NC Pro2 Designer

Tools and Libraries

PMAC HMI Pro2 Runtime

Development Software

Power PMAC IDE

MANUALS

PMAC2 User Manual - User Manual

EZ PMAC2A PC104 Setup - PMAC2A PC104 Quick Setup Manual

PMAC2A PC104 HRM - Hardware Reference Manual

Flex CPU - Hardware Reference Manual

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

