

Trig-Tek 801B
Compressor



**Limited Availability
Used and in Excellent Condition**

Open Web Page

<https://www.artisantg.com/77519-3>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.



MODEL 801B COMPRESSOR



tti 60 dB Dynamic Range

tti Crossover Network

tti Compression Meter

tti Automatic and Manual Set Compression Speeds

tti Interlocked Safety Controls

tti Isolated Chassis and Signal Grounds

The Trig-Tek, Inc. Model 801B Compressor is designed to provide automatic level control in systems using frequencies from 2 to 10 kHz to provide automatic compression of a signal. It is, of course, compatible with the Trig-Tek, Inc. Model 701B Sweep Generator. It can receive two feed-back signals, when working with the Trig-Tek, Inc. Model 610B Vibration Monitor (described on the rear page). Any two of the three signals, Acceleration, Velocity, and Displacement can be used to

control the output from the Sweep Generator-Compressor combination. The parameter controlling is indicated by LED indicators on the front panel labeled Channel 1 and Channel 2. Front panel SET CONTROLS are adjustable for each channel to determine the level and crossover point of control from Channels 1 and 2. Compression speed is automatically selected (proportional to frequency), or manually selected. A rear panel terminal strip provides for isolated signal and chassis grounds, external shutdown, and external reset.

SPECIFICATIONS

SIGNAL INPUT

Wave Form	Sine Wave
Impedance	50 kOhm
Frequency Range	2 Hz to 10 kHz
Level	5 V rms (nominal)
Connector	Isolated BNC (rear panel)

FEEDBACK INPUTS (Channel 1 and 2)

Impedance	50 kOhm
Frequency Range	2 Hz to 10 kHz
Level	0-5 V rms
Connectors	Two isolated BNC (rear panel)

SIGNAL OUTPUT

Impedance	Less than 50 ohm (5 mA max.)
Frequency Range	2 Hz to 10 kHz
Level	0 to 5 V rms
DC Off Set	0±5 mV
Hum and Noise	70 dB (min.) below F.S. output
Dynamic Range	60 dB
Connector	Isolated BNC

CONTROLS

POWER—Switch	Turns Power On and Off
MODE—Switch	Selects Set-Up, Operate, or Bypass
Bypass*	Connects signal input to signal output
Set-Up**	Provides manual control for Set-Up
Operate***	Provides automatic compression of system as set
GAIN—Control	Functions in conjunction with MODE switch as described below:

*In Bypass—A level control

**In Set-Up—Adjusts output for desired control as indicated on Vibration Monitor

***In Operate—Sets compression range as indicated on Compressor Meter.

Reset When the MODE switch is changed, the signal output is forced to full compression. The

Lo-Hi—Switch

SET LEVEL—Control (Two controls) Permits setting the Level and crossover points at which the compressor controls.

SPEED—dB/sec. Sets 1, 3, or 10 dB/second compressor speed.

SPEED—Auto-Manual Selects automatic or manual control of up to 100 times the set compression speed (1, 3, or 10 dB/sec.).

MULTIPLIER—LIMIT In Manual, this control multiplies the compressor speed continuously from 1 to approximately 100 times. In Automatic, the compressor speed increases with frequency until the Limit control setting is reached, and then holds at that point for even higher frequencies.

INDICATORS

POWER—LED	Illuminates when power is ON.
Channel 1 LED	Indicates which feedback input channel is controlling.
Channel 2 LED	
Reset LED	Indicates when unit is in full compression and must be reset by turning GAIN control full CCW Interlocked with MODE switch.
COMPRESSION—Meter	Indicates gain deviation from set point.

DIMENSIONS

Width	19 in.	48.2 cm
Height	3.5 in.	8.9 cm
Depth	10 in.	33 cm
Weight	10 lb.	

POWER

110 or 220 V rms ±10%
50-400 Hz
Less than 8 W

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

