

Excalibur Systems EXC-1553PCMCIA/EP

## MIL-STD-1553 Advanced Interface for PCMCIA

### Type III Card



Limited Availability  
Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/84701-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source  
for quality pre-owned  
equipment.

**Artisan Technology Group**

(217) 352-9330 | [sales@artisanng.com](mailto:sales@artisanng.com) | [artisanng.com](http://artisanng.com)

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

# EXC-1553PCMCIA/EPII

The EXC- 1553PCMCIA/EPII is an intelligent, memory-mapped MIL-STD-1553 interface card which complies with the Personal Computer Memory Card International Association (PCMCIA Release 2.1) standard, including Plug and Play. The card's small size and suitability for PCMCIA compatible notebook computers with Type II slots make it a complete solution for developing and testing 1553 interfaces and for performing system simulation of the MIL-STD-1553 bus, both in the lab and in the field.

## General Specifications:

- ◆ Supports 1553A/B, F-16, McAir
- ◆ 32K x 8 dual-port RAM
- ◆ Board setup modifiable in real time
- ◆ Programmable Interrupts
- ◆ Programmable Time Tag resolution (RT & MON)
- ◆ Reinforced I/O connector
- ◆ Loopback mode facilitates 1553 cable testing
- ◆ Direct or transformer bus coupling



## Host Interface

- ◆ PCMCIA compliance: PCMCIA release 2.1  
Flash based CIS table
- ◆ Memory space occupied: User-programmable
- ◆ Power: +5V  $\pm$ 5% @ 0.4A (0% duty cycle)  
@ 0.9A (75% duty cycle)

## Physical Characteristics

- ◆ Mechanical format: 86mm x 54mm x 10mm  
(PCMCIA type II)
- ◆ Weight : 100 grams

## Operating Environment

- ◆ Temperature: 0° - 70°C
- ◆ Humidity: 5% - 90% noncondensing
- ◆ MTBF: 50,000 hours at 25°C, G<sub>F</sub>

## Software Support

- ◆ C Drivers with source code
- ◆ Merlin+ Windows software for Windows  
9x/2000/XP

## Bus Controller Mode

- ◆ Programmable Intermessage delay
- ◆ Programmable RT Response Time Out
- ◆ Programmable Frame Time
- ◆ Loop and single-shot modes

## Remote Terminal Mode

- ◆ Up to 32 RTs
- ◆ Selectable Broadcast Mode
- ◆ Programmable Mode Code Subaddress ID
- ◆ Programmable Status Word
- ◆ Programmable RT response time

## Bus Monitor Mode

- ◆ Three operational modes: Fixed-block, Link-list,  
Look-up Table
- ◆ Three Storage Modes: Store All, Store Only,  
Store After
- ◆ Programmable Triggers and Masks

## Ordering Information

- ◆ EXC-1553PCMCIA/EPII  
Advanced 1553 Interface for PCMCIA Type II
- ◆ EXC-1553PCMCIA/EPII-R  
Hardwired cable connection
- ◆ EXC-1553PCMCIA/EPII-1760  
1760 protocol support
- ◆ EXC-1553PCMCIA/EPII-1760-R  
Hardwired cable connection



January, 2007



311 Meacham Ave ♦ Elmont NY 11003  
Tel [516] 327-0000 / Fax: [516] 327-4645  
e-mail:excalibur@mil-1553.com



# Artisan Technology Group is an independent supplier of quality pre-owned equipment

## Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

## We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

## Learn more!

Visit us at [artisan<sup>tg</sup>.com](https://www.artisantg.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

**We're here to make your life easier. How can we help you today?**

(217) 352-9330 | [sales@artisan<sup>tg</sup>.com](mailto:sales@artisan<sup>tg</sup>.com) | [artisan<sup>tg</sup>.com](https://www.artisantg.com)

