

Exfo VCS-20A-03BL-89

Voice Communicator



\$245.00

In Stock

Qty Available: 1

Used and in Excellent Condition

Open Web Page

<https://www.artisanTG.com/72605-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanTG.com | artisanTG.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

VCS-20A

NETWORK TESTING – OPTICAL

DISCONTINUED PRODUCT



Combines four convenient tools in a single test set

- Four instruments in one
- 50 dB dynamic range
- Clear digital voice transmission
- Hands-free operation
- Three-way powering
- Multiparty option
- Rugged casing

Flexibility

The VCS-20A brings together four convenient tools in a single test set, combining a full-duplex digital talk set, a stable light source, a 2 kHz tone generator and a 2 kHz tone detector.

Efficient applications

The VCS-20A fulfills more than simple communication needs. In fact, the light source is calibrated and is stable in time and temperature. Use continuous wave selection to perform attenuation and insertion loss tests. Why carry an extra source when one VCS-20A does it all?

Extended dynamic range

Two new configurations have extended the VCS-20A's dynamic range to 50 dB. This wide range makes it possible to use new applications requiring clip-on devices.

Easy-to-use talk set

This unit is rugged and provides high-quality voice communication over a single fiber. The unit's hands-free operation is convenient and simple: press the Talk button to send or receive a call. As usual, conversations are as clear as if both operators were in the same room.

Powerful and durable

For hours of flawless operation, the three-way powering function automatically selects the best alternative among the choices of rechargeable NiMH battery, 9 V alkaline backup and AC adapter/charger input. Its rugged waterproof casing and protective holster make the VCS-20A the preferred field-testing instrument in the outside plant industry.

SPECIFICATIONS ^a

Model	-02BL	-02BL-ER	-03BL	-03BL-ER
Emitter type	laser	laser	laser	laser
Wavelength (nm)	1310 ± 25	1310 ± 25	1550 ± 25	1550 ± 25
Spectral width (typical) (nm)	5	5	5	5
Optimum fiber type (μm)	9/125	9/125	9/125	9/125
Distance range ^b (approximately) (km/mi.)	128/80	142/89	180/112	200/125
Power output (dBm)/dynamic range (dB)				
9/125 μm	-5/45	-5/50	-5/45	-5/50
50/125 μm	-5/30	-5/35	-5/30	-5/35
62.5/125 μm	-5/28	-5/33	-5/28	-5/33
Stability (dB)				
1 hour ^c	± 0.10	± 0.10	± 0.10	± 0.10
8 hours ^d	± 0.20	± 0.20	± 0.25	± 0.25

GENERAL SPECIFICATIONS

Size (H x W x D)	220 mm x 110 mm x 50 mm	(8 3/4 in x 4 1/2 in x 2 in)
Weight		
unit	0.9 kg	(1 3/4 lb)
shipping	2.5 kg	(5 lb)
Temperature		
operating	-10 °C to 50 °C	(14 °F to 122 °F)
storage	-30 °C to 60 °C	(-22 °F to 140 °F)
Relative humidity	0 % to 95 % non-condensing	
Power	Built-in rechargeable NiMH battery lasts 17 hours from full charge, recharges in 6 hours; 9 V battery backup supply lasts 10 hours. Automatic transfer to disposable batteries when rechargeable battery pack runs low. AC adapter/charger for continuous use.	

Standard Accessories

User guide, AC adapter/charger, built-in rechargeable batteries, two 9 V alkaline batteries, carrying case, protective holster, shoulder strap, headset with boom microphone and Certificate of Compliance.

Safety

This product complies with 21 CFR 1040.10 and 1040.11, and with IEC 60825-1:2007.

CLASS 1 LASER PRODUCT

Notes

- a. All tests performed at 23°C ± 1°/73.4°F ± 4° after 1 minute warm-up period.
- b. 9/125 μm SMF 28 CPC 3 singlemode fiber.
- c. After 10-minute warm-up period.
- d. After a 20-minute warm-up period.

ORDERING INFORMATION

VCS-20A-XX-XX

Source

- 02BL = 1310 nm laser singlemode
- 03BL = 1550 nm laser singlemode
- 02BL-ER = Extended range 1310 nm laser singlemode
- 03BL-ER = Extended range 1550 nm laser singlemode

Connector

- 58 = FC/APC narrow key
- 89 = FC/UPC
- 90 = ST/UPC
- 91 = SC/UPC
- EI-EUI-28 = UPC/DIN 47256
- EI-EUI-76 = UPC/HMS-10/AG
- EI-EUI-89 = UPC/FC narrow key
- EI-EUI-90 = UPC/ST
- EI-EUI-91 = UPC/SC
- EI-EUI-95 = UPC/E-2000
- EA-EUI-28 = APC/DIN 47256
- EA-EUI-76 = UPC/HMS-10/AG
- EA-EUI-89 = APC/FC narrow key
- EA-EUI-90 = UPC/ST
- EA-EUI-91 = APC/SC7
- EA-EUI-95 = APC/E-20007

Example: VCS-20A-02BL-EI-EUI-89

EXFO Corporate Headquarters > 400 Godin Avenue, Quebec City (Quebec) G1M 2K2 CANADA | Tel.: +1 418 683-0211 | Fax: +1 418 683-2170 | info@EXFO.com

Toll-free: +1 800 663-3936 (USA and Canada) | www.EXFO.com

EXFO America	3701 Plano Parkway, Suite 160	Plano, TX 75075 USA	Tel.: +1 800 663-3936	Fax: +1 972 836-0164
EXFO Asia	151 Chin Swee Road, #03-29 Manhattan House	SINGAPORE 169876	Tel.: +65 6333 8241	Fax: +65 6333 8242
EXFO China	36 North, 3rd Ring Road East, Dongcheng District Room 1207, Tower C, Global Trade Center	Beijing 100013 P. R. CHINA	Tel.: +86 10 5825 7755	Fax: +86 10 5825 7722
EXFO Europe	Omega Enterprise Park, Electron Way	Chandlers Ford, Hampshire S053 4SE ENGLAND	Tel.: +44 2380 246810	Fax: +44 2380 246801
EXFO NetHawk	Elektronikkatie 2	FI-90590 Oulu, FINLAND	Tel.: +358 (0)403 010 300	Fax: +358 (0)8 564 5203
EXFO Service Assurance	270 Billings Road	Chelmsford, MA 01994 USA	Tel.: +1 978 287 5600	Fax: +1 978 287 5700

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at <http://www.EXFO.com/specs>. In case of discrepancy, the Web version takes precedence over any printed literature.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisan^{tg}.com](https://www.artisantg.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisan^{tg}.com | [artisan^{tg}.com](https://www.artisantg.com)

