# Greenspring IP-16ADC IndustryPack Module



Melean Technology Drive

#### In Stock

**Used and in Excellent Condition** 

Open Web Page

https://www.artisantg.com/66311-62

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.

- Critical and expedited services
- In stock / Ready-to-ship

- · We buy your excess, underutilized, and idle equipment
- · Full-service, independent repair center

ARTISAN'
TECHNOLOGY CROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisantg.com | artisantg.com

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.



## **IP-16ADC**

# IndustryPack® with 16 channel, 16-bit analog to digital conversion

#### **Features**

- Up to 16 single-ended or eight differential 16-bit ADC channels
- Precision on-board reference
- Input ranges of 0-5V, 0-10, ±5V, ±10V
- 10 µs conversion time
- Factory calibrated; data in ID PROM

The IP-16ADC provides 16 single-ended or eight differential channels of 16-bit analog to digital conversion on a single-wide IndustryPack. The single-ended and differential inputs may be mixed. A programmable gain amplifier provides a selection of input ranges. Conversions take place in less than 10  $\mu$ s.

Gain and offset calibration parameters are stored in the board's ID PROM.

Note that this product **requires** an external low noise +/- 15 VDC power supply.

#### **Specifications**

Form Factor	Single-wide IndustryPack
IndustryPack bus speed	8 MHz
Wait states	One on writes; none on reads
Number of channels	16 ADC single-ended or 8 ADC differential (may be mixed)
Precision	16 bits
Input voltage ranges	0-10V, 0-5V, ±10V, ±5V nominal; selectable by software
Accuracy	16 bit with no missing codes 0.002% typical (ADC and amp)
Calibration	Offset and gain factory calibrated. Parameters in ID PROM
Conversion time	8 μs. 100 ksamples/sec aggregate if single channel driven
Input impedance	60 Mohm
Input protection	±65 V with power on, ±80 V with power off
Reference	1ppm/C typical, 0.01% accuracy
Dimensions	1.8 inches x 3.9 inches
Power Requirements	+5 VDC, 210 mA typical, 270 mA max +15 VDC external, 45 mA typical, 70 mA max -15 VDC external, 45 mA typical, 70 mA max
Environmental	Operating temperature: 0° to +70°C
	Humidity: 5% to 95% non-condensing
	Storage: -10° to +85°C

#### **Order Information**

IP-16ADC	IndustryPack with sixteen 16-bit ADC channels
IP-TERM	50-screw terminal block with ribbon connector

#### **Corporate Headquarters**

2400 Louisiana Blvd. NE, #5-600 Albuquerque, NM 87110-4316 Tel 505.875.0600 Fax 505.875.0400 Email info@sbs.com

#### **European Headquarters**

Memminger Str. 14 D-86159 Augsburg, Germany Tel +49-821-5034-0 Fax +49-821-5034-119 Email aug-info@sbs.com

Specifications subject to change without notice. All trademarks and logos are property of their respective owners. ©2005 SBS Technologies, Inc. 20050510

For additional contact information, please visit our web site at www.sbs.com



# Artisan Technology Group is an independent supplier of quality pre-owned equipment

### **Gold-standard solutions**

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

# We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

#### Learn more!

Visit us at artisantg.com for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today? (217) 352-9330 | sales@artisantg.com | artisantg.com

