

Limited Availability
Used and in Excellent Condition

Open Web Page

https://www.artisantg.com/68627-6

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group

(217) 352-9330 | sales artisantg.com | artisantg.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- · Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

HAAKE Phoenix II drop-in circulators have been designed to precisely control your laboratory processes under temperature conditions from -90 to +280 degree C. They fit a wide range of baths, refrigerators and cryostats. These versatile circulators come in three capacities (1, 2 and 3 kW) and offer many additional features.

HAAKE Phoenix II

Drop-in circulators for general purpose applications





Phoenix II drop-in circulators



Ease of Use

A single screen display with a "wide angle" view allows the user to set the system in any of six languages using a simple command structure.

Electronic Connections

The unit can be connected to a wide range of external controls via an RS232/RS485 and/or Profibus interface.

A Reliable Supplier

Thermo is a proven industry leader with over 75 years of extensive industry experience. Thermo professionals – around the globe – continue to develop and support the solutions that help you analyze, detect, measure and control your business with increasingly advanced precision.

External Conditions

An optional PT 100 external sensor allows the use of the Phoenix II circulator in precision reactor control to assure ideal temperature conditions in external vessels.

Precision Tool

The use of FuzzyStar software allows the system to make minor changes to optimize your application.

Bath Temperature Gradient

The circulation pump assures even temperature conditions throughout the bath, guaranteeing high precision and low turbulence.




The HAAKE Phoenix II circulator is the successor to the established circulator series Phoenix for precise temperature control of small to medium volumes. The Phoenix II temperature controller is at the heart of a series of devices such as heating, refrigerating or cryostat baths. It allows the user to exactly control the environment in which his or her analyses or tests should run for maximum result or output. The Phoenix II circulator enables pilot production to study the influence of heating or cooling for pilot scale up. Responding to noise level concerns, temperature stability or communication with other instruments, the Phoenix II circulator is the temperature control device for applications in:

- the Pharmaceutical industry for fermentation or other biological processes
- the Petrochemical industry e.g. for viscosity testing of kerosene composition
- the Plastics industry for Fogging Tests and thermal stability of cables or isolated lines
- the Semiconductor industry for controlling wet bench chemical temperatures or sputtering processes and
- common applications like calibration of sensor devices or material characterization analyses in a wide industry field

HAAKE Phoenix II Performance

The graph shown here was generated during the validation process of the Phoenix II circulator. The test validated the Phoenix II circulator according to DIN 12876-1, 2 and 3 to demonstrate temperature accuracy. After the system reached stability at minus 10 degree in ethanol the test was run tor 30 minutes. The temperature in the bath was measured via a calibrated measuring system.



HAAKE Phoenix II Order Nos. and Types

Order Nos.	Туре	Description	Capacity
440-0001 *	P1	Phoenix II version P1 drop-in Circulator for non-chilled baths,	
		baths of the series V15, V26, W26, W45, B5, B7 and B12 with bath bridges H70, H71, H72 or H73	2 kW
441-0001 *	P2	Phoenix II version P2 drop-in Circulator for non-chilled baths, and as for 440-0001	3 kW
438-0001	P2	Phoenix II version P2 drop-in Circulator with Profibus connection for non-chilled baths,	3 kW
		and as for 440-0001	
442-0001 *	P1 Cool	Phoenix II version P1 drop-in Circulator for use in cooling baths	
		C25P, C30P, C35P, C40P, C41P and C50P	2 kW
445-0001	P1 Cool	Phoenix II version P1 drop-in Circulator for use in cooling bath C75P	1 kW
443-0001	P2 Cool	Phoenix II version P2 drop-in Circulator for use in Cryostat bath CT50W	3 kW
444-0001 *	P2 Cool	Phoenix II version P2 drop-in Circulator for use in cooling baths	
		C25P, C30P, C35P, C40P, C41P, C50P and Cryostat baths CT50L, CT90 and CT90L	2 kW
438-0011	P2 Cool	Phoenix II version P2 drop-in Circulator with Profibus connection as 444-0001	2 kW
446-0001	P2 Cool	Phoenix II version P2 drop-in Circulator for use in cooling bath C75P and CT80	1 kW

All products mentioned above are available in 230V/50-60 Hz

International/Germany

Thermo Electron (Karlsruhe) GmbH Dieselstr. 4 76227 Karlsruhe Tel. +49 (0) 721 4 09 44 44 info.tc.de@thermo.com Benelux

Thermo Electron B.V. Takkebijsters 1 4817 BL Breda Tel. +31 (0) 76 5 87 98 88 info.tc.nl@thermo.com France

Thermo Electron S.A. 16 Avenue du Québec - Silic 765 91963 Courtaboeuf Cedex Tel. +33 (0) 1 60 92 48 00 info.tc.fr@thermo.com United Kingdom Thermo Electron

Ion Path, Road Three Winsford, Cheshire CW7 3GA Tel. +44 (0) 1606 54 87 49 info.tc.uk@thermo.com USA

Thermo Electron 25 Nimble Hill Rd. Newington, NH 03801 Tel. 603 436 9444 info.tc.us@thermo.com

^{*} These products are also available in 115 V/60 Hz version and 1.2 kW (replace Order Nos. XXX-0001 with XXX-0002)

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at artisantg.com for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today? (217) 352-9330 | sales@artisantg.com | artisantg.com

