ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Keysight / Agilent 8350B* at our website: ***Click HERE***

83592A RF Plug-in for the Agilent 8350B, 10 MHz to 20 GHz (Discontinued - Support Information Only)

Data Sheet

Frequency Characteristics:
Range Band 0: 0.01 to 2.4 GHz
Band 1: 2.4 to 7 GHz
Band 2: 7 to 13.5 GHz
Band 3: 13.5 to 20 GHz
Full Band: 0.01 to 20 GHz
Accuracy (25° ±5°C) CW Mode Band 0: ±5 MHz
Band 1: ±5 MHz
Band 2: ±10 MHz
Band 3: ±10 MHz
All Sweep Modes Band 0: ±15 MHz
Band 1: ±20 MHz
Band 2: ±25 MHz
Band 3: ±30 MHz
Full Band: ±50 MHz
Frequency Markers Band 0: ±15 MHz, ±0.5% of sweep width
Band 1: ±20 MHz, ±0.5% of sweep width
Band 2: ±25 MHz, ±0.5% of sweep width
Band 3: ±30 MHz, ±0.5% of sweep width
Full Band: ±50 MHz, ±0.5% of sweep width
Stability With Temperature Band 0: ±200 kHz/°C, typical
Band 1: ±200 kHz/°C, typical
Band 2: ±400 kHz/°C, typical
Band 3: ±600 kHz/°C, typical
Full Band: ±600 kHz/°C, typical
With 10 dB Power Change: Band 0: ±200 kHz/°C
Band 1: ±200 kHz/°C
Band 2: ±400 kHz/°C
Band 3: ±600 kHz/°C
Full Band: ±600 kHz/°C
With 3:1 Load SWR: Band 0: ±100 kHz/°C
Band 1: ±100 kHz/°C
Band 2: ±200 kHz/°C
Band 3: ±300 kHz/°C
Full Band: ±300 kHz/°C

Agilent Technologies

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Output Characteristics:
Maximum Leveled Power:(25°C) Normal: Band 0: 10 mW
Band 1: 10 mW
Band 2: 10 mW
Band 3: 10 mW
Full Band: 10 mW
Option 002: Band 0: 10 mW
Band 1: 7.0 mW
Band 2: 6.3 mW
Band 3: 5.0 mW
Full Band: 5.0 mW
Power Level Accuracy: Band 0: ±1.5 dB
Band 1: ±1.3 dB
Band 2: ±1.3 dB
Band 3: ±1.4 dB
Full Band: ±1.5 dB
Spurious Signals: Harmonics and Subharmonics: Band 0: <-25 dBc
Band 1: <-25 dBc
Band 2: <-25 dBc
Band 3: <-25 dBc
Full Band: <-25 dBc
Output Power Resolution Displayed: 0.1 dB Programmable/Settable: 0.01 dB
Minimum Settable Power: -2 dBm Option 002: (-72 dBm with)
Power Sweep Calibrated Range: >12 dB Option 002: >9 dB

Modulation Characteristics:
External AM Frequency Response: 100 kHz, typical Maximum Input: 15 V Range of Amplitude Control: 15 dB, typical Sensitivity: 1 dB/V, typical Input Impedance: @ 10 kohms
External FM Maximum Deviations for Modulation Frequencies DC to 100 Hz: ±75 MHz 100 Hz to 1 MHz: ±7 MHz 1 MHz to 2 MHz: ±5 MHz 2 to 10 MHz: ±1 MHz Sensitivity (switch selectable) FM Mode: -20 MHz/V, typical Phase-Lock Mode: -6 MHz/V, typical Input Impedance: @ 2 kohms
External Pulse Modulation Pulse Input: TTL 0.01 to 20 GHz: Square wave modulation up to 30 kHz 0.01 to 2.5 GHz Rise/Fall Time: 15 nsec, typical Minimum RF Pulse Width Internally Leveled: 1 µsec, typical Unleveled (power set to +20 dBm): 200 nsec 2.5 to 20 GHz Rise/Fall Time: 10 nsec, typical Minimum RF Pulse Width Internally Leveled: 1 µsec, typical Unleveled (power set to +20 dBm): 100 nsec On/Off Ratio: >30 dB, typical

General Specifications:
Minimum Sweep Time: 10 ms (single band) 25 ms (full band)
Auxiliary Output Rear Panel: 2.3 to 7 GHz Fundamental Oscillator Output: 0 dBm, nominally
Frequency Reference Output: 1 V/Hz (0.01 to 18 GHz) 0.5 V/GHz (0.01 to 20 GHz) ±25 mV
RF Output Connector: Type-N, female
Net Weight: 6.0 kg (13.2 lb)
Shipping Weight: 9.2 kg (20 lb)
Furnished: Operating/service manual



Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP