

Hamamatsu C6979-01

## Constant Current Power Supply



**\$1350.00**

**In Stock**

**Qty Available: 1**

**New From Surplus Stock**

**Open Web Page**

<https://www.artisantg.com/50647-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source  
for quality pre-owned  
equipment.

**Artisan Technology Group**

(217) 352-9330 | [sales@artisantg.com](mailto:sales@artisantg.com) | [artisantg.com](http://artisantg.com)

- Critical and expedited services
- In stock / Ready-to-ship
- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

# C6979

## SPECIFICATIONS

Output voltage with no load . . . . .	C6979      Approx. 130Vdc		
Trigger voltage output . . . . .	C4251      20 to 30kV		
Output current (Adc) . . . . .	3.5	5.4	5.5
Steady operation voltage ( Vdc) . . . . .	12±3	15±2	18±2
Lamp wattage rating			
Xenon lamps . . . . .	35W	75W	
Mercury-xenon lamps . . . . .	50W	75W	100W
Typical applicable lamps			
Xenon lamps . . . . .	L2173 L2193 L2421	L2174 L2194 L2481	L2422 L7046
Mercury-xenon lamps . . . . .			
Output regulation	±0.1% or less (for ±10% change in AC line input)		
Input regulation . . . . .	±0.1% or less (for ±10% change in load)		
Load regulation . . . . .	0.1% p-p or less (at rated input and output)		
Ripple . . . . .	±0.1%/h or less (after 30 minute warm-up)		
Drift . . . . .	1A		
Overload protection . . . . .	AC input voltage . . . . .		
(Selectable by input voltage selector switch; factory setting 100Vac)	100/115/200/230Vac ±10%		
AC input fuse . . . . .	AC input fuse . . . . .		
Current consumption . . . . .	5A for 100/115Vac input (factory setting)		
Operating temperature . . . . .	3A for 200/230Vac input		
Performance guaranteed			
temperature . . . . .	400VA		
Cooling method	+5 to +35°C		
C6979 . . . . .	Forced air cooling		
C4251 . . . . .	Non (natural cooling)		
Dimensions			
C6979 . . . . .	144(W) × 280(D) × 176(H) mm		
C4251 . . . . .	100(W) × 60(D) × 89(H) mm		
Weight			
C6979 . . . . .	Approx. 10kg		
C4251 . . . . .	Approx. 810g		


### NOTE:

1. The C6979 power supply must be used in combination with the C4251 starter.
2. The above specifications are measured at  $23 \pm 5^\circ\text{C}$  after 30 minute warm-up.
3. Specifications are subject to change without prior notice due to performance improvement or other factors.

**HAMAMATSU**

HAMAMATSU PHOTONICS K.K. Electron Tube Center

DIMENSION (Unit: mm)  
C6979



Unit : mm

**Artisan Technology Group** is an independent supplier of quality pre-owned equipment

## **Gold-standard solutions**

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

## **We buy equipment**

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

## **Learn more!**

Visit us at [artisantg.com](http://artisantg.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

**We're here to make your life easier. How can we help you today?**

(217) 352-9330 | [sales@artisantg.com](mailto:sales@artisantg.com) | [artisantg.com](http://artisantg.com)

