Heurikon Laguna

VMEbus Module

In Stock

Used and in Excellent Condition

Open Web Page

https://www.artisantg.com/65150-1

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.

ARTISAN® TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisantg.com | artisantg.com

- Critical and expedited services
- In stock / Ready-to-ship
- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

Laguna Technical Specs

Bus Interface

- **VMEbus**
- VME64 architecture with 64-bit data path, 32-bit addressing and 7 bus interrupts
- Operates in Master or Slave Mode (Compliance Level: D64A32(7))
- 64-bit and 32-bit wide block transfers using local DMA capability
- Uses Newbridge SCV64 interface IC
- 58 Mbytes/sec peak master VME read rate

- **Mailbox interrupts**
- Allows remote control of Laguna via specified VMEbus addresses
- CPU interrupt and VMEbus lock functions supported

- **I/O bus**
- Connects all 8-bit board peripherals such as real-time clock, serial ports, timers, counters, and display drivers
- Minimizes loading on local bus
- Endian independent

Processor & Memory

- **IDT R4600**
- Operates at 133 MHz
- True 64-bit RISC processor
- 5-stage instruction pipeline
- 16 KB instruction cache / 16 KB data cache
- Floating point unit on-chip
- Instruction set fully compatible with R4000 processor family
- 92 SPECint92 @ 133 MHz
- 82 SPECfp92 @ 133 MHz

- **Random Access Memory**
- 16 or 64 Mbytes DRAM on-card
- 16 or 64 Mbytes DRAM on mezzanine
- Memory options available: 16, 32, 64, 128 Mbytes
- 2 bank interleaved architecture with parity

- **Read Only Memory**
- Two 44-pin PLCC EPROM sockets
- Up to 1 Mbyte capacity
- Provides boot code storage

- **Flash Memory**
- 2 Mbytes flash memory on-board
- Board can be booted from flash memory
- Provides field upgradeable non-volatile program storage

- **Timers/Counters**
- Three 16-bit timer/counters
- Interrupt capability

- **Real-Time Clock**
- DS1386 battery backed real-time clock
- Watchdog timer providing interrupt resolution of 0.01 seconds to 99.9 seconds
- 32 Kbytes of NVRAM

Peripheral I/O

- **Ethernet Interface**
- Intel 82596DX 32-bit LAN coprocessor
- On-chip DMA and memory management
- On-chip FIFOs
- Conforms to IEEE 802.3

- **Small Computer Systems Interface (SCSI)**
- NCR 53C720 SCSI I/O processor
- ANSI compatible SCSI 2 (fast & wide) permitting connection of up to fifteen additional independent, compatible I/O controllers
- 8 or 16-bit single ended I/O
- Supports variable block size and scatter/gather data transfers
- Supports 32-bit word data bursts with variable burst lengths
- Full 32-bit on-chip DMA to speed up memory-to-I/O transfers without host CPU intervention
- 20 Mbytes/sec 16-bit synchronous performance
- 10 Mbytes/sec 8-bit synchronous transfers
- High level programmer's interface (SCRIPTS™)
- Low-level programmability

- **Serial I/O**
- Two front panel serial I/O ports provided via 85C30 controller
- Multi-protocol data communications peripheral

Software support

- Wind River Systems' VxWorks(TM) real-time operating system and development environment
- IDT/sim on-board monitor and power-on diagonostics
- Rational Software Ada
- Green Hills compilers and tools

- Multilayer with ground and VCC planes
- Board size: 23.35 cm x 16.0 cm (9.19 in. x 6.3 in.)
- Estimated power requirements: +5VDC @ 5A, +-12VDC @ 0.1A
- Storage Temperature: -40C to 85C
- Operating range: 0-55C, 85% relative humidity (non-condensing)

- **Front Panel**
- SCSI, Ethernet, and serial connectors
- User programmable 7 segment display
- Reset / Interrupt switch

Target Applications

- Video on demand
- Graphics-oriented applications such as simulation, image processing and printing
- Data acquisition
- Machine vision
- Embedded control
- Communications system control

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP