

Novatel UIMU-H58

Tactical Grade Ring Laser Gyro Inertial Measurement Unit



© Artisan Technology Group

In Stock

Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/43621-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

UIMU-HG1700-AG58

Economical, tactical grade IMU combines with SPAN GNSS+INS technology from Hexagon | NovAtel to deliver 3D position, velocity and attitude solution

World-leading GNSS+INS technology

SPAN GNSS+INS technology brings together two different but complementary technologies: Global Navigation Satellite System (GNSS) positioning and inertial navigation. The absolute accuracy of GNSS positioning and the stability of Inertial Measurement Unit (IMU) gyro and accelerometer measurements are deeply coupled to provide an exceptional 3D navigation solution that is stable and continuously available, even through periods when satellite signals are blocked.

UIMU-HG1700-AG58 overview

The UIMU-HG1700-AG58 contains a Honeywell HG1700-AG58 tactical grade IMU containing ring-laser gyros and servo accelerometers. The UIMU-HG1700 handles the power requirements of the IMU from a 12-28 VDC power input and provides the IMU data to a SPAN enabled GNSS+INS receiver such as the PwrPak7 using a custom NovAtel interface. IMU measurements are used by the GNSS+INS receiver to compute a blended GNSS+INS position, velocity and attitude solution at up to 100 Hz. The HG1700-AG58 is a commercial product that can be licensed under the jurisdiction of the U.S. Department of Commerce for customers outside the United States.

Advantages of UIMU-HG1700-AG58

Honeywell's high production volume of HG1700 IMUs enables excellent tactical grade performance for an economical price with short delivery times. The UIMU-HG1700-AG58 is available as a complete assembly including the IMU and environmentally sealed enclosure. For customers who already have the HG1700-AG58 IMU, the enclosure can be purchased separately and the IMU easily integrated.

Improve UIMU-HG1700-AG58 accuracy

Receivers from NovAtel provide your choice of accuracy and performance, from decimetre to RTK-level positioning. For more demanding applications, Waypoint Inertial Explorer post-processing software can be used to post-process real-time data and offers the highest level of accuracy with the system.



Benefits

- High performance IMU
- Optimal for aerial, hydrographic survey and industrial applications
- Easy integration with SPAN capable GNSS+INS receivers from NovAtel
- Rugged design ideal for challenging environments
- High sensor dynamic range

Features

- Ring-laser gyros and servo accelerometers
- Stationary INS alignment capable
- IMU data rate: 100 Hz
- SPAN GNSS+INS capability with configurable application profiles

IMU performance¹**Gyroscope performance**

Technology	Ring laser
Dynamic range	1074 °/s
Bias drift	1.0 °/hr
Angular random walk	0.125 °/√hr

Accelerometer performance

Technology	RBA
Dynamic range	37 g
Bias drift	1.0 mg
Velocity random walk	0.02 m/s/√hr

Physical and electrical

Dimensions	168 x 195 x 146 mm
Weight	4.5 kg
Power	
Input voltage	+12 to +28 VDC
Power consumption	8 W (typical)
Connector	MIL-C-38999-III, 22 pin
Communication interface	RS-232 or RS-422 UART
Connection to receiver	Receiver serial port
Data rate	
IMU raw data rate	100 Hz
INS solution	Up to 200 Hz

Environmental

Temperature	
Operating	-30°C to +60°C
Storage	-45°C to +80°C
Humidity	95% non-condensing
MTBF	2,000 hrs
Waterproof	IEC 60259 IPX7
Dust	IEC 60259 IP6X
Compliance	
	FCC, ISED, CE

Performance during GNSS outages^{2,3,4}

Outage duration	Positioning mode	Position accuracy (m) RMS		Velocity accuracy (m/s) RMS		Attitude accuracy (degrees) RMS	
		Horizontal	Vertical	Horizontal	Vertical	Roll/Pitch	Heading
0 s	RTK ⁵	0.02	0.03	0.010	0.010	0.010	0.020
	TerraStar-C PRO PPP	0.025	0.05				
	Single point	1.00	0.60				
10 s	RTK ⁵	0.14	0.08	0.025	0.012	0.015	0.028
	TerraStar-C PRO PPP	0.14	0.10				
	Single point	1.12	0.65				
60 s	RTK ⁵	2.75	0.53	0.110	0.017	0.020	0.040
	TerraStar-C PRO PPP	2.75	0.55				
	Single point	3.75	1.10				
	RTK with Land profile and DMI	2.50	0.53				
0 s	Post-Processed using Inertial Explorer	0.01	0.01	0.015	0.010	0.004	0.008
10 s		0.01	0.02	0.020	0.010	0.004	0.009
60 s		0.13	0.02	0.021	0.010	0.005	0.013

1. Supplied by IMU manufacturer.

2. Performance may be impacted in conditions with unmitigated vibration or significant temperature variations.

3. Performance with one antenna, no DMI, and default SPAN profile unless otherwise specified.

4. Typical. Based on mixed urban road vehicle dynamics and benign GNSS conditions.

5. 1 ppm should be added to all values to account for additional error due to baseline length.

Contact Hexagon | NovAtel

sales.nov.ap@hexagon.com 1-800-NOVATEL (U.S. and Canada) or 403-295-4900 | China: 0086-21-68882300 | Europe: 44-1993-848-736 | SE Asia and Australia: 61-400-883-601. For the most recent details of this product: novatel.com

This document and the information contained herein are provided AS IS and without any representation or warranty of any kind. All warranties, express or implied, are hereby disclaimed, including but not limited to any warranties of merchantability, non-infringement, and fitness for a particular purpose. Nothing herein constitutes a binding obligation. The information contained herein is subject to change without notice. Inertial Explorer, NovAtel, OEM7, SPAN, TerraStar and Waypoint are trademarks of Hexagon AB and/or its subsidiaries and affiliates, and/or their licensors. All other trademarks are properties of their respective owners.

© Copyright 2006 – 2023 Hexagon AB and/or its subsidiaries and affiliates. All rights reserved. A list of entities within the Hexagon Autonomy & Positioning division is available at <https://hexagon.com/company/divisions/autonomy-and-positioning>.

D10152 Version 15 | 04 May 2023 | Printed in Canada

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisan^{tg}.com](https://www.artisantg.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisan^{tg}.com | [artisan^{tg}.com](https://www.artisantg.com)

