

ICS ICS-110B-32B

32-Channel, 24-Bit Sigma-Delta ADC VME Module



In Stock

Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/70367-3>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

ICS-110A 32-CHANNEL SIGMA-DELTA ADC BOARD



- up to 32 differential inputs;
- sigma-delta ADCs which virtually eliminate complex and expensive anti-alias filtering;
- simultaneous sampling on all channels at rates from 390 Hz/channel to 200kHz/ channel;
- 16-bit and 12-bit resolution output options;
- 90dB dynamic range;
- -90dB interchannel crosstalk.
- front panel synchronizing signals for synchronizing up to 32 ICS-110A boards;
- external or internal clock. Latter is programmable for output rates of 6.4kHz to 200kHz with very high precision;
- 64 KWord on-board storage;
- 32-bit VMEbus and VSB interfaces which support block transfers;
- a 16-bit Front Panel Data Port (FPDP) for direct input to Mercury, CSPI, Sky, Ixthos and other DSP/Array Processors, as well as other ICS products;
- the facility to bus the FPDP outputs from multiple ICS-110A boards into one composite data stream.

Analog Front End	Number Of Analog Input Channels :	32 maximum
	Input Impedance :	10 KOhm
	Full Scale Input :	2.0 Vpp differential*
	Input Signal Bandwidth :	44 kHz max.: 16-bit/100 kHz max.: 12-bit
	Maximum Sampling Rate per Channel :	6.4 MHz
	Maximum Channel Output Rate :	100 kHz: 16-bit/200 kHz: 12-bit
	Maximum Output Data Rate :	3.2 MSamples/s: 16-bit (32-channels) 6.4 MSamples/s: 12-bit (32-channels)
	Programmable Decimation Factor :	1 to 16
	Minimum CLOCK Frequency :	2.0 MHz
	Maximum CLOCK Frequency :	25.6 MHz
16-Bit Mode Performance	Dynamic Range :	> 90 dB @ -1.2dB FS**
	Harmonic Distortion :	< -90 dB @ -1.2dB FS**
12-bit Mode Performance	Dynamic Range :	> 70 dB @ -1.2dB FS**
	Harmonic Distortion :	< -70 dB @ -1.2dB FS**
Data Transfer Capabilities	Output Wordlength :	VMEbus 32 bits (1-2 channels) VSBbus 32 bits (1-2 channels) FPDP 16 bits (1 channel)
	VMEbus Interface :	A32/24/16 D32 BLT Slave Vectored Interrupts 32 Mbytes/sec
	VSBbus Interface :	A32 D32 BLT Slave Polled Interrupts 40 Mbytes/sec
	FPDP Support :	20 Mwords/sec burst
	On-board storage :	64 Kwords
Other	Power :	+5 volts 3.0 amps maximum +12 volts 0.3 amps maximum -12 volts 0.3 amps maximum
	Environmental :	Operating Temperature: 0 - 50°C Humidity: 0 - 95% Rel. Hum., Non-condensi
	Storage Temperature:	0 - 70°C Humidity: 0 - 95% Rel. Hum., Non-condensing
	Board Size :	233 x 160 mm VMEbus 6U standard

*2.0 Vpp in each differential input leg. * 4.0 Vpp for a single-ended input.

**Optimum performance is achieved when the maximum input signal is 1.75 Vpp differential. In this case the output is defined by: 0x9000 < ADC Output Code < 0x7000

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanTG.com](https://www.artisanTG.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanTG.com | [artisanTG.com](https://www.artisanTG.com)

