

Gentran GT435D-10K

## Analog-Digital Pressure Indicator



Limited Availability  
Used and in Good Condition

Open Web Page

<https://www.artisanng.com/88484-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source  
for quality pre-owned  
equipment.

**Artisan Technology Group**

(217) 352-9330 | [sales@artisanng.com](mailto:sales@artisanng.com) | [artisanng.com](http://artisanng.com)

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

**Analog-Digital  
Pressure  
Indicator**

**Model GT435**



- 
- **Universal Pressure Indicator** The Gentran model GT435 analog-digital indicator/power supply is designed for use with any four leg, 350 ohm Wheatstone bridge pressure transducer. Zero and span can be easily adjusted without removing the module. Shunt calibration is a standard feature.
  - **Easy To Read Analog & Digital Displays** The large 240 degree arc international scale makes the analog meter easy to read. Custom face plates, which have specific engineering units or other markings, can be easily added. A 4½ digit LED digital display provides the accuracy needed for setpoints.
  - **Dual Alarm Setpoints** Two alarms can be selected for above or below setpoint control. Relays provide N.O. (normally open) and N.C. (normally closed) contacts for maximum flexibility. Adjustments are made through pots on the faceplate.
  - **Versatility** The GT435 provides a choice of recorder outputs, damping constant, transducer sensitivities, input power, shunt-resistor calibrations, peak-hold, and reset options.
  - **Easy Installation** The easy-to-mount aluminum housing fits a 1/4 DIN cutout. Slide-type metal brackets hold the case firmly in place and can be installed quickly. The electronic module can be easily removed for option selection or service.

# Ordering Information

## TYPICAL PART NUMBER

GT435			D		-10		AB		8		-10K	
Series GT435 Analog-Digital Pressure Indicator	Alarm Setpoints		Recorder Outputs		Control Sequence		Shunt Calibration		Pressure Range *			
	None	No Alarm Setpoints	1	0-1 VDC	None	None	7	Gentran (54.9 Kohm)	5C	0-500		
	D	Dual Alarm Setpoints	2	0-2 VDC	AA	Control I above Control II above	8	Gentran (30.1 Kohm)	1K	0-1,000		
			5	0-5 VDC	AB	Control I above Control II below	9	Dynisco (External)	1.5K	0-1,500		
			6	4-20 mA					3K	0-3,000		
			10	0-10 VDC					5K	0-5,000		
					BA	Control I below Control II above			7.5K	0-7,500		
									10K	0-10,000		
									15K	0-15,000		
									350 BAR	0-350 BAR		
									700 BAR	0-700 BAR		
									500 KG	0-500 Kg/cm <sup>2</sup>		
					700 KG	0-700 Kg/cm <sup>2</sup>						

\* Other ranges available upon request.

The Gentran model GT435 analog-digital pressure indicator/power supply is a combination transducer power supply, indicator, and signal conditioner. It is housed in a 1/4 DIN standard-size case of extruded aluminum, which protects against EMI and RFI noise, heat dispersion, and physical damage. The large 6 inch, 240 degree analog meter is styled for ease of reading and incorporates the new international face. The digital display provides a 4½ digit LED display for quick, accurate readings or adjustment of set-points.

The GT435 is designed for use with a Gentran pressure transducer or any 4 leg, 350 ohm Wheatstone bridge strain-gage transducer. A calibration pushbutton allows for a quick span check and adjustment when you adjust zero at zero pressure. The complete electronic assembly can be removed and/or replaced from the front without disturbing the wiring in back. Various options are furnished as standard, dip-switch selectable. These options include various recorder outputs, transducer input sensitivity, power supply (120 or 240 VAC), dual setpoints, various calibration resistor values, manual or automatic reset on alarms, and overall response time.

The dual setpoint option can be used to give a preliminary warning before an actual shutdown sequence is initiated. You can program HI/HI, LO/LO, LO/HI, and HI/LO. The relays are isolated during a set-point change or calibration check to prevent accidental emergency shutdown.



# Specifications: GT435

## Performance Characteristics

### Standard Ranges:

0-500 psig, 0-1,000 psig, 0-1,500 psig,  
0-3,000 psig, 0-5,000 psig, 0-7,500 psig,  
0-10,000 psig, 0-15,000 psig, 0-350 BAR,  
0-700 BAR, 0-500 Kg/cm<sup>2</sup>, 0-700 Kg/cm<sup>2</sup>

### Special Ranges:

Other ranges available upon request.

### Accuracy:

Analog:  $\pm 2.0\%$  of full scale

Digital:  $\pm 0.1\%$  of full scale or one digit

### Recorder Output:

Accuracy:  $\pm 0.1\%$  of full scale

Repeatability:  $\pm 0.1\%$  of full scale

Linearity:  $\pm 0.1\%$  of full scale

Stability:  $\pm 0.1\%$  of full scale

## Physical Characteristics

### Size:

1/4 DIN

### Meter:

Six (6) inch scale 240 degree arc

### Operating Temperature:

0-140°F

### Weight:

2.5 lbs.

## Electrical Characteristics

### Power:

106-125 or 200-250 VAC, 50/60 hz,  
1/8 Amp maximum

### Zero Adjustment:

$\pm 35\%$  with panel pot

### Sensitivity Adjustment (Span):

1-2.5 mV/V or 2.5-5.0 mV/V,

Switch selectable and fully adjustable.

### Shunt Resistance Calibration:

Selectable for Gentran or Dynisco

### Response Time (Damping):

Selectable at 0.3 or 5.0 seconds

### Recorder Outputs:

Standard: 0-1 VDC, 0-2 VDC, 0-5 VDC  
& 0-10 VDC

Optional: 4-20 mA, Load from  
15-600 ohms

### Transducer Power Supply:

8.2 VDC  $\pm 5.0\%$

## Control Characteristics

### Dual Relays:

2 SPDT (Single Pole Double Throw)

## Control Characteristics (Cont.)

### Relay Rating:

8 Amp @ 125/250 VAC

5 Amp @ 30 VDC

### Set Point Range:

1-100% of full scale

### Accuracy:

$\pm 0.3\%$  of full scale

### Hysteresis:

$\pm 0.5\%$  of full scale

### Indication:

Front panel LED

### Mode:


Above or below set point

### Reset:

Automatic or manual

### Peak Hold:

Optional



# Artisan Technology Group is an independent supplier of quality pre-owned equipment

## Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

## We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

## Learn more!

Visit us at [artisan<sup>tg</sup>.com](https://www.artisantg.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

**We're here to make your life easier. How can we help you today?**

(217) 352-9330 | [sales@artisan<sup>tg</sup>.com](mailto:sales@artisan<sup>tg</sup>.com) | [artisan<sup>tg</sup>.com](https://www.artisantg.com)

