

Limited Availability Used and in Excellent Condition

Open Web Page

https://www.artisantg.com/78239-1

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.

ARTISAN'

Your definitive source for quality pre-owned equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisantg.com | artisantg.com

- Critical and expedited services
- In stock / Ready-to-ship

- · We buy your excess, underutilized, and idle equipment
- · Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

2500 and 2502 Dual Photodiode Meters

The Models 2500 and 2502 Dual Photodiode Meters can measure and display either photodiode current or optical power for two photodiodes with appropriate user-supplied optical power gain/wavelength calibration factors

The Model 2502 includes an analog output jack on the rear panel for each

Measurement Specifications

RANGE	MAXIMUM RESOLUTION	ACCURACY ^{1,2} 23°C±5°C ±(% rdg. + offset)	TEMPERATURE COEFFICIENT 0°-18°C & 28°-50°C ±(%rdg. + offset)/°C	DC INPUT IMPEDANCE ³ (Maximum)
2.000000 nA	1 fA	1.00% + 2 pA	0.01 + 200 fA	20 kΩ
20.00000 nA	10 fA	0.40% + 2 pA	0.01 + 200 fA	20 kΩ
200.0000 nA	100 fA	0.30% + 200 pA	0.02 + 20 pA	200 Ω
2.000000 μA	1 pA	0.20% + 200 pA	0.02 + 20 pA	200 Ω
20.00000 μΑ	10 pA	0.10% + 20 nA	0.01 + 2 nA	2.0 Ω
200.0000 μΑ	100 pA	0.10% + 20 nA	0.01 + 2 nA	2.0 Ω
2.000000 mA	1 nA	0.10% + 2 μA	0.02 + 200 nA	0.2 Ω
20.00000 mA	10 nA	0.10% + 2 μA	0.02 + 200 nA	0.2 Ω

MAXIMUM INPUT: ±20.0mA.

Typical Speed and Noise Rejection⁴

REA	DINCS	10

READINGS/S					
DIGITS	GPIB (SCPI)	GPIB (488.1)	NPLC	NMRR	
41/2	700	900	0.01	_	
51/2	460	475	0.1	_	
61/2	58	58	1	60 dB	

Photodiode Voltage Bias Specifications²

RANGE	RESOLUTION	ACCURACY 23°C ±5°C	MAXIMUM CURRENT	LOAD REGULATION ⁵	TEMPERATURE COEFFICIENT
0 to ±10 V	<400 μV	±(0.15% of setting + 5 mV)	20 mA	< 0.30%, 0 to 20 mA	150 ppm/°C
0 to ±100 V	<4 mV	±(0.3% of setting + 50 mV)	20 mA	< 0.30%, 0 to 20 mA	300 ppm/°C

NOTES:

- 1. Speed = Normal (1.0 NPLC), Filter On.
- 2. 1 year.
- Measured as ΔV_{in}/ΔI_{in} at full scale (and zero) input currents.
- 4. Dual channel, internal trigger, measure only, display off, Autorange off, Auto Zero off, source delay = 0, filters off, limits off, CALC5 and CALC6 off, 60Hz.
- Measured as $\Delta V_{\rm in}/\Delta I_{\rm in}$ at full scale (20mA) and zero load currents.
- Noise floor measured as rms (1 standard deviation), 100 samples, Filter off, open (capped) input.
- 8. Measured (at input triax) as ΔV_{in} at full scale (20mA) vs. zero input currents.

Analog Output Specifications (2502 only)

OUTPUT VOLTAGE RANGE1: OUTPUT IS INVERTING: -10V out for positive full scale input +10V out for negative full scale input

OUPUT IMPEDANCE: $1k\Omega$ typical.

RANGE	ACCURACY 23°C ±5°C ±(%output + offset)	TEMPERATURE COEFFICIENT 0°C - 18°C & 28°C - 50°C ±(%output + offset)/°C	RISE TIME Typical (10% to 90%)
2.000000 nA	6.0% + 90mV	0.30% + 7mV	6.1 ms
20.00000 nA	3.0% + 9mV	0.11% + 700μV	6.1 ms
200.0000 nA	6.0% + 90 mV	0.30% + 4mV	395 μs
2.000000 μΑ	3.0% + 9mV	0.11% + 400μV	395 μs
20.00000 μΑ	6.0% + 90 mV	0.30% + 4mV	135 µs
200.0000 μΑ	2.5% + 9mV	0.11% + 400μV	135 μs
2.000000 mA	6.0% + 90mV	0.30% + 4mV	21 µs
20.00000 mA	2.5% + 9mV	0.11% + 400μV	21 μs

¹ The analog output voltage for each channel is referenced to that channel's floating ground.

GENERAL

Typical Noise Floor Measurement Specification⁶

TYPICAL NOISE FLOOR RMS (1 STDEV), 100 SAMPLES

RANGE	0.01 NPLC	0.1 NPLC	1.0 NPLC	10 NPLC
2.000000 nA	2 pA	1 pA	40 fA	15 fA
20.00000 nA	2 pA	1 pA	40 fA	15 fA
200.0000 nA	200 pA	100 pA	2 pA	500 fA
2.000000 μΑ	200 pA	100 pA	2 pA	500 fA
20.00000 μΑ	20 nA	10 nA	200 pA	50 pA
200.0000 μΑ	20 nA	10 nA	200 pA	50 pA
2.000000 mA	2 μΑ	1 μΑ	25 nA	5 nA
20.00000 mA	2 μΑ	1 μΑ	25 nA	5 nA

SOURCE CAPACITANCE: Stable to 10.0nF typical.

INPUT BIAS CURRENT7: 50fA max. @ 23°C.

INPUT VOLTAGE BURDEN8: 4.0mV max

VOLTAGE SOURCE SLEW RATE: 3.0ms/V typical.

COMMON MODE VOLTAGE: 200VDC.

COMMON MODE ISOLATION: Typically 10°Ω in parallel with 150nF.

OVERRANGE: 105% of measurement range.

MEMORY BUFFER: 6000 readings (two 3000 point buffers). Includes selected measured value(s) and time stamp

PROGRAMMABILITY: IEEE-488 (SCPI-1995.0), RS-232, five userdefinable power-up states plus factory default and *RST.

DIGITAL INTERFACE:

Enable: Active low input.

Handler Interface: Start of test, end of test, 3 category bits. +5V @ 300mA supply.

500mA, diode clamped).

POWER SUPPLY: 100V/120V/220V/240V ±10%

LINE FREQUENCY: 50, 60Hz. POWER DISSIPATION: 60VA

WARRANTY: 1 year.

EMC: Complies with European Union Directive 89/336/EEC.

VIBRATION: MIL-T-28800F Random Class 3.

SAFETY: Complies with European Directive 73/23/EEC.

WARM-UP: 1 hour to rated accuracy.

DIMENSIONS: 89mm high \times 213mm wide \times 370mm deep (3½ in \times 8¾ in \times 14% in).

Bench configuration (with handle and feet): 104mm high × 238mm wide \times 370mm deep (4\% in \times 9\% in \times 14\% in).

WEIGHT: 23.1kg (10.5 lbs).

ENVIRONMENT:

Operating: 0°-50°C, 70% R.H. up to 35°C non-condensing. Derate 3% R.H./°C, 35°-50°C.

Storage: -25° to 65°C, non-condensing.

Specifications are subject to change without notice.

HW 4/22/02

LTR REVISIONS APP. DATE DRN. HW **DATE** 4/24/02 27166 Released 4/24/02 Α **CKD** DATE APP. **DATE** 4/24/02



KEITHLEY Keithley Instruments, Inc. Cleveland, Ohio 44139

PART NUMBER SPEC-250X

SPECIFICATIONS

BRUNING 40-21 62198-SBG

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at artisantg.com for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today? (217) 352-9330 | sales@artisantg.com | artisantg.com

