

Leibold 800120V0012

Venting Valve, 24 V DC, G 1/8"



\$550.00

In Stock

Qty Available: 10+

New From Surplus Stock

Open Web Page

<https://www.artisanng.com/97535-3>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

Technical Data

Product: TURBOVAC 450 iX
Part No.: 830071V3300

Inlet connection:	DN 160 ISO-K	
Outlet connection:	DN 25 ISO-KF	
Pumping speed		
N ₂ - Nitrogen:	430 l/s	
Ar - Argon:	400 l/s	
He - Helium:	440 l/s	
H ₂ - Hydrogen:	420 l/s	
Gas throughput		
N ₂ - Nitrogen:	4.5 mbar x l/s	
Ar - Argon:	2.0 mbar x l/s	
He - Helium:	8.0 mbar x l/s	
H ₂ - Hydrogen:	8.0 mbar x l/s	
Compression ratio		
N ₂ - Nitrogen:	1,0 x 10 ¹¹	
Ar - Argon:	1,0 x 10 ¹¹	
He - Helium:	1,0 x 10 ⁸	
H ₂ - Hydrogen:	1,0 x 10 ⁶	
Ultimate pressure:	< 1.0 x 10 ⁻⁸ mbar	< 7.5 x 10 ⁻⁹ Torr
Max. foreline pressure for N ₂ :	10.0 mbar	7.5 Torr
Nominal rotation speed:	60000 min ⁻¹	60000 rpm
Rotational speed adaptation:	50 -100%	
Run -up time:	≈ 5.5 min	
Admissible ambient temperature:	5 - 45°C	41 - 113°F
Standard cooling:	Convection	
Optional cooling	Air / Water	
Cooling water connection:	plug connection for 6x1 hose alternative G 1/8" screw in thread	
Cooling water consumption:	50 - 100 l/h	
Permissible cooling water pressure:	3 - 6 bar	
Permissible cooling water temperature:	15 - 35°C	
Dimensions:	See dimension sheet	
Weight:	≈ 8.2 kg	≈ 18.1 lbs
Noise level:	≤ 44 db(A)	

Technical data are subject to change

Technical Data

Technical data for integrated drive electronics:

Integrated vacuum system controller:	yes
Mains connection:	24/48 V DC \pm 10%
Max. current consumption:	10 A at 24 V DC
Max. power consumption:	240 W
Power consumption at ultimate pressure:	20 W
Interfaces:	RS 485, USB, 15-Pin digital I/O
Protection class:	IP 40

Technical data are subject to change

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanTG.com](https://www.artisanTG.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanTG.com | [artisanTG.com](https://www.artisanTG.com)

