MTL Instruments MTL5082

Resistance Isolator

$685.00

In Stock

Qty Available: 5+

New From Surplus Stock

Open Web Page

https://www.artisantg.com/84464-1

ARTISAN TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisantg.com | artisantg.com

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.

- Critical and expedited services
- In stock / Ready-to-ship
- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

MTL5082 RESISTANCE ISOLATOR

CE

The MTL5082 connects to a 2-, 3-, or 4-wire resistance temperature device (RTD) or other resistance located in a hazardous area, isolates it and repeats the resistance to a monitoring system in the safe area. The module is intended typically (but not exclusively) for use with Pt100 3-wire RTDs. Switches located on top of the module allow selection of 2-, 3-, or 4-wire RTD connection. The MTL5082 should be considered as an alternative, non-configurable MTL5074, for use in RTD applications where a resistance input is preferred or needed instead of 4/20mA. The design is notable for its ease of use and repeatability. The number of wires which can be connected on the safe-area side of the unit is independent of the number of wires which can be connected on the hazardous-area side. The module drives upscale in the case of open-circuit detection.

SPECIFICATION

See also common specification

Number of channels
One

Location of RTD
Zone 0, IIC, T4 hazardous area
Div 1, Group A hazardous location

Resistance source
2-, 3-, or 4-wire* RTDs to BS 1904/DIN 43760 (100Ω at 0°C)
*user selectable by switches located on top of the module (factory set for 3-wire)

Resistance range
10Ω to 400Ω

RTD excitation current
200µA nominal

Output configuration
2, 3 or 4 wires (independent of mode selected for hazardous-area terminals)

Output range
10Ω to 400Ω (from a 100µA to 5mA source)

Temperature drift
±10mΩ/C° typical (0.01%/°C @ 100Ω)

Response time
To within 4% of final value within 1s

Safety drive on open-circuit sensor
Upscale to 420Ω nominal

Transfer accuracy

Input		Output accuracy								
		At excitation current of								
		0.2mA			0.5mA			1 to 5mA		
Temp. °C	Pt100 resist. Ω	Ω	Ω, % Input	°C	Ω	Ω, % input	°C	Ω	Ω, % input	°C
-	10.0	0.25	2.5%	0.65	0.24	2.4%	0.62	0.23	2.3%	0.60
-200	18.5	0.26	1.4%	0.68	0.24	1.3%	0.62	0.23	1.2%	0.60
-100	60.3	0.28	0.5%	0.73	0.24	0.4%	0.62	0.23	0.4%	0.60
0	100.0	0.31	0.3%	0.81	0.24	0.2%	0.62	0.23	0.2%	0.60
100	138.5	0.34	0.2%	0.88	0.24	0.2%	0.62	0.23	0.2%	0.60
200	175.8	0.37	0.2%	0.96	0.25	0.1%	0.65	0.23	0.1%	0.60
400	247.0	0.44	0.2%	1.14	0.26	0.1%	0.68	0.23	0.1%	0.60
600	313.6	0.51	0.2%	1.32	0.27	0.1%	0.70	0.24	0.1%	0.62
-	400.0	0.59	0.1%	1.53	0.28	0.1%	0.73	0.24	0.1%	0.62



Terminal	Function
1	RTD input –ve
3	RTD input +ve
4	3-wire RTD input –ve
5	4-wire RTD input +ve
9	RTD output –ve
10	RTD output +ve
11	RTD output –ve
12	RTD output +ve
13	Supply –ve
14	Supply +ve

LED indicator
Green: one provided for power and status indication

Power requirements, Vs
55mA at 24V
65mA at 20V
45mA at 35V

Maximum power dissipation within unit
1.4W at 24V
1.6W at 35V

Isolation
250V ac between safe- and hazardous-area circuits and power supply

Safety description

Terminals 1 and 3
U_o = 1.1V
I_o = 4mA
P_o = 1mW

These terminals meet clause 5.4 of EN50020 : 1994 'simple apparatus' (U ≤ 1.5V, I ≤ 0.1A, P ≤ 25mW) and can be connected without further certification into any IS loop with open circuit voltage of not more than 10V. For higher voltages contact MTL. See certificate for further details.

Terminals 1 and 3 and 4 and 5
U_o = 6.6V
I_o = 27mA
P_o = 50mW

EUROPE (EMEA) Tel: +44 (0)1582 723633 Fax: +44 (0)1582 422283
AMERICAS Tel: +1 281 571 8065 Fax: +1 281 571 8069
ASIA PACIFIC Tel: +65 6 487 7887 Fax: +65 6 487 7997
E-mail: enquiry@mtl-inst.com **Web site: www.mtl-inst.com**

Aug 2008

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP