

Scalable Network Processor Module



In Stock

Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/69677-2>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.



CPCI-9120

Release Notes

Part Number 6806800A96A

June 2006

Copyright

Copyright 2006 Motorola GmbH

All rights reserved.

Motorola and the stylized M logo are trademarks of Motorola, Inc., registered in the U.S. Patent and Trademark Office.

All other product or service names mentioned in this document are the property of their respective owners.

Notice

While reasonable efforts have been made to assure the accuracy of this document, Motorola GmbH assumes no liability resulting from any omissions in this document, or from the use of the information obtained herein. Motorola reserves the right to revise this document and to make changes from time to time in the content hereof without obligation of Motorola to notify any person of such revision or changes.

Electronic versions of this material may be read online, downloaded for personal use, or referenced in another document as a URL to the Motorola Embedded Communications Computing Web site. The text itself may not be published commercially in print or electronic form, edited, translated, or otherwise altered without the permission of Motorola GmbH.

It is possible that this publication may contain reference to or information about Motorola products (machines and programs), programming, or services that are not available in your country. Such references or information must not be construed to mean that Motorola intends to announce such Motorola products, programming, or services in your country.

Limited and Restricted Rights Legend

If the documentation contained herein is supplied, directly or indirectly, to the U.S. Government, the following notice shall apply unless otherwise agreed to in writing by Motorola, Inc.

Use, duplication, or disclosure by the Government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data clause at DFARS 252.227-7013 (Nov.

1995) and of the Rights in Noncommercial Computer Software and Documentation clause at DFARS 252.227-7014 (Jun. 1995).

Motorola, Inc.

Embedded Communications Computing

2900 South Diablo Way

Tempe, Arizona 85282

Abbreviations

| Abbreviation | Description |
|--------------|-----------------------------------------------------|
| BOOTP | Bootstrap Protocol |
| CO | Central Office |
| CPCI | Compact Peripheral Component Interconnect |
| DHCP | Dynamic Host Configuration Protocol |
| EEPROM | Electrically Erasable Programmable Read Only Memory |
| EXT2 | Second Extended File System |
| FRU | Field Replaceable Unit |
| FTP | File Transfer Protocol |
| GPIO | General Purpose Input Output |
| IPMI | Intelligent Platform Management Interface |
| IXA | Intel Internet Exchange Architecture |
| I2C | Inter Integrated Circuit |
| JFFS2 | Journaling Flash File System, Version 2 |
| KCS | Keyboard Controller Style |
| MAC | Media Access Control |
| MSF | Media Switch Fabric |
| NFS | Network File System |
| OS | Operating System |
| PMC | PCI Mezzanine Card |
| RTC | Real Time Clock |
| SDK | Software Development Kit |
| TFTP | Trivial File Transfer Protocol |

Table of Contents

| | | |
|----------|-----------------------------------------------|-----------|
| 1 | Introduction..... | 7 |
| 1.1 | Purpose of this Document | 7 |
| 1.2 | Readers for this Document | 7 |
| 1.3 | Format of the Delivery | 7 |
| 1.4 | New Features of this Release | 7 |
| 2 | Hardware Release..... | 9 |
| 2.1 | Known Limitations | 9 |
| 3 | Content of the Software Release | 10 |
| 3.1 | Features | 10 |
| 4 | Environment of the SW Release | 12 |
| 4.1 | SW Release Environment and Dependencies | 12 |
| 4.2 | Operating Environment | 12 |

1 Introduction

The IXP/CPCI-9120 is a 6U 4HP CompactPCI Single Board Computer complex based on the Intel® IXP2400 network processor for up to duplex OC-48 or 4 Gbit Ethernet bandwidth applications. IXP/CPCI-9120 has a Processor PMC expansion for expandable control plane processing power, a flexible media interface mezzanine to support different 4 Gigabit Ethernet interfaces. An SRAM expansion mezzanine site for memory expansion or co-processing support is provided.

1.1 Purpose of this Document

This document describes the content of the IXP/CPCI-9120 PICMG 2.16 variant EA release 1.0

The information regarding the environment and the installation procedures are described in the user guides.

1.2 Readers for this Document

Intended readers of this document are customers for the IXP/CPCI-9120.

1.3 Format of the Delivery

The format of delivery is in the form of source code and binaries.

1.4 New Features of this Release

Hardware Features

- The CPCI-9120 is the PSB Variant and it is with RoHS components, except for QDR SRAM.
- The main features are :
 - Single-NPU Intel IXP2400 board at 600 MHz
 - 256 MB SO-DIMM DDRSDRAM with ECC
 - 8 MB QDRSRAM with ECC onboard
 - 8 MB QDRSRAM with ECC on accessory LA-1 mezzanine card
 - 4 MB Boot Flash onboard
 - 16 MB User Flash onboard
 - 2 x PCI GbE MAC or 2 x SPI-3 GbE MAC on MSF mezzanine routed to PICMG 2.16 links.

Redboot Bootloader

- 'exec' command provides support to specify the address location for placing Linux Tags in SDRAM
- Added support for ATAG_INITRD2. This tag will specify the physical address where the Ramdisk is placed to the Linux kernel.
- New commands **ixf_backplane** and **82546_backplane** have been provided
- RedBoot bootloader now supports DHCP.

Linux

- A configuration option has been provided in '**make menuconfig**' to specify the memory start and memory size to be used by Linux kernel.
- The default kernel configuration supports Ramdisk of size up to 32 MB.
- On system bootup, system clock gets synchronized with hardware clock.
- Enabled **cramfs** support
- Ramdisk has been updated to provide support for static IP assignment, FTP, telnet, strace, tcpdump etc.

2 Hardware Release

2.1 Known Limitations

- Non RoHS QDR SRAMs have been mounted on the boards due to non availability of RoHS SRAM part.
- Some of the components are in the process of qualification for W18 Certification.
- The eDVT is undergoing now.

3 Content of the Software Release

3.1 Features

IXP/CPCI-9120 single slot board complex comprises of the following features:

Single-NPU Intel IXP2400 board at 600 MHz
 256 MB SO-DIMM DDRSDRAM with ECC
 8 MB QDRSRAM with ECC onboard
 8 MB QDRSRAM with ECC on accessory LA-1 mezzanine card
 4 MB Boot Flash onboard
 16 MB User Flash onboard
 2 x PCI GbE MAC or 2 x SPI-3 GbE MAC on MSF mezzanine routed to PICMG 2.16 links

The following table lists the main features of the subsystems

| Subsystem Name | Features |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RedBoot Bootloader | <ul style="list-style-type: none"> • Based on RedBoot 1.24 for XScale • Xscale initialization and PCI devices enumeration • Boots Linux and supports tags for OS parameters • BOOTP, DHCP, TFTP support • 2.16 Ethernet links support • XYZ serial modem Protocol • IPMI KCS interface support |
| IPMI | <ul style="list-style-type: none"> • IPMI 1.0 mandatory command sets • Sensor devices support, Event Messages, BMC watchdog, FRU inventory • Integrates with CO 21KX, CO 21K |
| Montavista PE3.1 Linux | <ul style="list-style-type: none"> • Based on 2.4.20 kernel • Serial Console at 9600 Baud Rate • NFS Support for the Root File System • Ramdisk support for the Root File System with support for FTP, telnet, tcpdump, strace etc • Support for Ext2/3, JFFS2 file System • Intel 82546 Dual Ethernet MAC Driver • IPMI KCS style Driver • Watchdog timer support • On-Board MAX6900 RTC Driver • Intel 28F320J3A and 28F128J3A Flash Driver • Intel 82559 PMC Card Support • BOOTP and DHCP Support • I2C Adapter over two wire GPIO • I2C Driver for the AT24C02 serial EEPROM |

| | |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | |
| Intel NPU SDK environment | <ul style="list-style-type: none">• Intel IXA SDK 4.1 Software Framework ported for CPCI-9120• Reference IPv4 forwarding application able to support 4 ports• IXF1104 MAC Driver Support• User utility to provide support for statistics collection for the IXF1104 MAC• User utility to read and program AT24C02 EEPROMS• Support for IO920 MSF Mezzanine card• Reference Application (Microcode) – Forwarding packets between IO920 Mezzanine Card Ports |

4 Environment of the SW Release

4.1 SW Release Environment and Dependencies

Please refer to following documents :

- 1) IXP/CPCI-9120 Reference Guide
- 2) IXP/CPCI-9120 Linux Installation Guide

4.2 Operating Environment

Please refer to following documents:

- 1) IXP/CPCI-9120 Reference Guide
- 2) IXP/CPCI-9120 Linux Installation Guide

Applicable Documents

Third-Party Documents

Not applicable

References :

- 1) IXP/CPCI-9120 Reference Guide
- 2) IXP/CPCI-9120 Linux Installation Guide

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

