

NI PXIe-7820

PXI Digital Reconfigurable I/O Module



Limited Availability
New From Surplus Stock

Open Web Page

<https://www.artisanng.com/95126-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

SPECIFICATIONS

NI PXIe-7820R

R Series for PXI Express Digital RIO with Kintex-7 160T FPGA

Français	Deutsch	日本語	한국어	简体中文
ni.com/manuals				

This document contains the specifications for the NI PXIe-7820R. Specifications are typical at 25 °C unless otherwise noted.



Caution Using the NI PXIe-7820R in a manner not described in this document may impair the protection the NI PXIe-7820R provides.

Digital I/O

Number of connectors.....	4
Number of channels per connector.....	32
Maximum frequency.....	80 MHz
Compatibility.....	LVTTL, LVCMOS
Logic family.....	Software-selectable
Default software setting.....	3.3 V

Table 1. Digital Input Logic Levels

Logic Family	Input Low Voltage (V _{IL}) Max	Input High Voltage (V _{IH}) Min
1.2 V	0.42 V	0.84 V
1.5 V	0.51 V	1.01 V
1.8 V	0.61 V	1.21 V



Table 1. Digital Input Logic Levels (Continued)

Logic Family	Input Low Voltage (V_{IL}) Max	Input High Voltage (V_{IH}) Min
2.5 V	0.70 V	1.60 V
3.3 V	0.80 V	2.00 V

Minimum input.....-0.3 V

Maximum input.....3.6 V

Input leakage current..... $\pm 15 \mu\text{A}$ max

Input impedance.....50 k Ω typ, pull-down

Table 2. Digital Output Logic Levels

Logic Family	Current	Output Low Voltage (V_{OL}) Max	Output High Voltage (V_{OH}) Min
1.2 V	100 μA	0.20 V	1.00 V
1.5 V	100 μA	0.20 V	1.25 V
1.8 V	100 μA	0.20 V	1.54 V
2.5 V	100 μA	0.20 V	2.22 V
3.3 V	100 μA	0.20 V	3.00 V
	4 mA	0.40 V	2.40 V

Maximum DC output current per channel

Source.....4.0 mA

Sink.....4.0 mA

Output impedance.....50 Ω

Power-on state.....Programmable, by line

Protection..... ± 20 V, single line¹

Digital I/O voltage selection.....Programmable, per connector, and defined at compilation (not run-time configurable)

¹ NI recommends minimizing long-term over/under-voltage exposure to the Digital I/O. Prolonged DC voltage stresses that violate the maximum and minimum digital input voltage ratings may reduce device longevity. Over/under-voltage stresses are considered prolonged if the cumulative time in the abnormal condition exceeds 1 year.

Direction control of digital I/O.....	Per channel channels
Minimum I/O pulse width.....	6.25 ns
Minimum sampling period.....	5 ns

External Clock

Direction.....	Input into device
Maximum input leakage.....	±15 µA
Characteristic impedance.....	50 Ω
Power-on state.....	Tristated
Minimum input.....	-0.3 V
Maximum input.....	3.6 V
Logic level.....	Inherited from programmed digital voltage selection per connector
Maximum input frequency.....	80 MHz

Reconfigurable FPGA

FPGA type.....	Kintex-7 160T
Number of flip-flops.....	202,800
Number of LUTs.....	101,400
Embedded Block RAM.....	11,700 kbits
Number of DSP48 slices.....	600
Timebase.....	10, 40, 80, 100, 120, 160, or 200 MHz
Default timebase.....	40 MHz
Timebase reference source.....	PXI Express 100 MHz (PXIe_CLK100)
Timebase accuracy.....	±100 ppm, 250 ps peak-to-peak jitter
Data transfers.....	DMA, interrupts, programmed I/O

Synchronization Resources

Input/output source.....	PXI_Trig<0..7>
Input source.....	PXI_Star, PXIe_DStarA, PXIe_DStarB, PXI_Clk10, PXIe_Clk100, External Clock x
Output source.....	PXIe_DStarC

Bus Interface

Form factor.....	x4 PXI Express, specification v1.0 compliant
Slot compatibility.....	x4, x8, and x16 PXI Express or PXI Express hybrid slots
Data transfers.....	DMA, interrupts, programmed I/O
Number of DMA channels.....	16

Maximum Power Requirements

Power requirements are dependent on the digital output loads and configuration of the LabVIEW FPGA VI used in your application.

+3.3 VDC (±5%).....	3 A
+12 V.....	2 A

Physical Characteristics



Note If you need to clean the device, wipe it with a dry, clean towel.

Dimensions.....	16 cm by 10 cm (6.3 in. by 3.9 in.)
Weight.....	183 g (0.403 lb)
I/O connectors.....	x4 68-pin female high-density VHDCI type

Environmental

Ambient Operating temperature.....	0 °C to 55 °C (IEC 60068-2-1, IEC 60068-2-2)
Ambient Storage temperature.....	-40 °C to 71 °C (IEC 60068-2-1, IEC 60068-2-2)
Operating humidity.....	10% RH to 90% RH, noncondensing (IEC 60068-2-56)
Storage humidity (IEC 60068-2-56).....	5% RH to 95% RH, noncondensing
Pollution Degree.....	2
Maximum altitude.....	2,000 m at 25 °C
Indoor use only.	

Shock and Vibration

Operational shock.....	30 g peak, half-sine, 11 ms pulse (Tested in accordance with IEC 60068-2-27. Meets MIL-PRF-28800F Class 2 limits.)
Random vibration	
Operating.....	5 Hz to 500 Hz, 0.3 g _{rms}
Non-operating.....	5 Hz to 500 Hz, 2.4 g _{rms} (Tested in accordance with IEC 60068-2-64. Meets MIL-PRF-28800F Class 3.)

Safety Standards

This product meets the requirements of the following standards of safety for electrical equipment for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA 61010-1
- EN 60079-0:2012, EN 60079-15:2010
- IEC 60079-0: Ed 6, IEC 60079-15: Ed 4
- UL 60079-0: Ed 5, UL 60079-15: Ed 3
- CSA 60079-0: 2011, CSA 60079-15: 2012



Note For UL and other safety certifications, refer to the product label or the [Online Product Certification](#) section.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class B emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class B emissions
- EN 55022 (CISPR 22): Class B emissions
- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class B emissions
- AS/NZS CISPR 22: Class B emissions
- FCC 47 CFR Part 15B: Class B emissions
- ICES-001: Class B emissions



Note Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



Note For EMC declarations and certifications, and additional information, refer to the *Online Product Certification* section.



Note In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.

CE Compliance

This product meets the essential requirements of applicable European Directives, as follows:

- 2006/95/EC; Low-Voltage Directive (safety)
- 2014/30/EU; Electromagnetic Compatibility Directive (EMC)

Online Product Certification

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for this product, visit ni.com/certification, search by model number or product line, and click the appropriate link in the Certification column.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the *Minimize Our Environmental Impact* web page at ni.com/environment. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

Waste Electrical and Electronic Equipment (WEEE)



EU Customers At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/environment/weee.

电子信息产品污染控制管理办法（中国 RoHS）



中国客户 National Instruments 符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于 National Instruments 中国 RoHS 合规性信息，请登录 ni.com/environment/rohs_china。(For information about China RoHS compliance, go to ni.com/environment/rohs_china.)

Worldwide Support and Services

The National Instruments website is your complete resource for technical support. At ni.com/support, you have access to everything from troubleshooting and application development self-help resources to email and phone assistance from NI Application Engineers.

Visit ni.com/services for NI Factory Installation Services, repairs, extended warranty, and other services.

Visit ni.com/register to register your National Instruments product. Product registration facilitates technical support and ensures that you receive important information updates from NI.


A Declaration of Conformity (DoC) is our claim of compliance with the Council of the European Communities using the manufacturer's declaration of conformity. This system affords the user protection for electromagnetic compatibility (EMC) and product safety. You can obtain the DoC for your product by visiting ni.com/certification. If your product supports calibration, you can obtain the calibration certificate for your product at ni.com/calibration.

National Instruments corporate headquarters is located at 11500 North Mopac Expressway, Austin, Texas, 78759-3504. National Instruments also has offices located around the world. For telephone support in the United States, create your service request at ni.com/support or dial 1 866 ASK MYNI (275 6964). For telephone support outside the United States, visit the *Worldwide Offices* section of ni.com/niglobal to access the branch office websites, which provide up-to-date contact information, support phone numbers, email addresses, and current events.

NI PXIe-7820R Pinout

GND	68	34	GND
External Clock x*	67	33	GND
GND	66	32	GND
DIO0	65	31	DIO1
GND	64	30	GND
DIO2	63	29	DIO3
GND	62	28	GND
DIO4	61	27	DIO5
GND	60	26	GND
DIO6	59	25	DIO7
GND	58	24	GND
DIO8	57	23	DIO9
GND	56	22	GND
DIO10	55	21	DIO11
GND	54	20	GND
DIO12	53	19	DIO13
GND	52	18	GND
DIO14	51	17	DIO15
GND	50	16	GND
DIO16	49	15	DIO17
GND	48	14	GND
DIO18	47	13	DIO19
GND	46	12	GND
DIO20	45	11	DIO21
GND	44	10	GND
DIO22	43	9	DIO23
GND	42	8	GND
DIO24	41	7	DIO25
GND	40	6	GND
DIO26	39	5	DIO27
GND	38	4	GND
DIO28	37	3	DIO29
GND	36	2	GND
DIO30	35	1	DIO31

* x is the connector number.
External Clock x is an input only.



Refer to the *NI Trademarks and Logo Guidelines* at ni.com/trademarks for information on National Instruments trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering National Instruments products/technology, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your media, or the *National Instruments Patent Notice* at ni.com/patents. You can find information about end-user license agreements (EULAs) and third-party legal notices in the readme file for your NI product. Refer to the *Export Compliance Information* at ni.com/legal/export-compliance for the National Instruments global trade compliance policy and how to obtain relevant HTS codes, ECCNs, and other import/export data. NI MAKES NO EXPRESS OR IMPLIED WARRANTIES AS TO THE ACCURACY OF THE INFORMATION CONTAINED HEREIN AND SHALL NOT BE LIABLE FOR ANY ERRORS. U.S. Government Customers: The data contained in this manual was developed at private expense and is subject to the applicable limited rights and restricted data rights as set forth in FAR 52.227-14, DFAR 252.227-7014, and DFAR 252.227-7015.

© 2015 National Instruments. All rights reserved.

376823B-01 Jun15

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

