

DArlean Technology Dross

Limited Availability
Used and in Excellent Condition

Open Web Page

https://www.artisantg.com/71186-4

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisantg.com | artisantg.com

- · Critical and expedited services
- In stock / Ready-to-ship


- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

SWEPT-WAVELENGTH TUNABLE LASER SOURCE

- Fast 100-nm/s tuning speed covering the entire C+L bands
- >70-dB ASE low-noise version for testing high-performance components
- · Icon-based touch-screen interface with detachable control pad
- · Rugged design for 24/7 operation on the manufacturing floor

Designed specifically for high-volume testing of high-performance WDM components, the Model 6528 enables fast, high-resolution, low-noise measurements. This swept-wavelength tunable laser enables characterization of components faster and more precisely than an OSA, over the entire C and L bands.



Optical power transmission through two matched narrow-notch-filter fiber-Bragg-grating reflectors measured with the 6528-LN. The ratio of the signal power to the total integrated ASE background power outside the 0.8-nm filter width is >70 dB. With its 100-nm/s tuning, >70-dB ASE*, and 30-pm open-loop accuracy, you'll be able to observe your component's wavelength response in real time. This ability allows you to observe and measure critical component adjustments during the manufacturing process.

The Model 6528 is designed with a language-independent icon-based interface for easy global deployment. The controls are nearly as easy to use for novice technicians as for experts. With one knob and a touch-screen interface, we've kept the number of "clicks" to a minimum so the operator can quickly and easily program, select, or even step through a series of wavelengths. The revolutionary control pad detaches from the base unit so each user can customize their workplace for optimal convenience and productivity.

* Low-noise version.

The control pad detaches from the base unit so each user can customize their workplace for optimal convenience and productivity.



SPECIFICATIONS

Model #	6528-LN	6528-HP
Tuning Range	1520–1620 nm	
Absolute Wavelength Accuracy ⁽¹⁾	30 pm	
Mode-Hope Performance ⁽²⁾	Mode-Hop Free	
Wavelength Resolution (2.3)	0.1 pm	
Wavelength Repeatability ⁽²⁾	<±2.5 pm	
Wavelength Stability ^(2,4,8)	<5 pm	
Tuning Speed	1–100 nm/s	
Output Power	>+1 dBm (1570–1620 nm) >–1 dBm (1520–1570 nm)	>+6 dBm (1520–1620 nm)
Power Repeatability ^(2,8)	0.05 dB	
Power Stability ^(2,4)	±0.02 dB	
Amplified Spontaneous Emission (ASE)	>70 dB ^(2,5) >90 dB ^(2,6)	>40 dB ^(2,5) >45 dB ⁽⁵⁾ (1540–1620 nm)
Integrated Dynamic Range	>60 dB ^(2,7) >65 dB ^(7,8) (1540–1620 nm)	
Side-Mode Suppression Ratio ^(2,8)	>50 dB	
Control Pad	lcon-Based Touch Screen	
Control Pad Cord Length	4 feet	
Fiber Connector	FC/APC	
Fiber Type	PM (Polarization Maintaining)	
TTL Triggers	2 Settable Triggers	
Computer Interface	IEEE, RS232C, Ethernet, Keyboard, and Mouse	
Operating Temperature	15–35 °C	
Storage Temperature	−20 °C to 70 °C	
Shock/Vibration	ISTB Procedure 2B	
Operating Humidity	90% RH (non-condensing)	
Warm-Up Time	45 minutes	
Size	19" Rack Mount, 3U high	

PRELIMINARY SPECIFICATIONS

 $^{\mbox{\scriptsize (1)}}$ After wavelength recalibration (user-performed function).

(2) Over full wavelength range.

(3) 1 pm in step mode.

(4) 1 hour, temperature ± 2 °C.

 $^{(5)}$ 0.1-nm bandwidth, signal to max ASE, 1–3 nm from carrier.

(6) 0.2-nm bandwidth, signal to max ASE, >5 nm from carrier.

(7) Signal to total ASE >0.5 nm from carrier.

(8) Typical.







Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at artisantg.com for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today? (217) 352-9330 | sales@artisantg.com | artisantg.com

