

Newport 325
Temperature Controller



\$1295.00

In Stock

Qty Available: 1

Used and in Excellent Condition

Open Web Page

<https://www.artisanTG.com/52128-2>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanTG.com | artisanTG.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

300 Series

Temperature Controllers



The **300 Series Temperature Controllers** offer a combination of features, performance, and value that is unmatched by other laser diode temperature controllers.

Three operating modes are user selectable: constant R (thermistor), constant T (IC sensors), or constant I_{TE} (TE cooler), while delivering high output power of up to 50 W.

Quiet, safe output current results from fast hybrid P-I control circuitry. And an I_{TE} current limit setting protects TE coolers from damage, regardless of operating mode.

The system offers multiple sensor capability since it is compatible with thermistors, AD592 Series, and LM335 Series temperature sensors. Direct temperature readings are displayed in °C when using IC sensors.

Additional Benefits

- Preset display lets you adjust operating setpoint before switching the output on
- Low noise, bipolar current output
- Wide TEC temperature range from -50 to +150°C
- Analog interface provides remote control capability

Key Features

- Ultra-stable temperature control ($\pm 0.005^\circ\text{C}$) over a broad temperature range
- TEC is compatible with the most widely-used temperature sensors: thermistors, and AD590/592 and LM135/335 IC sensors
- Two models are offered, covering a wide range of output powers

LASER DIODE TESTING

FIBER OPTICS TEST
INSTRUMENTATIONPOWER METERS
& DETECTORSFIBER ALIGNMENT
& ASSEMBLY

LASERS

FIBER OPTIC
COMPONENTSOPTICAL FIBERS
& ACCESSORIES

Specifications

Model 325/325AN		Model 350/350AN	
Output			
Type	Bipolar, constant current source		
TEC Control Loop Type	Hybrid P-I		
Maximum Current	±2.5 A	±5 A	
Compliance Voltage	<6 V	<10 V	
Available Output Power	15 W	50 W	
Current Limit			
Range	0–2.5 A	0–5 A	
Accuracy	±10 mA	±20 mA	
Ripple/Noise (rms)	<1 mA	<2 mA	
Stability			
Short-Term Stability (1 h)	0.005°C		
Long-Term Stability (24 h)	0.01°C		
Display			
Range			
Temperature	-50.0 to +150.0°C		
Resistance (10 µA)	0.1–199.9 kΩ		
Resistance (100 µA)	0.01–19.99 kΩ		
TE Current	-2.50 to +2.50 A	-5.00 to +5.00 A	
Resolution			
Temperature	0.1°C		
Resistance (10 µA)	100 Ω		
Resistance (100 µA)	10 Ω		
TE Current	10 mA		
Accuracy			
Temperature	±0.2°C		
Resistance (10 µA)	±200Ω		
Resistance (100 µA)	±20Ω		
TE Current	±10	±20	
Temperature Sensors			
Sensor Type	Thermistor NTC 2-wire	AD592CN	LM335AZ
Temperature	0.01°C	0.1°C	0.1°C
Control Resolution			
Temp. Sensor	±0.2°C	±0.5°C	±3.0°C
Control Accuracy (at 25°C)			
Sensor Bias	10/100 µA	+12 V	1 mA

Call Newport's Application Sales Engineers to help you determine which Temperature Controller best meets your LD Cooling requirements.

Specifications

Power Requirements	90 to 125, 180 to 250 VAC, 50 to 60 Hz
Chassis Ground	4 mm Banana jack
Size (H x W x D)	3.5 x 8.5 x 11 in. (88 x 215 x 280 mm)
Weight	6.5 lb. (2.9 kg)
Operating Temperature	0°C to 50°C
Storage Temperature	-40°C to + 70°C
Relative Humidity, Storage	<90% humidity non-condensing
Connectors	
Output Connectors TE Module and Sensor	15-pin female D-sub
Analog Output	Isolated BNC
Analog Interface Connection (Models 300AN)	15-pin, high density D-sub (female)

Analog Interface Card

Inputs

Analog Interface Input ON/OFF	TTL
Analog Interface Input Set Point	R Mode 0 to 2 V; T Mode -0.5 to 1.5 V; I _{TE} Mode (model dependent)

Outputs

Analog Interface Output ON/OFF Status	TTL
Analog Interface Output ERROR Status	TTL
Analog Interface Output MODE Status	TTL
Analog Interface Output LIMIT Status	TTL
Analog Interface Output R/T Monitor	0–2 V (R); -0.5–1.5 V (T)
Analog Interface Output REMOTE ON/OFF	Switch on rear panel, OFF disables input set point line only

Ordering Information

Model	Description
325	Temperature Controller (15 W)
325AN	Temperature Controller (15 W) with analog interface
350	Temperature Controller (50 W)
350AN	Temperature Controller (50 W) with analog interface

Accessories

Model	Description
300-02	Temperature Controller Cable
300-04	TEC/Mount Cable
300-16	10.0 kΩ Thermistor (±0.2°C)
300-22	AD592CN IC Sensor (-45°C to +125°C Range)
35-RACK	Rack Mount Kit

Please see page 68 for Cable Diagrams

Related Products

Newport 300 Series Temperature Controllers are complemented in performance and value by our 500 Series Laser Diode Drivers and our complete line of Temperature Controlled Mounts and Telecom Mounts for laser diodes.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

