

Newport 818-ST

Low-Power Silicon Photodetector



\$295.00

In Stock

Qty Available: 1

Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/62750-4>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

Model 840-C Hand-Held Optical Power Meter



(Detector not included)

- Power and precision typical of a benchtop meter
- Includes both DC and AC peak-to-peak measurement modes
- Power sensitivity from 100 pW to 2 W (-70 to +33 dBm)
- Wavelength and range settings
- Linear, dB, dBm and linear ratio readouts
- Background subtraction and digital averaging

The Model 840-C hand-held optical power meter is fully compatible with all of Newport's 818 Series Low-Power Si, Ge and InGaAs detectors. Detectors connect to the power meter through an in-line calibration module that is dedicated to each detector (see System Specifications Table below for all compatible detectors). These detachable modules provide the Model 840-C with calibration and operating information specific to the assigned detector. Various detector accessories allow for free-space, as well as for fiber coupled power measurements. DC and AC peak-to-peak power measurements can be displayed in units of W and dBm on the instrument's 4 digit, backlit LCD.

Instrument Specifications

Display Type	4-digit LCD w/ backlight
Sampling Rate (Hz)	2.5
Gain Ranges	6 decades, DC; 4 decades, AC Pk-Pk
Full Scale Readings, Low-Power Detector	100 nA–5 mA
DC Accuracy, 100 nA range, full scale	$\pm(0.5\% + 50 \text{ pA})$
DC Accuracy, 1 μA to 5 mA range, full scale	$\pm(0.25\% + \text{offset})$ See Manual
Peak-to-Peak Accuracy, 50 Hz to 1 kHz	Squarewave $\pm 5\%$, Sinewave $\pm 1\%$
Peak-to-Peak Accuracy, 1 kHz to 2 kHz	Squarewave $\pm 1\%$, Sinewave $\pm 2\%$
Peak-to-Peak Accuracy, 2 kHz to 5 kHz	Squarewave $\pm 2\%$, Sinewave $\pm 5\%$
Analog Output Accuracy, 100 nA range	$\pm(2.5\% + 15 \text{ mV})$
Analog Output Accuracy, 1 μA to 5 mA range	$\pm(2\% + 10 \text{ mV})$
Analog Output	BNC, 0–1 V into 1 M Ω
Temperature Coefficient	0.1 x Accuracy/ $^{\circ}\text{C}$
Battery Life	18 hours (backlight on)
Battery	Ni-Cd rechargeable
Wall Power	AC adaptor/Charger
Dimensions (H x W x D) [in. (mm)]	7.2 (183) x 3.0 (76) x 1.5 (38)
Weight [lb (kg)]	1.1 (0.5)
Operating Temperature	0 $^{\circ}\text{C}$ to 50 $^{\circ}\text{C}$, <80% RH
Storage Temperature Range	-25 $^{\circ}\text{C}$ to 60 $^{\circ}\text{C}$, <90% RH

Additional Benefits

- Wavelength selection in 1 nm steps
- Audible tone for no-look tuning
- Rechargeable batteries for full portability
- Travel case included with power meter
- Most recent operating parameters are saved when unit is turned off

System Specifications

The 840-C is compatible with Newport's Ge, Si and InGaAs detectors, allowing both free-space and fiber pigtailed measurements in the 200–1800 nm range. When using 818 Series detectors with the 840-C, a calibration module needs to be attached to the detector (818-xx/CM), assuring the correct reading at any pre-selected wavelength. Newport's new 918D and 918L Series detectors can also be used with the 840-C, in combination with the 818P-DIN adapter.

Model	818-UV/CM	818-SL/CM	818-F-SL	818-ST/CM	818-ST-UV/CM	818-IR/CM 818-F-IR	818-IG/CM	818-IS-1
Material	Silicon	Silicon	Silicon	Silicon	Silicon (UV Enhanced)	Germanium	Indium Gallium Arsenide	InGaAs/Si
Diameter (cm)	1.13	1.13	0.3	1 x 1	1 x 1	0.3	0.3	N/A
Wavelength (nm)	200–1100	400–1100	400–1100	400–1100	200–1100	780–1800	800–1650	400–1650
Power Range[W (dBm) per cm ²]	5 pW to 200 mW (-83 to +23)	1 pW to 2 W (-90 to +33)	1 pW to 2 mW (-90 to +3)	100 pW to 2 W (-70 to +33)	100 pW to 2 W (-70 to +33)	100 pW to 140 mW (-70 to +21.5) ⁽²⁾	1 pW to 140 mW (-90 to +21.5)	100 pW to 200 mW (-70 to +23)
Display Resolution	0.01 dB or dBm							
Display Resolution (pW)	0.1	0.1	0.1	0.1	0.1	10	0.1	0.1
Accuracy (%) ⁽¹⁾	±2	±2	±2	±2	±2	±3	±2	±2.5
Applicable Wavelength Range (nm)	200–1100	400–1100	400–1100	400–1100	200–1100	780–1700	800–1650	400–1650
Linearity (%)	±0.5							
NEP @ 5 Hz and 1 A/W	50 fW/√Hz	50 fW/√Hz	50 fW/√Hz	3 pW/√Hz	3 pW/√Hz	4 pW/√Hz	30 fW/√Hz	3 pW/√Hz ⁽³⁾

1) At calibration temperature maintained to ± 0.2°C, -20 dBm level having 99% encircled energy on detector with no optical attenuator

2) -70 to +3 dBm for 818-F-IR

3) 0.01 A/W for the 818-IS-1

4) Append /220 for 220V version

Ordering Information

Model	Description
840-C ⁽⁴⁾	Hand-held Power Meter
840-C-CAL ⁽⁴⁾	840-C with test data and certificate
840-C/220	Hand-held Power Meter, 220V Version
840-C/220-CAL	840-C with test data and certificate

For more details on Newport's low-power detectors and fiber optic accessories compatible with the 840-C, please see page 1090 thru page 1095.

Call Newport's Application Sales Engineers to help you select the optical detector that best meets your application requirements.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

