MIL-STD-1553 Data Bus Coupler



Limited Availability
New From Surplus Stock

Open Web Page

https://www.artisantg.com/97559-3

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.

- Critical and expedited services
- In stock / Ready-to-ship

- · We buy your excess, underutilized, and idle equipment
- · Full-service, independent repair center



Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisantg.com | artisantg.com

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

Box-Type, Single-Stub Data Bus Coupler



Data Sheet

North Hills manufactures a full line of single-stub couplers for MIL-STD-1553. All four versions of USAF #7822056 are available from stock as are most other devices in our standard box-type DB series. Multiple- stub and in-line couplers are described in separate data sheets.

North Hills couplers provide 55 dB common mode rejection and are fabricated using a hot tinned cold rolled steel case which is solder sealed for superior environmental, EMI and corrosion protection. A full environmental qualification report and source control drawing template are available upon request for select products.



North Hills Model # DB02M01E Box-Type, Single-Stub Data Bus Coupler.

Features:

- 55 dB common mode rejection (CMR)
- High EMI resistance
- All industry standard connectors

Benefits:

- Flight qualified
- All four USAF #7822056 versions
- In stock
- Low cost


Specifications:


| Electrical (All parameters are in accordance with MIL-STD-1553B and Notice 2) | | | | | |
|---|---|--|--|--|--|
| Parameter | Description | | | | |
| Droop | 20% Maximum (250 kHZ) | | | | |
| Overshoot and Ringing | \pm 1.0V Peak (250 kHz square wave with 100 ns max rise and fall) | | | | |
| Common Mode Rejection | -55.0 dB (Min) @ 1 MHz | | | | |
| Fault Protection | $59\Omega \pm 1\%$, 1 Watt per MIL-R-39007 | | | | |
| Turns Ratio | 1:1.41 or 1.0:1.0 | | | | |
| Stub Voltage | 1.0V _{pp} to 14.0V _{pp} transformer coupled | | | | |
| Operating Temperature | -55°C to +125°C | | | | |
| Storage Temperature | -55°C to +150°C | | | | |
| Higher temperature units available. | Specifications subject to change without notice. | | | | |




Technical Drawings


DB0-SERIES







DB12012





NH12824-27/USAF 7822056-XXX





Ordering Information

| Model # | Connector | Mating Connector | Terminator (recomm.) | Weight (g) | Turns Ratio | Case Material | Isolation Resistors (Ω) | Comment |
|----------|--|---|----------------------|------------|----------------|------------------|----------------------------|-------------------------------|
| DB01M01E | Raychem D-621-0012 Female Socket D-602-0127 | Raychem D-621-0011 Male Pin D-602-0126 | | 65 | 1.4:1 | Tinned CRS | 59 | -55 dB CMR |
| DB02M01E | Trompeter BJ71 | Trompeter PL75 | RT500078 | 75 | 1.4:1 | Tinned CRS | 59 | -55 dB CMR |
| DB03M01E | Trompeter BJ371 | Trompeter PL375 | RT600078 | 75 | 1.4:1 | Tinned CRS | 59 | -55 dB CMR |
| DB04M01E | Trompeter BJ3150 | Trompeter PL3155 | RT800078 | 75 | 1.4:1 | Tinned CRS | 59 | -55 dB CMR |
| DB05M01E | Trompeter BJ150 | Trompeter PL155 | RT700078 | 75 | 1.4:1 | Tinned CRS | 59 | -55 dB CMR |
| NH12824 | Trompeter BJ71 | Trompeter PL75 | RT500078 | 65 | 1.0:1 | AL | 59 | Low Cost USAF#7822056-001 |
| NH12825* | Trompeter BJ71 | Trompeter PL75 | | 65 | 1.0:1 | AL | 53.5 | Low Cost USAF#7822056-003* |
| NH12826 | Trompeter BJ71 | Trompeter PL75 | RT500078 | 65 | 1.4:1 | AL | 56.2 | Low Cost USAF#7822056-005 |
| NH12827* | Trompeter BJ71 | Trompeter PL75 | | 65 | 1.4:1 | AL | 56.2 | Low Cost USAF#7822056-007* |
| NH12915 | Trompeter BJ71 | Trompeter PL75 | RT500078 | 65 | 1.4:1 | AL | 59 | Low Cost -55 dB CMR |
| DB12012* | Trompeter BJ71 | Trompeter PL75 | | 75 | 1.4:1 | Tinned CRS | 59 | -55 dB CMR |

^{*}Contains internal 76.8Ω termination resistor.



The information in this Brochure is believed to be accurate; however, no responsibility is assumed by Beta Transformer Technology Corporation for its use, and no license or rights are granted by implication or otherwise in connection therewith. Specifications are subject to change without notice.

For ordering assistance and technical support,

E-Mail: service@BTTC-Beta.com

Visit: BTTC-Beta.com in У f Data Device Corporation

Call: HQ, N.Y., U.S.A (631) 224-7393

UK +44-(0)1635-811140 France +33-(0)1-41-16-3424 Germany +49-(0)89-1500-12-11

Japan +81-(0)3-3814-7688 Asia +65-6489-4801 India +91 80 46797 0368



Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at artisantg.com for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today? (217) 352-9330 | sales@artisantg.com | artisantg.com

