

OMEGA DP26-RTD-R-03

1/8 DIN Size Differential Temperature Meter



Limited Availability
Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/54147-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship
- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

Differential Temperature Meter 1/8 DIN Size

Panel Punches Available, Visit Omega

DP26 Series



- ✓ Temperature Displayed as T1-T2, T1 or T2
- ✓ J, K, T or J DIN Thermocouple Input, User-Selectable
- ✓ Optional Programmable Analog Output
- ✓ Optional 2 Form "C", 5 A Relays—Each Relay Independently Assignable to T1, T2, or T1-T2
- ✓ One-Touch Tuning in Proportional Mode
- ✓ Peak Memory with One-Touch Recall

The DP26 differential temperature meter is a versatile, dual input indicator/controller. The touch of a button toggles the display between T1, T2 and T1-T2. Analog output is optional, using any of the 3 values available. The optional control relays for alarms or on/off control can be tied to T1, T2 or T1-T2. The user can select J, K, T or J DIN thermocouple input from the front panel. The units of measure can be switched between °F and °C with the front panel pushbuttons. The optional analog output can function as retransmission of temperature (assignable to T1, T2, or T1-T2) or be assigned to setpoint #1 and used as a proportional control output. Setpoint #1 will still continue to operate as a setpoint, while the analog output of either 4 to 20 mA or 0 to 10V can be used to proportionally control an external process.

Specifications

Isolation: Dielectric strength to 2500V transient per 3 mm spacing based on EN 61010 for 260 Vrms or DC
NMR: 60 dB
CMR: 120 dB



DP26-TC shown smaller than actual size.

KMTXL-125G-6 6" thermocouple probe, sold separately. Please visit omega for our entire line of probes.

Over voltage: 240 V rms
Display: Red 14-segment LED, 13.8 mm (0.54")
Analog-to-Digital Technique: Dual slope
Internal Resolution: 15-bit
Read Rate: 3/s
Polarity: Automatic
Accuracy: ±0.5°C (0.9°F) above -100°C (-148°F); ±1°C (1.8°F) below -100°C (-148°F)
Span Tempco: ±50 ppm/°C
Step Response: 1 to 2 seconds

Warm-Up to Rated Accuracy: 30 minutes
Relay Outputs (Optional): 2 form "C" (SPDT) on/off relays, max current 5 A, max voltage 250 Vac or 30 Vdc
Analog Output (Optional): 0 to 10V, 4 to 20 mA or 0 to 20 mA; user-selectable
Power: 115 or 230 V±10%; 10 to 32 Vdc; 26 to 56 Vdc; 8 W maximum (optional)
Operating Temperature: 0 to 50°C (32 to 122°F); RH 90% at 40°C (104°F) (non-condensing)
Dimensions: 48 H x 96 W x 152 mm D (1.89 x 3.78 x 6.0")
Panel Cutout: 1/8 DIN, 45 H x 92 mm W (1.77 x 3.62")
Weight: 574 g (1.27 lb)

To Order		
Model No.	Input Type	Range
DP26-TC	J	-210 to 760°C (-346 to 1400°F)
	K	-270 to 1372°C (-454 to 2500°F)
	T	-210 to 400°C (-346 to 752°F)
	J DIN	-200 to 900°C (-328 to 1652°F)
DP26-RTD	100 Ω Pt, 0.00385 2-, 3-, 4-wire	-200 to 850°C (-328 to 1562°F)

Comes complete with operator's manual.
Ordering Example: DP26-TC-GN-AR, differential thermocouple indicator for J, K, T or J DIN inputs, with green display, analog output, dual 5 A relays and 115 Vac power.

Display and Output Options*

Order Suffix	Description
-GN	Green display
-A	Analog output
-R	Dual 5 A relays
-AR	Analog output/dual relays
-AI	Isolated analog output
-AI-R	Isolated analog output/dual relays

Power Options**

Order Suffix	Power
-230	230 Vac
-DC10/32	10 to 32 Vdc
-DC26/56	26 to 56 Vdc

** Not field installable.

* Not field installable. For "-AI" option, the "-R" option is required.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at artisanng.com for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | artisanng.com

