

Thales Optem LampLink2ps
Illuminator with Power Supply



**Limited Availability
Used and in Excellent Condition**

Open Web Page

<https://www.artisanng.com/65079-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.



Markets

What's New

Products

Custom Products

Technical Info

Trade Shows

Company Info

Site Map

Contact

News



The LampLink2 is a specially designed illuminator, which has the features required for today's computer controlled, machine vision applications.

Two models are available, a Power Supply and Non Power Supply. The Power Supply unit has an internal 15V, 3A DC power supply, which is available to provide power to a variety of accessories such as Thales Optem's Motorized Focus Blocks and customer supplied cameras.

Catalog Number	Description
33-50-71	Non Power Supply LampLink2
33-50-72	Power Supply LampLink2
38-51-00	Basic Controller

Features:

- ETL, ECSA and CE Approved
- Switch selectable power source (100, 115 or 230 VAC)
- Microprocessor control of lamp intensity
- Line regulation (No spiking)
- Auto detection of line frequency
- Optional internal 15V, 3A DC power supply
- Computer controllable via the RS232 interface
- Control Software available for Windows and LabVIEW applications
- Internal IR filter for cool operation
- Optional color filtering
- 150 watt halogen lamp available in 3 color temperatures (EKE, EJA & DDL)
- Input static protection
- Thermal Protection against overheating in case of fan failure
- Switch selectable addressing for connecting multiple illuminators
- Controls are optically isolated from the AC source
- Remote intensity control
- Detachable IEC power cord
- Quick and convenient lamp exchange

The LampLink2 has a single cable entry in the front of the illuminator for connections to the controllers.


LampLink2 Specifications:

LampLink 2	Illuminator Specifications:
ENCLOSURE	
Type	Rectangle formed Aluminum with soft plastic feet.
Size	8.25 wide x 9.50 deep x 4.35 high (210 x 241 x 110 mm).


Weight	Single, 8 lb., (3.6 kg).
Color	Cool white with black front panel.
Fiber Receiver	Diameter .721 in.
Cooling	Rear exhaust fan.
REMOTE	
Type	Slope front formed Aluminum with soft plastic feet.
Size	2.0 wide x 3.0 deep x 1.5 high (51x76x38mm) (basic controller).
Weight	0.2 lb., (0.09kg).
Color	Black, fine texture with white lettering.
Control	Rotary rheostat.
Cable	8 ft with RJ-45 termination.
POWER	
Voltage	90-250 VAC, 47/63 Hz. Field selectable by switch (no wiring change).
Current	Maximum. Single 3.1/1.5A.
	Nominal Single 200w, /P units add 50 watts.
Duty Cycle	Continuous.
LAMPS	
	*Life in hours (hr.) is at maximum intensity. Life can be extended up 100x at lower settings.
Standard	EKE 150w, 3250°K, 21v, 200 hr.* order # LEKE-15.
Optional	EJA 150w, 3350°K, 21v, 50 hr.* order # LEJA-15
Optional	DDL 150w, 3150°K, 20v, 500 hr.* order # LDDL-15.
ENVIRONMENT	
Temperature	Operating 65°-100°F (18°-38°C). Storage 35°-120°F (2°-49°C).
Humidity	Operating 20%-50%. Storage 10%-95%.
SHIPPING	Weight 11 lb. (5 kg) Volume 11 x 11 x 11 in., 0.8 cu. ft. (280 x 280 x 280 mm, 0.2 cu. M).
LampLink 2	
POWER SUPPLY, OPTIONAL	
Input	90-264 VAC, 47-63 Hz, 1A RMS, Inrush cold start 20A max. Hold up 12 ms, MTBF 100,000 hr.
Output	15 VDC, Current @ load min. 0, max 3A, Peak 4A. Ripple 150 mv, Regulation 2%.



The Basic Controller is designed to control illumination intensity from a remote source. The Basic Controller is not required, as the LampLink2 can be controlled via a computer only if desired.



The rear view shows the selectable power source of 100, 115 or 230 VAC.



A unique slide-rail mechanism for easy bulb replacement keeps the unit in one piece during bulb maintenance.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

