#### Allen-Bradley 1492-FB3C30-L **Fuse Holder**



\$35.00

In Stock **Qtv Available: 2 Used and in Excellent Condition** 

**Open Web Page** 

https://www.artisantg.com/90251-1

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.

- Critical and expedited services
- In stock / Ready-to-ship

- · We buy your excess, underutilized, and idle equipment
- · Full-service, independent repair center



Your definitive source for quality pre-owned equipment.

**Artisan Technology Group** 

(217) 352-9330 | sales@artisantg.com | artisantg.com

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

# CONTROL CIRCUIT AND LOAD PROTECTION DEVICES

**TECHNICAL DATA** 

Rockwell Automation has Short Circuit Current Ratings on the list of products below per the specific UL Standard and Category Code.

BULLETIN 1489 BULLETIN 1492-CB BULLETIN 1492-FB BULLETIN 1492-GH BULLETIN 1492-GS BULLETIN 1492-MC BULLETIN 1492-SP

These ratings are included in the UL acceptance file of the device and summarized on the UL Certification site per the Category Code for the specific product.

## SHORT CIRCUIT CURRENT RATINGS

Per the requirements of the 2005
National Electric Code (NEC)
and UL508A (effective April 25,
2006), many electrical panels must
be rated for their Short Circuit
Withstand Rating. Analyzing the
SCCR of individual components,
and the associated branch and
feeder overcurrent devices is a
method of determining the SCCR
of an electrical assembly.

UL Standard 508A permits these devices to have a SCCR without any additional testing.

Device	SCCR		
Circuit Breaker	5 kA		
Circuit Breaker With GFCI	5 kA		
Fuse Holder	10 kA		
Supplementary Protector	200 A		

The Allen-Bradley products far exceed those ratings (see page 2).



UL489 CIRCUIT BREAKERS — CAT. CODE DIVQ

UL 508 MANUAL MOTOR STARTERS — CAT. CODE NLRV

UL 1077 SUPPLEMENTARY PROTECTORS — CAT. CODE QVNU2

UL512 FUSE HOLDERS — CAT. CODE IZLT

#### STANDARD PRODUCT

Rockwell Automation has tested a number of the 1492-PD Power Terminal blocks to determine their SCCR related to the new testing requirements. These are the standard Power Terminal Blocks that have been used in Industrial Control Panels.

The new ratings for these blocks permit their continued use in panels where the higher SCCR ratings are required.

HIGH FAULT SCCR RATINGS

- UP TO 200,000 A

CERTIFIED TO UL REQUIREMENTS

STANDARD PRODUCTS



Bulletin Number	Notes	UL508A Category Code	UL File Number	Poles	Current Rating	Max Voltage	SCCR	Application code/notes
1489	Circuit Breaker	DIVQ	E197878	1 pole	0.5 - 25 <sup>®</sup> A 30 - 40 A 0.5 - 25 <sup>®</sup> A	277 VAC 240 VAC	10 kA	
				2, 3 pole	30 - 40 A	480Y/277 VAC 240 VAC	<u> </u>	
1492-CB	When used	NLRV	E14841	1 pole	0.5 - 52A	277 VAC	5 kA	
	as UL508 Manual Motor Controller			2, 3 pole		480Y/277 VAC		
	Supplementary	QVNU2	E65138	1, 2, 3 pole	0.5 - 50 A	125 VAC	10 kA	U2
	Protector			1 + N pole 3 + N pole		240 VAC	5 kA	U2
				3 + 14 hous		480Y/277 VAC	3 kA	U2
		3		4		480Y/277 VAC	5 kA	U1
1492-FB	Fuse holder	IZLT	E34648	1, 2, 3 pole	0.1 - 30 A	1492-FB	200 kA (*)	Type CC & J (*) Interrupt rating of fuse
					35 - 60 A			Type J  (*) Interrupt rating of fuse
					0.1 - 30 A		(*)	Type M (*) Interrupt rating of fuse
			-65	15%		S		sevicetic site to
192-GH	Supplementary Protector	QVNU2	E65138	1 pole	0.2 - 15 A	250 VAC	1 kA	U1
			T	T				
492-GS	Supplementary	QVNU2	E65138	1 pole	0.2 - 16 A	277 VAC	5 kA	C1 C1
	Protector				20 - 25 A 0.2 - 5 A	-	3 kA 400 A	U1
				A.	6 - 25 A	1	800 A	U1
				2, 3 pole	0.2 - 16 A	480Y/277 VAC	5 kA	C1
				90, 30	20 - 25 A		3 kA	C1
					0.2 - 5 A		400 A	U1
					6 - 25 A	el .	500 A	U1
1492-MC	Circuit Breaker	DIVQ	E197878	1, 2 pole	10 - 60 A	120/240 VAC	10 kA	1492-MCAAnnn
		on which		ore pesso	70 - 100 A		1.5000000	1492-MCBAnnn
				2 pole	15 - 30 A	240 VAC	1	1492-MCAA2Hnn
					40 - 100 A	and the second second	1	1492-MCBA2Hnn
				3 pole	15 - 30 A	240 VAC	1	1492-MCAA3nn
				1 pole	40 - 100 A 15 - 100 A	120 VAC	65 kA	1492-MCBA3nn 1492-MCCA1nn
				1 hois	10-100 A	277 VAC	14 kA	1492-MCCA IIIII
				2 pole	-	240 VAC	65 kA	1492-MCCA2nn
				2,00.0		480Y/277 VAC	14 kA	1 102 1110 01 121111
	Circuit Breaker with Ground			1 pole	15 - 50 A	120VAC	10 kA	1492-MCGA1nn 1492-MCEA1nn
	Fault GFCI and GFEP	8		2 pole	15 - 50 A	120/240 VAC		1492-MCGA2nn 1492-MCEA2nn
	400		244000000000000000000000000000000000000	W				
1492-SP	Supplementary	QVNU2	E65138	1 pole	0.5 - 35 A	277 VAC	10 kA	U2 - B or C trip
	Protector			1 + N pole	40 - 63 A		5 kA	U2 - B or C trip
				2.2 polo	0.5 - 40 A	400V/277VAA	5 kA	U2 - D trip
				2, 3 pole 3 + N pole	0.5 - 35 A	480Y/277 VAC	10 kA	U2 - B or C trip
	1			19 ± 14 hous	40 - 63 A 0.5 - 40 A		5 kA 5 kA	U2 - B or C trip U2 - D trip

(a) Indicates 25 A @ 480Y/277 available November 2006

#### ${\bf www.rockwell automation.com}$

#### Power, Control and Information Solutions Headquarters

Americas: Rockwell Automation, 1201 South Second Street, Milwaukee, WI 53204-2496 USA, Tel: (1) 414.382.2000, Fax: (1) 414.382.4444

Europe/Middle East/Africa: Rockwell Automation, Vorstlaan/Boulevard du Souverain 36, 1170 Brussels, Belgium, Tel: (32) 2 663 0600, Fax: (32) 2 663 0640

Asia Pacific: Rockwell Automation, Level 14, Core F, Cyberport 3, 100 Cyberport Road, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846

Publication CCLP-TD001A-EN-E – September 2006

Copyright ©2006 Rockwell Automation, Inc. All Rights Reserved. Printed in USA.

C1 Indicates that the short-circuit test was conducted with series overcurrent protection that is no greater than 400% of Supplementary Protector or 15 A whichever is greater. Indicates that a recalibration and dielectric

test was not conducted as part of the short-circuit test.
U1 Indicates that the short-circuit test was conducted without series overcurrent protection. Indicates that a recalibration and dielectric test was not conducted as part of the short-circuit test.
U2 Indicates that the short-circuit test was conducted without series overcurrent protection. Indicates that a recalibration and dielectric test was conducted as part of the short-circuit test.

### Artisan Technology Group is an independent supplier of quality pre-owned equipment

#### **Gold-standard solutions**

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

### We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

#### Learn more!

Visit us at artisantg.com for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today? (217) 352-9330 | sales@artisantg.com | artisantg.com

