

Allen-Bradley 440P-COHB03R6
Safety Position Switch



\$75.00

In Stock

Qty Available: 1

Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/82059-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.



Catalog #: 440P-COHB03R6

Bulletin 440P, Small Plastic IEC, Full Switch (Head <(>&<)> Body), Offset Hinge, Slow Acting, 3NC Circuits, 6-Pin AC M12 Quick Disconnect

Lifecycle status: **ACTIVE**

Technical Specifications

Electrical

Number of contacts as normally closed contact	3
Number of contacts as normally open contact	0
With status indication	No
Type of electric connection	Other
Utilization category	0600/DC-13
Three-circuit 6-pin micro connector current	2 A @ 30V DC
Switching current, min	25 mA @ 5V DC
Auxiliary contacts	1NO (with 2 NC)
Contact current rating (Ie)	6 A @ 120V AC (Ue)
Thermal current (Ith)	10 A
Actuation speed, min	100 mm/min
Actuation speed, max	250 mm/s
Actuation frequency, max	6000 ops/hr
Rated insulation voltage	600V AC

Mechanical

Suitable for safety functions	Yes
Forced opening	Yes
Degree of protection (NEMA)	1
Material housing	Plastic
Degree of protection (IP)	IP66

Number of pins	6-pins
Contact type	Break before make
Enclosure color	Red
Mounting	2 x M4, any position
Body style	22 mm small plastic body
Width	31 mm
Height	103 mm
Actuator type	Offset hinge
Mechanical life operations	10000000 operations with no electrical load
Housing material	UL approved glass-filled polybutylene terephthalate
Connection type	AC micro
Construction type housing	Cuboid

Construction

Depth	31 mm
Actuator material	Various polymers and metals

Environmental

Operating temperature	-25 °C
Safety contacts	1 NC snap acting, 2 NC, 3 NC or 4 NC slow acting
Pollution degree	3
Shock	IEC 60068-2-7(30 Gn 3 pulses per axis)
Vibration	IEC 60068-2-6(10...55 Hz, 0.35 mm amplitude)

Documentation

For all available documentation, please see the [literature results](#).



Copyright ©2022 Rockwell Automation, Inc.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanTG.com](https://www.artisanTG.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanTG.com | [artisanTG.com](https://www.artisanTG.com)

