Potter & Brumfield PM-17DY-24 Power Relay



Limited Availability
Used and in Excellent Condition

Open Web Page

https://www.artisantg.com/72828-1

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.

- Critical and expedited services
- In stock / Ready-to-ship

- · We buy your excess, underutilized, and idle equipment
- · Full-service, independent repair center

ARTISAN'

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisantg.com | artisantg.com

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.



POWER RELAYS

S86/S87 Series Power Relays

	Coil			Contacts	
Mfr.'s Type	Input	Res In Ohms	Nom. Power	Arrange- ment	Amp Rating
Enclosed Relay			•		
KAP-5AG-120	120	2,250	2VA	SPDT	10
KAP-5AY-24	24	472	1.2W	SPDT	10
KAP-11AY-24	24	85	2VA	DPDT	5
KAP-11AY-120	120	2.250	2VA	DPDT	10
KAP-11AG-24	24	85	1.2W	DPDT	5
KAP-11AG-120	120	2,250	1.2W	DPDT	10
KAP-11DY-12	12	120	2VA	DPDT	5
KAP-11DY-24	24	472	2VA	3PDT	10
KAP-11DY-110	110	10.000	1.2W	3PDT	5
KAP-11DG-24	24	472	1.2W	3PDT	10
KAP-11DG-110	110	10.000			
KAP-14AY-120	120	2.250			
KAP-14AG-120	120	2,250			
KAP-14DY-24	24	472			
KAP-14DG-12	12	120			
KAP-14DG-24	24	472			

KAP-5DG-24 "P" denotes polycarbonate cover with octal-style plug.

"A" denotes AC coil KAP-5AG-24 KAP-5DG-24 "D" denotes DC coil

KA-5AY-24 "Y" denotes Ag contacts KA-5AG-24 "G" denotes AgCdO contacts

Note: Open style KArelays mount via a # 6-32 threaded stud and a locating tab on .438 centers Tab requires .165" dia. clearance hole.
Enclosed KAP relays have a seated height of 2.281" and are 1.531" wide and

KUHP Series Power Relays

- FEATURES 20-30Arating
- **Enclosed Case**
- Various mounting options
- 3,750Vrms coil-to contact breakdown
- Class B coil construction
- Approximate Size 1.53" x 1.41" x 1.97"h

Mounting Options: Panel Mount, side or top mount



		Coil	Coil Con		
Mfr.'s Type	Input	Res In Ohms	Nom. Power	Arrange- ment	Amp Rating
Enclosed Relay		•			
KUHP-5A51-24	24	72	2.7VA	SPDT	30
KUHP-5A51-120	120	1,700			
KUHP-5AT1-120	124	1,700	2.7VA	SPDT	30
KUHP-5D51-12	12	120	1.2W	SPDT	30
KUHP-5D51-24	24	472			
KUHP-5DT1-12	12	120	1.2W	SPDT	30
KUHP-5DT1-24	24	472			
KUHP-11A51-24	24	72	2.7VA	DPDT	20
KUHP-11AT1-120	120	1,700	2.7VA	DPDT	20
KUHP-11D51-12		120	1.2W	DPDT	20
KUHP-11D51-24		472			
KUHP-11DT1-12	12	120	1.2W	DPDT	30
KUHP-11DT1-24	24	472			
IZLUID 44 A E4 O4	A -	A O !I			·

KUHP-11A51-24 'A" denotes AC coil KUHP-11D51-24 "D" denotes DC coil

KUHP-11A51-120 "5" denotes side mtg. brackets. Mounts on 2.5" centers KUHP-11AT1-120 "T" denotes top mtg. brackets. Mounts on 1.875" centers

FEATURES

- 20Arating
- Compact package
- Choice of two mounting brackets
- Class B coil construction
- Approximate Size 2.42" x 2.07" x 1.31"h Mounting Options: Panel Mount



		Coil		Con	tacts
Mfr.'s Type	Input	Res In Ohms	Nom. Power	Arrange- ment	Amp Rating
S86R5A1B1D1-120	120	800	4.0VA	SPDT	20
S87R5A2B1D1-24	24	32			
S87R5A2B1D1-120	120	800	4.0VA	SPDT	20
S87R5A2B1D1-240		3,200			
S87R5D2B1D1-12	12	50	2.9W	SPDT	20
S87R5D2B1D1-24	24	200			
S86R11A1B1D1-120	120	800	4.0VA	DPDT	20
S87R11A2B1D1-24	24	32			
S87R11A2B1D1-120	120	800	4.0VA	DPDT	20
C07D11A2D1D1 240	240	3 200		1	

S87R11D2B1D1-24 S86R5A1B1D1-120 S87R5D2B1D1-24

"A" denotes AC coil

"D" denotes DC coil

S86 and S87 have identical electrical specifications, but their mounting dimensions and terminal locations differ.

128

PM Series Power Relays

24

FEATURES

- 25Arating
- 4PDT Arrangement
- High dielectric Strength
- Screw or quick connect terminals
- Approximate Size 3.39" x 2.66" x 2.72"h

Mounting Options: Panel Mount .



DPDT

20

4.5W

		Coil		Con	tacts
Mfr.'sType	Input	Res In Ohms	Nom. Power	Arrange- ment	Amp Rating
PM17AY-24	24	5			
PM17AY-120	120	120	14VA	4PDT	25
PM17AY-240	240	587			
PM-17DY-12	2	33			
PM-17DY-24	24	132	4.4W	4PDT	25
PM-17DY-110	110	2,760			
PMT17DY-24	24	132	4.4W	4PDT	25

PM -17DY-24 "PM denotes screw terminal type


PMT-17DY-24 "PMT" denotes .25" quick connect terminal type


PM Dust Covers

Mfr.'s Type	Description	Length	Width	Height
35D203	Plastic Cover	3.394 (86.21)	2.657 (67.49)	2.791 (69.06)
35D227	Metal Cover	5.313 (134.95)	3.831 (96.85)	3.813 (96.85)

35D227

35D203





Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at artisantg.com for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today? (217) 352-9330 | sales@artisantg.com | artisantg.com

