

DSPCon 9842-110

32-Channel, 16-Bit, 200 kHz A/D Converter, High-Performance Data Acquisition Module



© Artisan Technology Group

In Stock

Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/95115-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com


- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

Search:

GO



My KSI

[Sitemap](#) [About KSI](#) [Products](#) [Applications](#) [News](#) [Support](#) [Custom Solutions](#) [Contact Us](#)
Model 9842**32-channel, 16-bit, 256 kHz A/D Converter****Low cost-per-channel, High-performance Data Acquisition**

The Model 9842 VME board is a Sigma/Delta A/D Converter that offers sampling rates to 256kHz, built-in signal conditioning; and a built-in, optional, user-programmable, TMS320C6416, 2400 MMAC DSP (digital signal processor) for real-time decimation and filtering. The 9842's Xilinx XC2V1000 has 40 built-in, single-cycle, 18-bit multipliers. The board also has a Direct Digital synthesizer for sample rate generation that allows ultra-fine (.001Hz) adjustment capability.

This versatile converter can be used in a variety of applications, including high-frequency sonar, beam forming, speech processing, and acoustic/vibration analysis. The Model 9842 allows users to upgrade current systems to a higher bandwidth, while keeping the same system configuration.

[Features](#)[Specifications](#)[Ordering Information](#)**Features**

- Up to 256 kHz sampling rate; simultaneous on all channels.
- External clock connector
- 16-bit resolution with 90 dB signal-to-noise performance
- Integral linear-phase, anti-aliasing filters
- Differential inputs
- Built-in temperature sensor
- Direct digital synthesizer for sample clock

Specifications

SNR	>94dB
SFDR	>98dB
SINAD	>92dB
Inter-Channel Skew	Better than 50ns
Max Sample Rate	256 Ksamples/second/channel
Input Slew Rate	15V/uSec
Frequency Response	+/- 0.1 dB, DC to 90 kHz
Input Range	Differential inputs +/-10v @ gain of 1
Input Impedance	100 Kohms
Input Anti-aliasing Filter	2 pole Butterworth, Fc at 320 kHz Sigma/Delta filter, Fc at 0.4535 Fs
Input channels	1-32, software programmable
Input connectors	2 DB-37s, 1 BNC for external clock
FIFO	32 Ksample deep FIFO with half-full, empty and full status interrupt capability
Power Consumption	3 amps @ +5V .8 amps @ +/-12V
Programmable Gain	1, 10, 100
A/D conversion	AKM5394A
A/D output coding	16-bit 2's complement
Sampling rates	1k-200k @ .001Hz increments
VME Interface	3 row A16D16 for control A32D64 for data FIFO
MIX interface	32-bit transfers.
Operating Temp	0-60C

Ordering Information

Options:

- 001 MIXbus
- 002 VMEbus
- 003 TMS320C6416 DSP Option
- 004 Gain Option 1, 10, 100
- 005 Direct Digital Synthesizer (Internal Clock)
- 006 Temperature Sensor

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanTG.com](https://www.artisanTG.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanTG.com | [artisanTG.com](https://www.artisanTG.com)

